



SITOR cylindrical fuse link, 10 x 38 mm, 6 A, aR, Un AC: 600 V, Un DC: 700 V, DC according to UL

Figure similar

| Model | |
|---|--------------------------|
| product brand name | SENTRON |
| product designation | SITOR fuse link |
| design of the product | DC acc. to UL |
| General technical data | |
| operating class of the fuse link | aR |
| type of voltage of the operating voltage | AC |
| supply voltage at DC | 700 V |
| Dissipation | |
| power loss [W] | 1.5 W |
| power loss [W] for rated value of the current at AC in hot operating state per pole | 2 W |
| Main circuit | |
| operational current rated value | 6 A |
| Product details | |
| product component striker | No |
| Mechanical Design | |
| mounting position | Any, preferably vertical |
| Net Weight | 9 g |
| Approvals Certificates | |
| General Product Approval | other |



| other | Environment |
|------------------------------|---|
| Confirmation | Environmental Confirmations |
| | Environmental Confirmations |

| Further information |
|--|
| Information on the packaging https://support.industry.siemens.com/cs/ww/en/view/109813875 |
| Information for data generation and storage https://support.industry.siemens.com/cs/ww/en/view/109995012 |
| Information- and Downloadcenter (Catalogs, Brochures,...) |

<https://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3NC1006>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3NC1006>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)


https://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3NC1006

CAX-Online-Generator

<https://www.siemens.com/cax>

Tender specifications

<https://www.siemens.com/specifications>



last modified:

11/14/2025 