



evaluation unit for full motor protection (monostable) for IO-Link frame size S00...S12, class 5...30 stand-alone installation main circuit: -- auxiliary circuit: spring-loaded terminal manual-automatic RESET

<b>product brand name</b>	SIRIUS
<b>product designation</b>	Electronic overload relay for IO-Link
<b>product type designation</b>	3RB24
<b>General technical data</b>	
<b>size of overload relay</b>	S00 ... S12
<b>size of contactor can be combined company-specific</b>	S00 ... S12
<b>power loss [W] for rated value of the current at AC in hot operating state</b>	0.5 W
• per pole	0.17 W
<b>insulation voltage with degree of pollution 3 at AC rated value</b>	300 V
<b>surge voltage resistance rated value</b>	4 kV
<b>shock resistance according to IEC 60068-2-27</b>	15g / 11 ms
<b>reference code according to IEC 81346-2</b>	F
<b>Substance Prohibittance (Date)</b>	05/28/2009
<b>SVHC substance name</b>	Lead - 7439-92-1 Lead monoxide (lead oxide) - 1317-36-8 2,2',6,6'-tetrabromo-4,4'-isopropylidenediphenol - 79-94-7 6,6'-di-tert-butyl-2,2'-methylenedi-p-cresol - 119-47-1
<b>Weight</b>	0.261 kg
<b>Ambient conditions</b>	
<b>installation altitude at height above sea level maximum</b>	2 000 m
<b>ambient temperature</b>	
• during operation	-25 ... +60 °C
• during storage	-40 ... +80 °C
• during transport	-40 ... +80 °C
<b>relative humidity during operation</b>	100 %
<b>Main circuit</b>	
<b>number of poles for main current circuit</b>	3
<b>adjustable current response value current of the current-dependent overload release</b>	0.3 ... 630 A
<b>operating frequency rated value</b>	50 ... 60 Hz
<b>operational current rated value</b>	630 A
<b>Auxiliary circuit</b>	
<b>number of NO contacts for auxiliary contacts</b>	1
<b>number of CO contacts for auxiliary contacts</b>	1
<b>operational current of auxiliary contacts at AC-15</b>	
• at 24 V	6 A
• at 125 V	6 A
• at 230 V	3 A
<b>operational current of auxiliary contacts at DC-13</b>	
• at 24 V	2 A
• at 60 V	0.55 A

<ul style="list-style-type: none"> <li>• at 125 V</li> <li>• at 220 V</li> </ul>	0.3 A 0.2 A
<b>Protective and monitoring functions</b>	
<b>trip class</b>	CLASS 5, 10, 20 and 30 adjustable
<b>UL/CSA ratings</b>	
<b>contact rating of auxiliary contacts according to UL</b>	B300 / R300
<b>Short-circuit protection</b>	
<b>design of the fuse link</b>	fuse gG: 6 A
<ul style="list-style-type: none"> <li>• for short-circuit protection of the auxiliary switch required</li> </ul>	
<b>Installation/ mounting/ dimensions</b>	
<b>mounting position</b>	any
<b>fastening method</b>	stand-alone installation
<b>height</b>	113 mm
<b>width</b>	45 mm
<b>depth</b>	95 mm
<b>required spacing</b>	
<ul style="list-style-type: none"> <li>• with side-by-side mounting <ul style="list-style-type: none"> <li>— forwards</li> <li>— backwards</li> <li>— upwards</li> <li>— downwards</li> <li>— at the side</li> </ul> </li> </ul>	
<ul style="list-style-type: none"> <li>— forwards</li> </ul>	
<ul style="list-style-type: none"> <li>— backwards</li> </ul>	
<ul style="list-style-type: none"> <li>— upwards</li> </ul>	
<ul style="list-style-type: none"> <li>— downwards</li> </ul>	
<ul style="list-style-type: none"> <li>— at the side</li> </ul>	
<ul style="list-style-type: none"> <li>• for grounded parts <ul style="list-style-type: none"> <li>— forwards</li> <li>— backwards</li> <li>— upwards</li> <li>— at the side</li> <li>— downwards</li> </ul> </li> </ul>	
<ul style="list-style-type: none"> <li>— forwards</li> </ul>	
<ul style="list-style-type: none"> <li>— backwards</li> </ul>	
<ul style="list-style-type: none"> <li>— upwards</li> </ul>	
<ul style="list-style-type: none"> <li>— at the side</li> </ul>	
<ul style="list-style-type: none"> <li>— downwards</li> </ul>	
<ul style="list-style-type: none"> <li>• for live parts <ul style="list-style-type: none"> <li>— forwards</li> <li>— backwards</li> <li>— upwards</li> <li>— downwards</li> <li>— at the side</li> </ul> </li> </ul>	
<ul style="list-style-type: none"> <li>— forwards</li> </ul>	
<ul style="list-style-type: none"> <li>— backwards</li> </ul>	
<ul style="list-style-type: none"> <li>— upwards</li> </ul>	
<ul style="list-style-type: none"> <li>— downwards</li> </ul>	
<ul style="list-style-type: none"> <li>— at the side</li> </ul>	
<b>Connections/ Terminals</b>	
<b>product component removable terminal for auxiliary and control circuit</b>	Yes
<b>type of electrical connection</b>	spring-loaded terminals
<ul style="list-style-type: none"> <li>• for auxiliary and control circuit</li> </ul>	
<b>type of connectable conductor cross-sections</b>	
<ul style="list-style-type: none"> <li>• for auxiliary contacts <ul style="list-style-type: none"> <li>— solid or stranded</li> <li>— finely stranded with core end processing</li> <li>— finely stranded without core end processing</li> </ul> </li> </ul>	
<ul style="list-style-type: none"> <li>— solid or stranded</li> </ul>	
<ul style="list-style-type: none"> <li>— finely stranded with core end processing</li> </ul>	
<ul style="list-style-type: none"> <li>— finely stranded without core end processing</li> </ul>	
<ul style="list-style-type: none"> <li>• for AWG cables for auxiliary contacts</li> </ul>	
<b>Safety related data</b>	
<b>failure rate [FIT] with low demand rate according to SN 31920</b>	2 310 FIT
<b>Electrical Safety</b>	
<b>protection class IP on the front according to IEC 60529</b>	IP20
<b>touch protection on the front according to IEC 60529</b>	finger-safe, for vertical contact from the front
<b>Approvals Certificates</b>	
<b>General Product Approval</b>	EMV



EMV

For use in hazardous locations

Test Certificates

other



Environment

[Environmental Confirmations](#)

Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information for data generation and storage

<https://support.industry.siemens.com/cs/ww/en/view/109995012>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RB2483-4AC1>

Cax online generator

<https://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RB2483-4AC1>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RB2483-4AC1>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

[https://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3RB2483-4AC1&lang=en](https://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RB2483-4AC1&lang=en)

Characteristic: Tripping characteristics, I<sub>t</sub>, Let-through current

<https://support.industry.siemens.com/cs/ww/en/ps/3RB2483-4AC1/char>

Further characteristics (e.g. electrical endurance, switching frequency)

<https://www.automation.siemens.com/bilddb/index.aspx?view=Search&mlfb=3RB2483-4AC1&objecttype=14&gridview=view1>



