



SIRIUS motor starter M200D technology module direct-on-line starter electronic switching AC-3, 0.75 kW/400 V 0.15 A...2.00 A electronic overload protection thermistor: thermoclock / PTC without brake contact 4 DI / 2 DO Han Q4/2 - Han Q8/0 with manual on-site operation and keyswitch via communications module 3RK1305* can be used on PROFIBUS or PROFINET

product brand name	SIRIUS
product designation	Motor starters
design of the product	direct starter
product type designation	M200D
product function	
• on-site operation	Yes
• control circuit interface to parallel wiring	No
insulation voltage rated value	500 V
degree of pollution	3
surge voltage resistance rated value	6 000 V
maximum permissible voltage for protective separation	
• between main and auxiliary circuit	400 V
• between control and auxiliary circuit	24 V
shock resistance	12g / 11 ms
vibration resistance	7 mm / 2g
type of coordination	1
Substance Prohibition (Date)	07/01/2006
SVHC substance name	Lead - 7439-92-1 Lead monoxide (lead oxide) - 1317-36-8 2,2',6,6'-tetrabromo-4,4'-isopropylidenediphenol - 79-94-7
Weight	3.972 kg
product function	
• direct start	Yes
• reverse starting	No
product component motor brake output	No
product feature	
• brake control with 230 V AC	No
• brake control with 400 V AC	No
• brake control with 24 V DC	No
• brake control with 180 V DC	No
• brake control with 500 V DC	No
product extension braking module for brake control	No
product function short circuit protection	Yes
design of short-circuit protection	circuit-breakers
maximum short-circuit current breaking capacity (Icu)	
• at 400 V rated value	50 000 A
• at 500 V rated value	20 000 A
EMC emitted interference according to IEC 60947-1	CISPR11, ambience A (group 2)
EMC immunity according to IEC 60947-1	corresponds to degree of severity 3, ambience A (industrial sector)
conducted interference	
• due to burst according to IEC 61000-4-4	2 kV network connection / 1 kV control connection

- due to conductor-earth surge according to IEC 61000-4-5
- due to conductor-conductor surge according to IEC 61000-4-5

2 kV
1 kV

Safety related data

proportion of dangerous failures

- with low demand rate according to SN 31920 50 %
- with high demand rate according to SN 31920 75 %

B10 value with high demand rate according to SN 31920 1 000 000

failure rate [FIT] with low demand rate according to SN 31920 100 FIT

IEC 61508

T1 value for proof test interval or service life according to IEC 61508 20 a

Electrical Safety

touch protection against electrical shock finger-safe

Main circuit

number of poles for main current circuit 3

design of the switching contact solid-state / thyristor / 2 phases

adjustable current response value current of the current-dependent overload release 0.15 ... 2 A

type of the motor protection full motor protection

operating voltage rated value 200 ... 440 V

operational current

- at AC at 400 V rated value 2 A
- at AC-3 at 400 V rated value 2 A

operating power

- at AC-3
 - at 400 V rated value 0.75 kW
 - at 500 V rated value 750 W
- at AC-3e
 - at 400 V rated value 1 kW
 - at 500 V rated value 0.75 kW

product function

- digital inputs parameterizable Yes
- digital outputs parameterizable Yes

number of digital inputs 4

number of sockets

- for digital output signals 2
- for digital input signals 4

number of digital outputs 2

Supply voltage

type of voltage of the supply voltage DC

supply voltage 1 at DC 24 V

Control circuit/ Control

type of voltage of the control supply voltage DC

control supply voltage 1 at DC rated value 20.4 ... 28.8 V

control supply voltage 1 at DC 20.4 ... 28.8 V

control current at DC

- in standby mode of operation 100 mA
- during operation 600 mA

power loss [W] in auxiliary and control circuit

- in switching state OFF with bypass circuit 2.7936 W
- in switching state ON with bypass circuit 3.2256 W

Response times

ON-delay time 25 ms

OFF-delay time 35 ms

mounting position vertical, horizontal, flat

mounting position recommended horizontal

fastening method screw fixing

height 215 mm

width 294 mm

depth 148 mm

Ambient conditions	
installation altitude at height above sea level maximum	2 000 m
ambient temperature	
• during operation	-25 ... +55 °C
• during storage	-40 ... +70 °C
• during transport	-40 ... +70 °C
relative humidity during operation	10 ... 95 %
protocol is supported	
• PROFIBUS DP protocol	No
• PROFINET protocol	No
design of the interface	
• AS-Interface protocol	No
• PROFINET protocol	No
• PROFIBUS DP protocol	No
product function bus communication	Yes
protocol is supported AS-Interface protocol	No
product function control circuit interface with IO link	No
type of electrical connection	
• for main current circuit	plug according to ISO 23570, HAN Q4/2
• for auxiliary and control circuit	connector
type of electrical connection	
• 1 for digital input signals	M12 socket
• 1 for digital output signals	M12 socket
• 2 for digital input signals	M12 socket
• 3 for digital input signals	M12 socket
• 4 for digital input signals	M12 socket
full-load current (FLA) for 3-phase AC motor at 480 V rated value	1.6 A
yielded mechanical performance [hp]	
• for 3-phase AC motor	
— at 460/480 V rated value	0.7 hp
operating voltage at AC at 60 Hz according to CSA and UL rated value	480 V

Approvals Certificates

General Product Approval	EMV
--------------------------	-----



Test Certificates	other	Environment	Industrial Communication
-------------------	-------	-------------	--------------------------

[Type Test Certificates/Test Report](#)



[Confirmation](#)

[Environmental Confirmations](#)



Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information for data generation and storage

<https://support.industry.siemens.com/cs/ww/en/view/109995012>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RK1395-6KS71-2AD0>

Cax online generator

<https://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RK1395-6KS71-2AD0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RK1395-6KS71-2AD0>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

https://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RK1395-6KS71-2AD0&lang=en



