



AS-i compact module K45 digital 2 x (1 DI/1 DQ), IP67 2 x 1 input/1 output 2 x M12 socket Total current for all inputs and outputs max. 200 mA Supply I/O via U_AS! Mounting plate 3RK1901-2EA00 or 3RK1901-2DA00 is to be ordered separately

General technical data	
design of the product	digital I/O modules for operation in the field, IP65 - K45
Type	2 x (1 input / 1 output)
design of the slave type	standard slave
I/O configuration	3
ID/ID2 code	F/F
Number I/O sockets	2
type of electrical connection of the inputs and outputs	M12 screw-type terminals
AS interface total current input max	270 mA
Total current for all inputs and outputs	200 mA
operating voltage according to AS-Interface specification	26.5 ... 31.6 V
Ground terminal	Using PIN5 on the M12 sockets. Outgoing via flat tab sleeve (2.8 x 0.8 mm form A)
Addressing	front addressing socket
AS interface Connection Polarity reversal protection	built-in
Delivery note	the modules are delivered without mounting plate
Note 2	The maximum current carrying capacity per module for all inputs and all outputs is 200 mA.
Sensor supply	
type of voltage supply for sensor supply	using AS-Interface
input voltage	20 ... 30 V
property of the sensor supply short-circuit and overload resistant	Yes
ampacity of the sensor supply for all inputs	200 mA
<ul style="list-style-type: none"> at ambient temperature 40 °C 	
Inputs	
number of digital inputs	2
type of connection technology	2- and 3-wire technology
Input circuit	PNP transistor
type of voltage of the input voltages	DC
Inputs switching level High min	10 V
input current at digital input	
<ul style="list-style-type: none"> for signal <1> minimum 	
6 mA	
<ul style="list-style-type: none"> with signal <0> maximum 	
1.5 mA	
Inputs sensor supply using AS-Interface	short-circuit and overload resistant
Inputs socket assignment	
<ul style="list-style-type: none"> PIN 1 	
sensor supply L+	
<ul style="list-style-type: none"> PIN 2 	
output	
<ul style="list-style-type: none"> PIN 3 	
sensor supply/outputs L-	
<ul style="list-style-type: none"> PIN 4 	
data input	
<ul style="list-style-type: none"> PIN 5 	
ground terminal	

design of the pin assignment of the inputs	Y assignment
Outputs	
number of digital outputs	2
type of voltage of output voltages	DC
Outputs external power supply 24 V DC	not required
ampacity of the semiconductor output at DC-13 at 24 V	0.2 A
Outputs aggregate current	
• max	0.2 A
type of switching output	PNP transistor
design of the pin assignment of the outputs	Y assignment
Outputs socket assignment	3 = "-", 2 = output, 5 = ground terminal
Outputs	
• short-circuit protection	built-in
• induction protection	built-in
• watchdog	built-in

Display	
Status display	
• display of I/Os	yellow LED
• display of Uaux	not required
• display of AS-Interface/diagnostics	green/red dual LED

Assignment of the data bits	
Assignment of data bits	
• socket	PIN 4 = IN1 (D0), PIN 2 = OUT3 (D2)
• socket 2	not available
• socket 3	not available
• socket 4	PIN 4 = IN2 (D1), PIN2 = OUT4 (D3)

Ambient conditions	
ambient temperature	
• during operation	-25 ... +85 °C
• during storage	-40 ... +85 °C
protection class IP	IP67

Mechanical data	
width	45 mm
height	80 mm
depth	30 mm
fastening method	standard rail mounting/wall mounting using mounting plate for K45 compact module
shock resistance	15g / 11 ms

Certificates/ approvals		
General Product Approval	EMV	Test Certificates



EG-Konf.



UL



RCM

[Special Test Certificate](#)

Maritime application	other
-----------------------------	--------------



[Confirmation](#)

[Miscellaneous](#)

Environment	Industrial Communication
--------------------	---------------------------------

[Environmental Conformations](#)



ASi

Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information for data generation and storage

<https://support.industry.siemens.com/cs/ww/en/view/109995012>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RK1400-0GQ20-0AA3>

Cax online generator


<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RK1400-0GQ20-0AA3>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RK1400-0GQ20-0AA3>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RK1400-0GQ20-0AA3&lang=en



last modified:

4/1/2025 