

		Firing PCB 460 V for 3RW4444, 3RW4445	
product designation		Printed circuit board	
product type designation		3RW47	
<b>General technical data</b>			
Substance Prohibitance (Date)		03/01/2017	
SVHC substance name		Lead - 7439-92-1 Lead monoxide (lead oxide) - 1317-36-8	
Weight		0.38 kg	
<b>Approvals Certificates</b>			
General Product Ap- proval	EMV	other	Environment



[KC](#)



[Confirmation](#)

[Environmental Con-  
firmations](#)

### Further information

#### Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

#### Information for data generation and storage

<https://support.industry.siemens.com/cs/ww/en/view/109995012>

#### Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

#### Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RW4745-0VC70>

#### Cax online generator

<https://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RW4745-0VC70>

#### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RW4745-0VC70>

#### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

[https://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3RW4745-0VC70&lang=en](https://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RW4745-0VC70&lang=en)

#### Characteristic: Tripping characteristics, I<sub>t</sub>, Let-through current

<https://support.industry.siemens.com/cs/ww/en/ps/3RW4745-0VC70/char>

#### Characteristic: Installation altitude

<https://www.automation.siemens.com/bilddb/index.aspx?view=Search&mlfb=3RW4745-0VC70&objecttype=14&gridview=view1>

#### Simulation Tool for Soft Starters (STS)

<https://support.industry.siemens.com/cs/ww/en/view/101494917>

last modified:

4/2/2025

