

Control unit 230 V for 3RW4446 with screw terminals



|                               |   |       |             |
|-------------------------------|---|-------|-------------|
| product designation           | Control unit  |       |             |
| product type designation      | 3RW47   |       |             |
| <b>General technical data</b> |   |       |             |
| Substance Prohibance (Date)   | 05/01/2012  |       |             |
| SVHC substance name           | Lead - 7439-92-1<br>Lead monoxide (lead oxide) - 1317-36-8<br>2,2',6,6'-tetrabromo-4,4'-isopropylidenediphenol - 79-94-7<br>Lead titanium zirconium oxide - 12626-81-2<br>6,6'-di-tert-butyl-2,2'-methylenedi-p-cresol - 119-47-1 |       |             |
| Weight                        | 0.779 kg  |       |             |
| <b>Approvals Certificates</b> |   |       |             |
| General Product Approval      | EMV   | other | Environment |



[KC](#)



[Confirmation](#)

[Environmental Confirmations](#)

### Further information

**Information on the packaging**

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

**Information for data generation and storage**

<https://support.industry.siemens.com/cs/ww/en/view/109995012>

**Information- and Downloadcenter (Catalogs, Brochures,...)**

<https://www.siemens.com/ic10>

**Industry Mall (Online ordering system)**

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RW4746-6SC44>

**Cax online generator**

<https://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RW4746-6SC44>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<https://support.industry.siemens.com/cs/ww/en/ps/3RW4746-6SC44>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)**

[https://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3RW4746-6SC44&lang=en](https://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RW4746-6SC44&lang=en)

**Characteristic: Tripping characteristics, I<sup>2</sup>t, Let-through current**

<https://support.industry.siemens.com/cs/ww/en/ps/3RW4746-6SC44/char>

**Characteristic: Installation altitude**

<https://www.automation.siemens.com/bilddb/index.aspx?view=Search&mlfb=3RW4746-6SC44&objecttype=14&gridview=view1>

**Simulation Tool for Soft Starters (STS)**

<https://support.industry.siemens.com/cs/ww/en/view/101494917>

last modified:

4/2/2025



