

External display and control module for SIRIUS soft starter 3RW44 Connecting cable e.g. 2.5 m (3UF7933-0BA00-0) not included in scope of delivery Required firmware version 3RW44 >= *E05*. implemented for starters 3RW44 from delivery date May 2006



product brand name	SIRIUS
product category	Display and operator modules
product designation	External display and control module
design of the product	For indicating and operating the functions provided by the 3RW44 soft starter using an externally mounted display and operator module in degree of protection IP54 (e.g. in the control cabinet door)
product type designation	3RW49

General technical data	
Substance Prohibittance (Date)	07/01/2006
SVHC substance name	Lead - 7439-92-1 Lead monoxide (lead oxide) - 1317-36-8 2,2',6,6'-tetrabromo-4,4'-isopropylidenediphenol - 79-94-7
Weight	0.136 kg

Installation/ mounting/ dimensions	
height	600 mm
width	960 mm
Electrical Safety	
protection class IP on the front according to IEC 60529	IP20
touch protection on the front according to IEC 60529	finger-safe, for vertical contact from the front

Approvals Certificates	
General Product Approval	EMV



[KC](#)

Test Certificates	Maritime application	other
Special Test Certificate	 	  

other	Environment
Confirmation	Environmental Confirmations

Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information for data generation and storage

<https://support.industry.siemens.com/cs/ww/en/view/109995012>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RW4900-0AC00>

Cax online generator

<https://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RW4900-0AC00>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RW4900-0AC00>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

https://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RW4900-0AC00&lang=en

Characteristic: Tripping characteristics, I²t, Let-through current


<https://support.industry.siemens.com/cs/ww/en/ps/3RW4900-0AC00/char>

Characteristic: Installation altitude

<https://www.automation.siemens.com/bilddb/index.aspx?view=Search&mlfb=3RW4900-0AC00&objecttype=14&gridview=view1>


Simulation Tool for Soft Starters (STS)

<https://support.industry.siemens.com/cs/ww/en/view/101494917>



-K1

SIRIUS 3RW



last modified:

4/2/2025 

