

Siemens  
EcoTech



SIRIUS soft starter 200-600 V 171 A, 24 V AC/DC Screw terminals Analog output



|  |  |
|--|--|
| <b>product brand name</b>  | SIRIUS   |
| <b>product category</b>  | Hybrid switching devices   |
| <b>product designation</b>   | Soft starter   |
| <b>product type designation</b>  | 3RW50  |
| <b>manufacturer's article number</b>   |  |
| <ul style="list-style-type: none"> <li>• of standard HMI module usable</li> <li>• of high feature HMI module usable</li> <li>• of communication module PROFINET standard usable</li> <li>• of communication module PROFIBUS usable</li> <li>• of communication module Modbus TCP usable</li> <li>• of communication module Modbus RTU usable</li> <li>• of communication module Ethernet/IP</li> <li>• of circuit breaker usable at 400 V</li> <li>• of circuit breaker usable at 500 V</li> <li>• of the gG fuse usable up to 690 V</li> <li>• of full range R fuse link for semiconductor protection usable up to 690 V</li> <li>• of back-up R fuse link for semiconductor protection usable up to 690 V</li> <li>• of line contactor usable up to 480 V</li> <li>• of line contactor usable up to 690 V</li> </ul> | <ul style="list-style-type: none"> <li><a href="#">3RW5980-0HS01</a></li> <li><a href="#">3RW5980-0HF00</a></li> <li><a href="#">3RW5980-0CS00</a></li> <li><a href="#">3RW5980-0CP00</a></li> <li><a href="#">3RW5980-0CT00</a></li> <li><a href="#">3RW5980-0CR00</a></li> <li><a href="#">3RW5980-0CE00</a></li> <li><a href="#">3VA2220-7MN32-0AA0; Type of assignment 1, Iq = 20 kA</a></li> <li><a href="#">3VA2220-7MN32-0AA0; Type of assignment 1, Iq = 20 kA</a></li> <li><a href="#">3NA3244-6; Type of coordination 1, Iq = 65 kA</a></li> <li><a href="#">3NE1 230-0; Type of coordination 2, Iq = 65 kA</a></li> <li><a href="#">3NE3 335; Type of coordination 2, Iq = 65 kA</a></li> <li><a href="#">3RT1056</a></li> <li><a href="#">3RT1064</a></li> </ul> |
| <b>General technical data</b>  |  |
| <b>starting voltage [%]</b>  | 30 ... 100 %   |
| <b>stopping voltage [%]</b>  | 50 %; non-adjustable   |
| <b>start-up ramp time of soft starter</b>  | 0 ... 20 s   |
| <b>ramp-down time of soft starter</b>  | 0 ... 20 s   |
| <b>current limiting value [%] adjustable</b>   | 130 ... 700 %  |
| <b>certificate of suitability</b>  |  |
| <ul style="list-style-type: none"> <li>• CE marking</li> <li>• UL approval</li> <li>• CSA approval</li> </ul>  | <ul style="list-style-type: none"> <li>Yes</li> <li>Yes</li> <li>Yes</li> </ul>  |
| <b>product component</b>   |  |
| <ul style="list-style-type: none"> <li>• HMI-High Feature</li> <li>• is supported HMI-Standard</li> <li>• is supported HMI-High Feature</li> </ul>   | <ul style="list-style-type: none"> <li>No</li> <li>Yes</li> <li>Yes</li> </ul>   |
| <b>product feature integrated bypass contact system</b>  | Yes  |
| <b>number of controlled phases</b>   | 2  |
| <b>buffering time in the event of power failure</b>  |  |

|   |   |
|---|---|
| <ul style="list-style-type: none"> <li>• for main current circuit</li> <li>• for control circuit</li> </ul>   | 100 ms<br>100 ms  |
| <b>insulation voltage rated value</b>   | 600 V   |
| <b>degree of pollution</b>  | 3, acc. to IEC 60947-4-2  |
| <b>impulse voltage rated value</b>  | 6 kV  |
| <b>blocking voltage of the thyristor maximum</b>  | 1 800 V   |
| <b>service factor</b>   | 1   |
| <b>surge voltage resistance rated value</b>   | 6 kV  |
| <b>maximum permissible voltage for protective separation</b> <ul style="list-style-type: none"> <li>• between main and auxiliary circuit</li> </ul>   | 600 V   |
| <b>shock resistance</b>   | 15 g / 11 ms, from 12 g / 11 ms with potential contact lifting  |
| <b>vibration resistance</b>   | 15 mm to 6 Hz; 2g to 500 Hz   |
| utilization category according to IEC 60947-4-2   | AC-53a  |
| <b>reference code according to IEC 81346-2</b>  | Q   |
| <b>Substance Prohibitance (Date)</b>  | 09/23/2019  |
| <b>SVHC substance name</b>  | Lead - 7439-92-1<br>Lead monoxide (lead oxide) - 1317-36-8<br>2,2',6,6'-tetrabromo-4,4'-isopropylidenediphenol - 79-94-7<br>6,6'-di-tert-butyl-2,2'-methylenedi-p-cresol - 119-47-1<br>2-methyl-1-(4-methylthiophenyl)-2-morpholinopropan-1-one - 71868-10-5  |
| <b>Weight</b>   | 5.878 kg  |
| <b>product function</b> <ul style="list-style-type: none"> <li>• ramp-up (soft starting)</li> <li>• ramp-down (soft stop)</li> <li>• Soft Torque</li> <li>• adjustable current limitation</li> <li>• pump ramp down</li> <li>• intrinsic device protection</li> <li>• motor overload protection</li> <li>• evaluation of thermistor motor protection</li> <li>• auto-RESET</li> <li>• manual RESET</li> <li>• remote reset</li> <li>• communication function</li> <li>• operating measured value display</li> <li>• error logbook</li> <li>• via software parameterizable</li> <li>• via software configurable</li> <li>• <b>PROFenergy</b></li> <li>• voltage ramp</li> <li>• torque control</li> <li>• analog output</li> </ul> | Yes<br>Yes<br>Yes<br>Yes<br>Yes<br>Yes<br>Yes; Electronic motor overload protection<br>No<br>Yes<br>Yes<br>Yes; By turning off the control supply voltage<br>Yes<br>Yes; Only in conjunction with special accessories<br>Yes; Only in conjunction with special accessories<br>No<br>Yes<br>Yes; in connection with the PROFINET Standard communication module<br>Yes<br>No<br>Yes; 4 ... 20 mA (default) / 0 ... 10 V (parameterizable with High Feature HMI) |
| <b>Power Electronics</b>  |   |
| <b>operational current</b> <ul style="list-style-type: none"> <li>• at 40 °C rated value</li> <li>• at 50 °C rated value</li> <li>• at 60 °C rated value</li> </ul>   | 171 A<br>153 A<br>141 A   |
| <b>operating voltage</b> <ul style="list-style-type: none"> <li>• rated value</li> </ul>  | 200 ... 600 V   |
| <b>relative negative tolerance of the operating voltage</b>   | -15 %   |
| <b>relative positive tolerance of the operating voltage</b>   | 10 %  |
| <b>operating power for 3-phase motors</b> <ul style="list-style-type: none"> <li>• at 230 V at 40 °C rated value</li> <li>• at 400 V at 40 °C rated value</li> <li>• at 500 V at 40 °C rated value</li> </ul>   | 45 kW<br>90 kW<br>110 kW  |
| <b>Operating frequency 1 rated value</b>  | 50 Hz   |
| <b>Operating frequency 2 rated value</b>  | 60 Hz   |
| <b>relative negative tolerance of the operating frequency</b>   | -10 %   |
| <b>relative positive tolerance of the operating frequency</b>   | 10 %  |
| <b>adjustable motor current</b> <ul style="list-style-type: none"> <li>• at rotary coding switch on switch position 1</li> <li>• at rotary coding switch on switch position 2</li> </ul>  | 81 A<br>87 A  |

|  |  |
|--|--|
| <ul style="list-style-type: none"> <li>• at rotary coding switch on switch position 3</li> <li>• at rotary coding switch on switch position 4</li> <li>• at rotary coding switch on switch position 5</li> <li>• at rotary coding switch on switch position 6</li> <li>• at rotary coding switch on switch position 7</li> <li>• at rotary coding switch on switch position 8</li> <li>• at rotary coding switch on switch position 9</li> <li>• at rotary coding switch on switch position 10</li> <li>• at rotary coding switch on switch position 11</li> <li>• at rotary coding switch on switch position 12</li> <li>• at rotary coding switch on switch position 13</li> <li>• at rotary coding switch on switch position 14</li> <li>• at rotary coding switch on switch position 15</li> <li>• at rotary coding switch on switch position 16</li> <li>• minimum</li> </ul> | 93 A<br>99 A<br>105 A<br>111 A<br>117 A<br>123 A<br>129 A<br>135 A<br>141 A<br>147 A<br>153 A<br>159 A<br>165 A<br>171 A<br>81 A   |
| <b>minimum load [%]</b>  | 15 %; Relative to smallest settable le   |
| <b>power loss [W] for rated value of the current at AC</b>   |  |
| <ul style="list-style-type: none"> <li>• at 40 °C after startup</li> <li>• at 50 °C after startup</li> <li>• at 60 °C after startup</li> </ul>   | 29 W<br>23 W<br>20 W   |
| <b>power loss [W] at AC at current limitation 350 %</b>  |  |
| <ul style="list-style-type: none"> <li>• at 40 °C during startup</li> <li>• at 50 °C during startup</li> <li>• at 60 °C during startup</li> </ul>  | 1 751 W<br>1 478 W<br>1 308 W  |
| <b>type of the motor protection</b>  | Electronic, tripping in the event of thermal overload of the motor   |
| <b>Control circuit/ Control</b>  |  |
| <b>type of voltage of the control supply voltage</b>   | AC/DC  |
| <b>control supply voltage at AC</b>  |  |
| <ul style="list-style-type: none"> <li>• at 50 Hz rated value</li> <li>• at 60 Hz rated value</li> </ul>   | 24 V<br>24 V   |
| <b>relative negative tolerance of the control supply voltage at AC at 50 Hz</b>  | -20 %  |
| <b>relative positive tolerance of the control supply voltage at AC at 50 Hz</b>  | 20 %   |
| <b>relative negative tolerance of the control supply voltage at AC at 60 Hz</b>  | -20 %  |
| <b>relative positive tolerance of the control supply voltage at AC at 60 Hz</b>  | 20 %   |
| <b>control supply voltage frequency</b>  | 50 ... 60 Hz   |
| <b>relative negative tolerance of the control supply voltage frequency</b>   | -10 %  |
| <b>relative positive tolerance of the control supply voltage frequency</b>   | 10 %   |
| <b>control supply voltage at DC rated value</b>  | 24 V   |
| <b>relative negative tolerance of the control supply voltage at DC</b>   | -20 %  |
| <b>relative positive tolerance of the control supply voltage at DC</b>   | 20 %   |
| <b>control supply current in standby mode rated value</b>  | 160 mA   |
| <b>holding current in bypass operation rated value</b>   | 360 mA   |
| <b>inrush current by closing the bypass contacts maximum</b>   | 7.6 A  |
| inrush current peak at application of control supply voltage maximum   | 3.3 A  |
| duration of inrush current peak at application of control supply voltage   | 12.1 ms  |
| <b>design of the overvoltage protection</b>  | Varistor   |
| <b>design of short-circuit protection for control circuit</b>  | 4 A gG fuse (I <sub>cu</sub> =1 kA), 6 A quick-acting fuse (I <sub>cu</sub> =1 kA), C1 miniature circuit breaker (I <sub>cu</sub> = 600 A), C6 miniature circuit breaker (I <sub>cu</sub> = 300 A); Is not part of scope of supply |
| <b>Inputs/ Outputs</b>   |  |
| <b>number of digital inputs</b>  | 1  |
| <b>number of digital outputs</b>   | 3  |
| <ul style="list-style-type: none"> <li>• not parameterizable</li> </ul>  | 2  |
| <b>digital output version</b>  | 2 normally-open contacts (NO) / 1 changeover contact (CO)  |

|  |  |
|--|--|
| <b>number of analog outputs</b>  | 1  |
| <b>switching capacity current of the relay outputs</b>                                 |  |
| • at AC-15 at 250 V rated value  | 3 A  |
| • at DC-13 at 24 V rated value   | 1 A  |
| <b>Installation/ mounting/ dimensions</b>  |  |
| <b>mounting position</b>   | with vertical mounting surface +/-90° rotatable, with vertical mounting surface +/- 22.5° tiltable to the front and back |
| <b>fastening method</b>  | screw fixing   |
| <b>height</b>  | 198 mm   |
| <b>width</b>   | 120 mm   |
| <b>depth</b>   | 249 mm   |
| required spacing with side-by-side mounting  |  |
| • forwards   | 10 mm  |
| • backwards  | 0 mm   |
| • upwards  | 100 mm   |
| • downwards  | 75 mm  |
| • at the side  | 5 mm   |
| <b>weight without packaging</b>  | 5.2 kg   |
| <b>Connections/ Terminals</b>  |  |
| <b>type of electrical connection</b>   |  |
| • for main current circuit   | busbar connection  |
| • for control circuit  | screw-type terminals   |
| <b>width of connection bar maximum</b>   | 25 mm  |
| <b>type of connectable conductor cross-sections for main contacts for box terminal</b> |  |
| • using the front clamping point solid   | 16 ... 120 mm <sup>2</sup>   |
| • using the front clamping point finely stranded with core end processing              | 16 ... 120 mm <sup>2</sup>   |
| • using the front clamping point finely stranded without core end processing           | 10 ... 120 mm <sup>2</sup>   |
| • using the front clamping point stranded  | 16 ... 70 mm <sup>2</sup>  |
| • using the back clamping point solid  | 16 ... 120 mm <sup>2</sup>   |
| • r box terminal using the back clamping point   | 6 ... 250 kcmil  |
| • using both clamping points solid   | max. 1x 95 mm <sup>2</sup> , 1x 120 mm <sup>2</sup>  |
| • using both clamping points finely stranded with core end processing                  | max. 1x 95 mm <sup>2</sup> , 1x 120 mm <sup>2</sup>  |
| • using both clamping points finely stranded without core end processing               | max. 1x 95 mm <sup>2</sup> , 1x 120 mm <sup>2</sup>  |
| • using both clamping points stranded  | max. 2x 120 mm <sup>2</sup>  |
| • using the back clamping point finely stranded with core end processing               | 16 ... 120 mm <sup>2</sup>   |
| • using the back clamping point finely stranded without core end processing            | 10 ... 120 mm <sup>2</sup>   |
| • using the back clamping point stranded   | 16 ... 120 mm <sup>2</sup>   |
| <b>type of connectable conductor cross-sections</b>                                    |  |
| • for AWG cables for main current circuit solid  | 4 ... 250 kcmil  |
| • for DIN cable lug for main contacts stranded   | 16 ... 95 mm <sup>2</sup>  |
| • for DIN cable lug for main contacts finely stranded                                  | 25 ... 120 mm <sup>2</sup>   |
| <b>type of connectable conductor cross-sections</b>                                    |  |
| • for control circuit solid  | 1x (0.5 ... 4.0 mm <sup>2</sup> ), 2x (0.5 ... 2.5 mm <sup>2</sup> )   |
| • for control circuit finely stranded with core end processing                         | 1x (0.5 ... 2.5 mm <sup>2</sup> ), 2x (0.5 ... 1.5 mm <sup>2</sup> )   |
| • for AWG cables for control circuit solid   | 1x (20 ... 12), 2x (20 ... 14)   |
| <b>wire length</b>   |  |
| • between soft starter and motor maximum   | 800 m  |
| • at the digital inputs at AC maximum  | 1 000 m  |
| <b>tightening torque</b>   |  |
| • for main contacts with screw-type terminals  | 10 ... 14 N·m  |
| • for auxiliary and control contacts with screw-type terminals                         | 0.8 ... 1.2 N·m  |
| <b>tightening torque [lbf·in]</b>  |  |
| • for main contacts with screw-type terminals  | 89 ... 124 lbf·in  |
| • for auxiliary and control contacts with screw-type terminals                         | 7 ... 10.3 lbf·in  |

| Ambient conditions  |   |
|---|---|
| installation altitude at height above sea level maximum   | 5 000 m; Derating as of 1000 m, see catalog   |
| <b>ambient temperature</b>  |   |
| <ul style="list-style-type: none"> <li>during operation</li> <li>during storage and transport</li> </ul>  | -25 ... +60 °C; Please observe derating at temperatures of 40 °C or above<br>-40 ... +80 °C   |
| <b>environmental category</b>   |   |
| <ul style="list-style-type: none"> <li>during operation according to IEC 60721</li> <li>during storage according to IEC 60721</li> <li>during transport according to IEC 60721</li> </ul>   | 3K6 (no ice formation, only occasional condensation), 3C3 (no salt mist), 3S2 (sand must not get into the devices), 3M6<br>1K6 (only occasional condensation), 1C2 (no salt mist), 1S2 (sand must not get inside the devices), 1M4<br>2K2, 2C1, 2S1, 2M2 (max. fall height 0.3 m) |
| Environmental footprint   |   |
| global warming potential [CO2 eq] total   | 345 kg  |
| global warming potential [CO2 eq] during manufacturing  | 31.2 kg   |
| global warming potential [CO2 eq] during sales  | 0.945 kg  |
| global warming potential [CO2 eq] during operation  | 316 kg  |
| global warming potential [CO2 eq] after end of life   | -2.75 kg  |
| Siemens Eco Profile (SEP)   | Siemens EcoTech   |
| Electromagnetic compatibility   |   |
| <b>EMC emitted interference</b>   | acc. to IEC 60947-4-2: Class A  |
| Communication/ Protocol   |   |
| <b>communication module is supported</b>  |   |
| <ul style="list-style-type: none"> <li>PROFINET standard</li> <li>EtherNet/IP</li> <li>Modbus RTU</li> <li>Modbus TCP</li> <li>PROFIBUS</li> </ul>  | Yes<br>Yes<br>Yes<br>Yes<br>Yes   |
| UL/CSA ratings  |   |
| <b>manufacturer's article number</b>  |   |
| <ul style="list-style-type: none"> <li><b>of circuit breaker</b> <ul style="list-style-type: none"> <li>— usable for Standard Faults at 460/480 V according to UL</li> <li>— usable for High Faults at 460/480 V according to UL</li> </ul> </li> <li><b>of the fuse</b> <ul style="list-style-type: none"> <li>— usable for Standard Faults up to 575/600 V according to UL</li> <li>— usable for High Faults up to 575/600 V according to UL</li> </ul> </li> </ul> | Siemens type: 3VA5225, max. 250 A; Iq = 10 kA<br>Siemens type: 3VA52, max. 250 A; Iq max = 65 kA<br>Type: Class RK5 / K5, max. 400 A; Iq = 10 kA<br>Type: Class J, max. 350 A; Iq = 100 kA  |
| <b>operating power [hp] for 3-phase motors</b>  |   |
| <ul style="list-style-type: none"> <li>at 200/208 V at 50 °C rated value</li> <li>at 220/230 V at 50 °C rated value</li> <li>at 460/480 V at 50 °C rated value</li> <li>at 575/600 V at 50 °C rated value</li> </ul>  | 50 hp<br>50 hp<br>100 hp<br>150 hp  |
| Electrical Safety   |   |
| <b>protection class IP on the front according to IEC 60529</b>  | IP00; IP20 with cover   |
| <b>touch protection on the front according to IEC 60529</b>   | finger-safe, for vertical contact from the front with cover   |
| ATEX  |   |
| <b>Safety Integrity Level (SIL) according to IEC 61508 relating to ATEX</b>   | SIL 1   |
| <b>PFHD with high demand rate according to IEC 61508 relating to ATEX</b>   | 9E-6 1/h  |
| <b>PFDavg with low demand rate according to IEC 61508 relating to ATEX</b>  | 0.09  |
| <b>hardware fault tolerance according to IEC 61508 relating to ATEX</b>   | 0   |
| <b>T1 value for proof test interval or service life according to IEC 61508 relating to ATEX</b>   | 3 a   |
| <b>certificate of suitability</b>   |   |
| <ul style="list-style-type: none"> <li>ATEX</li> <li>IECEx</li> <li>UKEX</li> </ul>   | Yes<br>Yes<br>Yes   |
| Approvals Certificates  |   |
| <b>General Product Approval</b>   | <b>EMV</b>  |



[KC](#)

For use in hazardous locations

Test Certificates

Maritime application



[Miscellaneous](#)

[Type Test Certificates/Test Report](#)



Maritime application

other

Environment



[Confirmation](#)



[Environmental Confirmations](#)

#### Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information for data generation and storage

<https://support.industry.siemens.com/cs/ww/en/view/109995012>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RW5056-6AB05>

Cax online generator

<https://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RW5056-6AB05>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RW5056-6AB05>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

[https://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3RW5056-6AB05&lang=en](https://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RW5056-6AB05&lang=en)

Characteristic: Tripping characteristics, I<sup>2</sup>t, Let-through current

<https://support.industry.siemens.com/cs/ww/en/ps/3RW5056-6AB05/char>

Characteristic: Installation altitude

<https://www.automation.siemens.com/bilddb/index.aspx?view=Search&mlfb=3RW5056-6AB05&objecttype=14&gridview=view1>

Simulation Tool for Soft Starters (STS)

<https://support.industry.siemens.com/cs/ww/en/view/101494917>





