

Siemens  
EcoTech



SIRIUS soft starter 200-600 V 315 A, 110-250 V AC Spring-loaded terminals  
Thermistor input



|  |  |
|--|--|
| <b>product brand name</b>  | SIRIUS   |
| <b>product category</b>  | Hybrid switching devices   |
| <b>product designation</b>   | Soft starter   |
| <b>product type designation</b>  | 3RW50  |
| <b>manufacturer's article number</b>   |  |
| <ul style="list-style-type: none"> <li>• of standard HMI module usable</li> <li>• of high feature HMI module usable</li> <li>• of communication module PROFINET standard usable</li> <li>• of communication module PROFIBUS usable</li> <li>• of communication module Modbus TCP usable</li> <li>• of communication module Modbus RTU usable</li> <li>• of communication module Ethernet/IP</li> <li>• of circuit breaker usable at 400 V</li> <li>• of circuit breaker usable at 500 V</li> <li>• of the gG fuse usable up to 690 V</li> <li>• of full range R fuse link for semiconductor protection usable up to 690 V</li> <li>• of back-up R fuse link for semiconductor protection usable up to 690 V</li> <li>• of line contactor usable up to 480 V</li> <li>• of line contactor usable up to 690 V</li> </ul> | <ul style="list-style-type: none"> <li><a href="#">3RW5980-0HS01</a></li> <li><a href="#">3RW5980-0HF00</a></li> <li><a href="#">3RW5980-0CS00</a></li> <li><a href="#">3RW5980-0CP00</a></li> <li><a href="#">3RW5980-0CT00</a></li> <li><a href="#">3RW5980-0CR00</a></li> <li><a href="#">3RW5980-0CE00</a></li> <li><a href="#">3VA2440-7MN32-0AA0; Type of assignment 1, Iq = 65 kA</a></li> <li><a href="#">3VA2440-7MN32-0AA0; Type of assignment 1, Iq = 65 kA</a></li> <li>2x3NA3365-6; Type of coordination 1, Iq = 65 kA</li> <li><a href="#">3NE1 333-2; Type of coordination 2, Iq = 65 kA</a></li> <li><a href="#">3NE3 335; Type of coordination 2, Iq = 65 kA</a></li> <li><a href="#">3RT1075</a></li> <li><a href="#">3RT1075</a></li> </ul> |
| <b>General technical data</b>  |  |
| <b>starting voltage [%]</b>  | 30 ... 100 %   |
| <b>stopping voltage [%]</b>  | 50 %; non-adjustable   |
| <b>start-up ramp time of soft starter</b>  | 0 ... 20 s   |
| <b>ramp-down time of soft starter</b>  | 0 ... 20 s   |
| <b>current limiting value [%] adjustable</b>   | 130 ... 700 %  |
| <b>certificate of suitability</b>  |  |
| <ul style="list-style-type: none"> <li>• CE marking</li> <li>• UL approval</li> <li>• CSA approval</li> </ul>  | <ul style="list-style-type: none"> <li>Yes</li> <li>Yes</li> <li>Yes</li> </ul>  |
| <b>product component</b>   |  |
| <ul style="list-style-type: none"> <li>• HMI-High Feature</li> <li>• is supported HMI-Standard</li> <li>• is supported HMI-High Feature</li> </ul>   | <ul style="list-style-type: none"> <li>No</li> <li>Yes</li> <li>Yes</li> </ul>   |
| <b>product feature integrated bypass contact system</b>  | Yes  |
| <b>number of controlled phases</b>   | 2  |
| <b>buffering time in the event of power failure</b>  |  |

|   |   |
|---|---|
| <ul style="list-style-type: none"> <li>• for main current circuit</li> <li>• for control circuit</li> </ul>   | 100 ms<br>100 ms  |
| <b>insulation voltage rated value</b>   | 600 V   |
| <b>degree of pollution</b>  | 3, acc. to IEC 60947-4-2  |
| <b>impulse voltage rated value</b>  | 6 kV  |
| <b>blocking voltage of the thyristor maximum</b>  | 1 600 V   |
| <b>service factor</b>   | 1   |
| <b>surge voltage resistance rated value</b>   | 6 kV  |
| <b>maximum permissible voltage for protective separation</b> <ul style="list-style-type: none"> <li>• between main and auxiliary circuit</li> </ul>   | 600 V   |
| <b>shock resistance</b>   | 15 g / 11 ms, from 12 g / 11 ms with potential contact lifting  |
| <b>vibration resistance</b>   | 15 mm to 6 Hz; 2g to 500 Hz   |
| utilization category according to IEC 60947-4-2   | AC-53a  |
| <b>reference code according to IEC 81346-2</b>  | Q   |
| <b>Substance Prohibitance (Date)</b>  | 09/23/2019  |
| <b>SVHC substance name</b>  | Lead - 7439-92-1<br>Lead monoxide (lead oxide) - 1317-36-8<br>2,2',6,6'-tetrabromo-4,4'-isopropylidenediphenol - 79-94-7<br>6,6'-di-tert-butyl-2,2'-methylenedi-p-cresol - 119-47-1<br>2-methyl-1-(4-methylthiophenyl)-2-morpholinopropan-1-one - 71868-10-5  |
| <b>Weight</b>   | 5.1 kg  |
| <b>product function</b> <ul style="list-style-type: none"> <li>• ramp-up (soft starting)</li> <li>• ramp-down (soft stop)</li> <li>• Soft Torque</li> <li>• adjustable current limitation</li> <li>• pump ramp down</li> <li>• intrinsic device protection</li> <li>• motor overload protection</li> <li>• evaluation of thermistor motor protection</li> <li>• auto-RESET</li> <li>• manual RESET</li> <li>• remote reset</li> <li>• communication function</li> <li>• operating measured value display</li> <li>• error logbook</li> <li>• via software parameterizable</li> <li>• via software configurable</li> <li>• <b>PROFInergy</b></li> <li>• voltage ramp</li> <li>• torque control</li> <li>• analog output</li> </ul> | Yes<br>Yes<br>Yes<br>Yes<br>Yes<br>Yes<br>Yes; Full motor protection (thermistor motor protection and electronic motor overload protection)<br>Yes; Type A PTC or Klaxon / Thermoclick<br>Yes<br>Yes<br>Yes; By turning off the control supply voltage<br>Yes<br>Yes; Only in conjunction with special accessories<br>Yes; Only in conjunction with special accessories<br>No<br>Yes<br>Yes; in connection with the PROFINET Standard communication module<br>Yes<br>No<br>No |
| <b>Power Electronics</b>  |   |
| <b>operational current</b> <ul style="list-style-type: none"> <li>• at 40 °C rated value</li> <li>• at 50 °C rated value</li> <li>• at 60 °C rated value</li> </ul>   | 315 A<br>279 A<br>255 A   |
| <b>operating voltage</b> <ul style="list-style-type: none"> <li>• rated value</li> </ul>  | 200 ... 600 V   |
| <b>relative negative tolerance of the operating voltage</b>   | -15 %   |
| <b>relative positive tolerance of the operating voltage</b>   | 10 %  |
| <b>operating power for 3-phase motors</b> <ul style="list-style-type: none"> <li>• at 230 V at 40 °C rated value</li> <li>• at 400 V at 40 °C rated value</li> <li>• at 500 V at 40 °C rated value</li> </ul>   | 90 kW<br>160 kW<br>200 kW   |
| <b>Operating frequency 1 rated value</b>  | 50 Hz   |
| <b>Operating frequency 2 rated value</b>  | 60 Hz   |
| <b>relative negative tolerance of the operating frequency</b>   | -10 %   |
| <b>relative positive tolerance of the operating frequency</b>   | 10 %  |
| <b>adjustable motor current</b> <ul style="list-style-type: none"> <li>• at rotary coding switch on switch position 1</li> </ul>  | 135 A   |

|  |  |
|--|--|
| <ul style="list-style-type: none"> <li>• at rotary coding switch on switch position 2</li> <li>• at rotary coding switch on switch position 3</li> <li>• at rotary coding switch on switch position 4</li> <li>• at rotary coding switch on switch position 5</li> <li>• at rotary coding switch on switch position 6</li> <li>• at rotary coding switch on switch position 7</li> <li>• at rotary coding switch on switch position 8</li> <li>• at rotary coding switch on switch position 9</li> <li>• at rotary coding switch on switch position 10</li> <li>• at rotary coding switch on switch position 11</li> <li>• at rotary coding switch on switch position 12</li> <li>• at rotary coding switch on switch position 13</li> <li>• at rotary coding switch on switch position 14</li> <li>• at rotary coding switch on switch position 15</li> <li>• at rotary coding switch on switch position 16</li> <li>• minimum</li> </ul> | 147 A<br>159 A<br>171 A<br>183 A<br>195 A<br>207 A<br>219 A<br>231 A<br>243 A<br>255 A<br>267 A<br>279 A<br>291 A<br>303 A<br>315 A<br>135 A   |
| <b>minimum load [%]</b>  | 15 %; Relative to smallest settable le   |
| <b>power loss [W] for rated value of the current at AC</b>   |  |
| <ul style="list-style-type: none"> <li>• at 40 °C after startup</li> <li>• at 50 °C after startup</li> <li>• at 60 °C after startup</li> </ul>   | 36 W<br>29 W<br>24 W   |
| <b>power loss [W] at AC at current limitation 350 %</b>  |  |
| <ul style="list-style-type: none"> <li>• at 40 °C during startup</li> <li>• at 50 °C during startup</li> <li>• at 60 °C during startup</li> </ul>  | 3 368 W<br>2 805 W<br>2 455 W  |
| <b>type of the motor protection</b>  | Electronic, tripping in the event of thermal overload of the motor   |
| <b>Control circuit/ Control</b>  |  |
| <b>type of voltage of the control supply voltage</b>   | AC   |
| <b>control supply voltage at AC</b>  |  |
| <ul style="list-style-type: none"> <li>• at 50 Hz</li> <li>• at 60 Hz</li> </ul>   | 110 ... 250 V<br>110 ... 250 V   |
| <b>relative negative tolerance of the control supply voltage at AC at 50 Hz</b>  | -15 %  |
| <b>relative positive tolerance of the control supply voltage at AC at 50 Hz</b>  | 10 %   |
| <b>relative negative tolerance of the control supply voltage at AC at 60 Hz</b>  | -15 %  |
| <b>relative positive tolerance of the control supply voltage at AC at 60 Hz</b>  | 10 %   |
| <b>control supply voltage frequency</b>  | 50 ... 60 Hz   |
| <b>relative negative tolerance of the control supply voltage frequency</b>   | -10 %  |
| <b>relative positive tolerance of the control supply voltage frequency</b>   | 10 %   |
| <b>control supply current in standby mode rated value</b>  | 30 mA  |
| <b>holding current in bypass operation rated value</b>   | 105 mA   |
| <b>inrush current by closing the bypass contacts maximum</b>   | 2.2 A  |
| inrush current peak at application of control supply voltage maximum   | 12.2 A   |
| duration of inrush current peak at application of control supply voltage   | 2.2 ms   |
| <b>design of the overvoltage protection</b>  | Varistor   |
| <b>design of short-circuit protection for control circuit</b>  | 4 A gG fuse (I <sub>cu</sub> =1 kA), 6 A quick-acting fuse (I <sub>cu</sub> =1 kA), C1 miniature circuit breaker (I <sub>cu</sub> = 600 A), C6 miniature circuit breaker (I <sub>cu</sub> = 300 A); Is not part of scope of supply |
| <b>Inputs/ Outputs</b>   |  |
| <b>number of digital inputs</b>  | 1  |
| <b>number of digital outputs</b>   | 3  |
| <ul style="list-style-type: none"> <li>• not parameterizable</li> </ul>  | 2  |
| <b>digital output version</b>  | 2 normally-open contacts (NO) / 1 changeover contact (CO)  |
| <b>number of analog outputs</b>  | 0  |
| <b>switching capacity current of the relay outputs</b>   |  |
| <ul style="list-style-type: none"> <li>• at AC-15 at 250 V rated value</li> <li>• at DC-13 at 24 V rated value</li> </ul>  | 3 A<br>1 A   |

**Installation/ mounting/ dimensions**

|  |  |
|--|--|
| <b>mounting position</b>   | with vertical mounting surface +/-90° rotatable, with vertical mounting surface +/- 22.5° tiltable to the front and back |
| <b>fastening method</b>  | screw fixing   |
| <b>height</b>  | 230 mm   |
| <b>width</b>   | 160 mm   |
| <b>depth</b>   | 282 mm   |
| required spacing with side-by-side mounting  |  |
| <ul style="list-style-type: none"> <li>• forwards</li> <li>• backwards</li> <li>• upwards</li> <li>• downwards</li> <li>• at the side</li> </ul> | 10 mm<br>0 mm<br>100 mm<br>75 mm<br>5 mm   |
| <b>weight without packaging</b>  | 7.3 kg   |

**Connections/ Terminals**

|  |   |
|--|---|
| <b>type of electrical connection</b>   |   |
| <ul style="list-style-type: none"> <li>• for main current circuit</li> <li>• for control circuit</li> </ul>  | busbar connection<br>spring-loaded terminals  |
| <b>width of connection bar maximum</b>   | 35 mm; with connection cover 3RT1966-4EA1 maximum length 45 mm  |
| <b>wire length for thermistor connection</b>   |   |
| <ul style="list-style-type: none"> <li>• with conductor cross-section = 0.5 mm<sup>2</sup> maximum</li> <li>• with conductor cross-section = 1.5 mm<sup>2</sup> maximum</li> <li>• with conductor cross-section = 2.5 mm<sup>2</sup> maximum</li> </ul>  | 50 m<br>150 m<br>250 m  |
| <b>type of connectable conductor cross-sections for main contacts for box terminal</b>   |   |
| <ul style="list-style-type: none"> <li>• using the front clamping point solid</li> <li>• using the front clamping point finely stranded with core end processing</li> <li>• using the front clamping point finely stranded without core end processing</li> <li>• using the front clamping point stranded</li> <li>• using the back clamping point solid</li> <li>• r box terminal using the back clamping point</li> <li>• using both clamping points solid</li> <li>• using both clamping points finely stranded with core end processing</li> <li>• using both clamping points finely stranded without core end processing</li> <li>• using both clamping points stranded</li> <li>• using the back clamping point finely stranded with core end processing</li> <li>• using the back clamping point finely stranded without core end processing</li> <li>• using the back clamping point stranded</li> </ul> | 95 ... 300 mm <sup>2</sup><br>70 ... 240 mm <sup>2</sup><br>70 ... 240 mm <sup>2</sup><br>95 ... 300 mm <sup>2</sup><br>120 ... 240 mm <sup>2</sup><br>250 ... 500 kcmil<br>min. 2x 70 mm <sup>2</sup> , max. 2x 240 mm <sup>2</sup><br>min. 2x 50 mm <sup>2</sup> , max. 2x 185 mm <sup>2</sup><br>min. 2x 50 mm <sup>2</sup> , max. 2x 185 mm <sup>2</sup><br>min. 2x 70 mm <sup>2</sup> , max. 2x 240 mm <sup>2</sup><br>120 ... 185 mm <sup>2</sup><br>120 ... 185 mm <sup>2</sup><br>120 ... 240 mm <sup>2</sup> |
| <b>type of connectable conductor cross-sections</b>  |   |
| <ul style="list-style-type: none"> <li>• for AWG cables for main current circuit solid</li> <li>• for DIN cable lug for main contacts stranded</li> <li>• for DIN cable lug for main contacts finely stranded</li> </ul>   | 2/0 ... 500 kcmil<br>50 ... 240 mm <sup>2</sup><br>70 ... 240 mm <sup>2</sup>   |
| <b>type of connectable conductor cross-sections</b>  |   |
| <ul style="list-style-type: none"> <li>• for control circuit solid</li> <li>• for control circuit finely stranded with core end processing</li> <li>• for AWG cables for control circuit solid</li> <li>• for AWG cables for control circuit finely stranded with core end processing</li> </ul>   | 2x (0.25 ... 1.5 mm <sup>2</sup> )<br>2x (0.25 ... 1.5 mm <sup>2</sup> )<br>2x (24 ... 16)<br>2x (24 ... 16)  |
| <b>wire length</b>   |   |
| <ul style="list-style-type: none"> <li>• between soft starter and motor maximum</li> <li>• at the digital inputs at AC maximum</li> </ul>  | 800 m<br>1 000 m  |
| <b>tightening torque</b>   |   |
| <ul style="list-style-type: none"> <li>• for main contacts with screw-type terminals</li> <li>• for auxiliary and control contacts with screw-type terminals</li> </ul>  | 14 ... 24 N·m<br>0.8 ... 1.2 N·m  |
| <b>tightening torque [lbf·in]</b>  |   |
| <ul style="list-style-type: none"> <li>• for main contacts with screw-type terminals</li> <li>• for auxiliary and control contacts with screw-type</li> </ul>  | 124 ... 210 lbf·in<br>7 ... 10.3 lbf·in   |

|   |   |
|---|---|
| terminals   |   |
| <b>Ambient conditions</b>   |   |
| installation altitude at height above sea level maximum   | 5 000 m; Derating as of 1000 m, see catalog   |
| <b>ambient temperature</b>  |   |
| • during operation  | -25 ... +60 °C; Please observe derating at temperatures of 40 °C or above   |
| • during storage and transport  | -40 ... +80 °C  |
| <b>environmental category</b>   |   |
| • during operation according to IEC 60721   | 3K6 (no ice formation, only occasional condensation), 3C3 (no salt mist), 3S2 (sand must not get into the devices), 3M6 |
| • during storage according to IEC 60721   | 1K6 (only occasional condensation), 1C2 (no salt mist), 1S2 (sand must not get inside the devices), 1M4                 |
| • during transport according to IEC 60721   | 2K2, 2C1, 2S1, 2M2 (max. fall height 0.3 m)   |
| <b>Environmental footprint</b>  |   |
| global warming potential [CO2 eq] total   | 464 kg  |
| global warming potential [CO2 eq] during manufacturing  | 87.4 kg   |
| global warming potential [CO2 eq] during sales  | 2.05 kg   |
| global warming potential [CO2 eq] during operation  | 407 kg  |
| global warming potential [CO2 eq] after end of life   | -32.4 kg  |
| Siemens Eco Profile (SEP)   | Siemens EcoTech   |
| <b>Electromagnetic compatibility</b>  |   |
| <b>EMC emitted interference</b>   | acc. to IEC 60947-4-2: Class A  |
| <b>Communication/ Protocol</b>  |   |
| <b>communication module is supported</b>  |   |
| • PROFINET standard   | Yes   |
| • EtherNet/IP   | Yes   |
| • Modbus RTU  | Yes   |
| • Modbus TCP  | Yes   |
| • PROFIBUS  | Yes   |
| <b>UL/CSA ratings</b>   |   |
| <b>manufacturer's article number</b>  |   |
| • of circuit breaker<br>— usable for High Faults at 460/480 V according to UL                   | Siemens type: 3VA54, max. 600 A; Iq max = 65 kA   |
| • of the fuse<br>— usable for Standard Faults up to 575/600 V according to UL                   | Type: Class L, max. 1000 A; Iq = 18 kA  |
| — usable for High Faults up to 575/600 V according to UL  | Type: Class L, max. 1000 A; Iq = 100 kA   |
| <b>operating power [hp] for 3-phase motors</b>  |   |
| • at 200/208 V at 50 °C rated value   | 75 hp   |
| • at 220/230 V at 50 °C rated value   | 100 hp  |
| • at 460/480 V at 50 °C rated value   | 200 hp  |
| • at 575/600 V at 50 °C rated value   | 250 hp  |
| <b>Electrical Safety</b>  |   |
| <b>protection class IP on the front according to IEC 60529</b>                                  | IP00; IP20 with cover   |
| <b>touch protection on the front according to IEC 60529</b>                                     | finger-safe, for vertical contact from the front with cover   |
| <b>ATEX</b>   |   |
| <b>Safety Integrity Level (SIL) according to IEC 61508 relating to ATEX</b>                     | SIL 1   |
| <b>PFHD with high demand rate according to IEC 61508 relating to ATEX</b>                       | 9E-6 1/h  |
| <b>PFDavg with low demand rate according to IEC 61508 relating to ATEX</b>                      | 0.09  |
| <b>hardware fault tolerance according to IEC 61508 relating to ATEX</b>                         | 0   |
| <b>T1 value for proof test interval or service life according to IEC 61508 relating to ATEX</b> | 3 a   |
| <b>certificate of suitability</b>   |   |
| • ATEX  | Yes   |
| • IECEx   | Yes   |
| • UKEX  | Yes   |
| <b>Approvals Certificates</b>   |   |
| <b>General Product Approval</b>   | <b>EMV</b>  |



[KC](#)

For use in hazardous locations

Test Certificates

Maritime application



[Miscellaneous](#)

[Type Test Certificates/Test Report](#)



Maritime application

other

Environment



[Confirmation](#)



[Environmental Confirmations](#)

#### Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information for data generation and storage

<https://support.industry.siemens.com/cs/ww/en/view/109995012>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RW5074-2TB15>

Cax online generator

<https://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RW5074-2TB15>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RW5074-2TB15>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

[https://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3RW5074-2TB15&lang=en](https://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RW5074-2TB15&lang=en)

Characteristic: Tripping characteristics, I<sup>2</sup>t, Let-through current

<https://support.industry.siemens.com/cs/ww/en/ps/3RW5074-2TB15/char>

Characteristic: Installation altitude

<https://www.automation.siemens.com/bilddb/index.aspx?view=Search&mlfb=3RW5074-2TB15&objecttype=14&gridview=view1>

Simulation Tool for Soft Starters (STS)

<https://support.industry.siemens.com/cs/ww/en/view/101494917>





