

Siemens  
EcoTech



SIRIUS soft starter 200-480 V 570 A, 110-250 V AC, Screw terminals Fail-safe



|                                      |   |
|--------------------------------------|---|
| <b>product brand name</b>            | SIRIUS  |
| <b>product category</b>              | Hybrid switching devices  |
| <b>product designation</b>           | Failsafe soft starters  |
| <b>product type designation</b>      | 3RW55   |
| <b>manufacturer's article number</b> | <ul style="list-style-type: none"> <li>• of high feature HMI module usable <a href="#">3RW5980-0HF00</a></li> <li>• of communication module PROFINET standard usable <a href="#">3RW5980-0CS00</a></li> <li>• of communication module PROFINET high-feature usable <a href="#">3RW5950-0CH00</a></li> <li>• of communication module PROFIBUS usable <a href="#">3RW5980-0CP00</a></li> <li>• of communication module Modbus TCP usable <a href="#">3RW5980-0CT00</a></li> <li>• of communication module Modbus RTU usable <a href="#">3RW5980-0CR00</a></li> <li>• of communication module Ethernet/IP <a href="#">3RW5980-0CE00</a></li> <li>• of circuit breaker usable at 400 V <a href="#">3VA2580-6HN32-0AA0; Type of coordination 1, Iq = 65 kA, CLASS 10</a></li> <li>• of circuit breaker usable at 500 V <a href="#">3VA2580-6HN32-0AA0; Type of coordination 1, Iq = 65 kA, CLASS 10</a></li> <li>• of circuit breaker usable at 400 V at inside-delta circuit <a href="#">3VA2510-6HN32-0AA0; Type of coordination 1, Iq = 65 kA, CLASS 10</a></li> <li>• of circuit breaker usable at 500 V at inside-delta circuit <a href="#">3VA2510-6HN32-0AA0; Type of coordination 1, Iq = 65 kA, CLASS 10</a></li> <li>• of the gG fuse usable up to 690 V 2x3NA3365-6; Type of coordination 1, Iq = 65 kA</li> <li>• of the gG fuse usable at inside-delta circuit up to 500 V 2x3NA3365-6; Type of coordination 1, Iq = 65 kA</li> <li>• of full range R fuse link for semiconductor protection usable up to 690 V <a href="#">3NE1437-2; Type of coordination 2, Iq = 65 kA</a></li> <li>• of back-up R fuse link for semiconductor protection usable up to 690 V <a href="#">3NC3342-1U; Type of coordination 2, Iq = 65 kA</a></li> </ul> |

| General technical data                       |                           |
|--|---------------------------|
| <b>starting voltage [%]</b>                  | 20 ... 100 %              |
| <b>stopping voltage [%]</b>                  | 50 %; non-adjustable      |
| <b>start-up ramp time of soft starter</b>    | 0 ... 360 s               |
| <b>ramp-down time of soft starter</b>        | 0 ... 360 s               |
| <b>start torque [%]</b>                      | 10 ... 100 %              |
| <b>stopping torque [%]</b>                   | 10 ... 100 %              |
| <b>torque limitation [%]</b>                 | 20 ... 200 %              |
| <b>current limiting value [%] adjustable</b> | 125 ... 800 %             |
| <b>breakaway voltage [%] adjustable</b>      | 40 ... 100 %              |
| <b>breakaway time adjustable</b>             | 0 ... 2 s                 |
| <b>number of parameter sets</b>              | 3                         |
| <b>accuracy class</b>                        | 5 (based on IEC 61557-12) |
| <b>certificate of suitability</b>            |                           |
| • CE marking                                 | Yes                       |

|  |   |
|--|---|
| <ul style="list-style-type: none"> <li>• UL approval</li> </ul>                                | Yes   |
| <ul style="list-style-type: none"> <li>• CSA approval</li> </ul>                               | Yes   |
| <b>product component</b>   |   |
| <ul style="list-style-type: none"> <li>• HMI-High Feature</li> </ul>                           | Yes   |
| <ul style="list-style-type: none"> <li>• is supported HMI-High Feature</li> </ul>              | Yes   |
| <b>product feature integrated bypass contact system</b>  | Yes   |
| <b>number of controlled phases</b>   | 3   |
| <b>current unbalance limiting value [%]</b>  | 10 ... 60 %   |
| <b>ground-fault monitoring limiting value [%]</b>  | 10 ... 95 %   |
| <b>buffering time in the event of power failure</b>  |   |
| <ul style="list-style-type: none"> <li>• for main current circuit</li> </ul>                   | 100 ms  |
| <ul style="list-style-type: none"> <li>• for control circuit</li> </ul>                        | 100 ms  |
| <b>idle time adjustable</b>  | 0 ... 255 s   |
| <b>insulation voltage rated value</b>  | 480 V   |
| <b>degree of pollution</b>   | 3, acc. to IEC 60947-4-2  |
| <b>impulse voltage rated value</b>   | 6 kV  |
| <b>blocking voltage of the thyristor maximum</b>   | 1 400 V   |
| <b>service factor</b>  | 1.15  |
| <b>surge voltage resistance rated value</b>  | 6 kV  |
| <b>maximum permissible voltage for protective separation</b>                                   |   |
| <ul style="list-style-type: none"> <li>• between main and auxiliary circuit</li> </ul>         | 480 V; does not apply for thermistor connection   |
| <b>shock resistance</b>  | 15 g / 11 ms, from 6 g / 11 ms with potential contact lifting   |
| <b>vibration resistance</b>  | 15 mm up to 6 Hz; 2 g up to 500 Hz  |
| <b>recovery time after overload trip adjustable</b>  | 60 ... 1 800 s  |
| utilization category according to IEC 60947-4-2  | AC 53a  |
| <b>reference code according to IEC 81346-2</b>   | Q   |
| <b>Substance Prohibitance (Date)</b>   | 11/22/2019  |
| <b>SVHC substance name</b>   | Lead - 7439-92-1<br>Lead monoxide (lead oxide) - 1317-36-8<br>2,2',6,6'-tetrabromo-4,4'-isopropylidenediphenol - 79-94-7<br>6,6'-di-tert-butyl-2,2'-methylenedi-p-cresol - 119-47-1<br>2-methyl-1-(4-methylthiophenyl)-2-morpholinopropan-1-one - 71868-10-5<br>Dibutylbis(pentane-2,4-dionato-O,O')tin - 22673-19-4<br>Lead titanium trioxide - 12060-00-3 |
| <b>Weight</b>  | 13.726 kg   |
| <b>product function</b>  |   |
| <ul style="list-style-type: none"> <li>• ramp-up (soft starting)</li> </ul>                    | Yes   |
| <ul style="list-style-type: none"> <li>• ramp-down (soft stop)</li> </ul>                      | Yes   |
| <ul style="list-style-type: none"> <li>• breakaway pulse</li> </ul>                            | Yes   |
| <ul style="list-style-type: none"> <li>• adjustable current limitation</li> </ul>              | Yes   |
| <ul style="list-style-type: none"> <li>• creep speed in both directions of rotation</li> </ul> | Yes   |
| <ul style="list-style-type: none"> <li>• pump ramp down</li> </ul>                             | Yes   |
| <ul style="list-style-type: none"> <li>• DC braking</li> </ul>                                 | Yes   |
| <ul style="list-style-type: none"> <li>• motor heating</li> </ul>                              | Yes   |
| <ul style="list-style-type: none"> <li>• min/max pointer</li> </ul>                            | Yes   |
| <ul style="list-style-type: none"> <li>• trace function</li> </ul>                             | Yes   |
| <ul style="list-style-type: none"> <li>• intrinsic device protection</li> </ul>                | Yes   |
| <ul style="list-style-type: none"> <li>• motor overload protection</li> </ul>                  | Yes; Full motor protection (thermistor motor protection and electronic motor overload protection) / When using the motor overload protection according to ATEX, an upstream contactor is required in inside-delta circuit.  |
| <ul style="list-style-type: none"> <li>• evaluation of thermistor motor protection</li> </ul>  | Yes; Type A PTC or Klixon / Thermoclick   |
| <ul style="list-style-type: none"> <li>• inside-delta circuit</li> </ul>                       | Yes   |
| <ul style="list-style-type: none"> <li>• auto-RESET</li> </ul>                                 | Yes   |
| <ul style="list-style-type: none"> <li>• manual RESET</li> </ul>                               | Yes   |
| <ul style="list-style-type: none"> <li>• remote reset</li> </ul>                               | Yes   |
| <ul style="list-style-type: none"> <li>• communication function</li> </ul>                     | Yes   |
| <ul style="list-style-type: none"> <li>• operating measured value display</li> </ul>           | Yes   |
| <ul style="list-style-type: none"> <li>• event list</li> </ul>                                 | Yes   |
| <ul style="list-style-type: none"> <li>• error logbook</li> </ul>                              | Yes   |
| <ul style="list-style-type: none"> <li>• via software parameterizable</li> </ul>               | Yes   |
| <ul style="list-style-type: none"> <li>• via software configurable</li> </ul>                  | Yes   |

|   |   |
|---|---|
| • screw terminal                                | Yes   |
| • spring-loaded terminal                        | No  |
| • <b>PROFInergy</b>                             | Yes; in connection with the PROFINET Standard and PROFINET High-Feature communication modules |
| • <b>firmware update</b>                        | Yes   |
| • <b>removable terminal for control circuit</b> | Yes   |
| • voltage ramp                                  | Yes   |
| • torque control                                | Yes   |
| • combined braking                              | Yes   |
| • analog output                                 | Yes; 4 ... 20 mA (default) / 0 ... 10 V   |
| • programmable control inputs/outputs           | Yes   |
| • condition monitoring                          | Yes   |
| • automatic parameterisation                    | Yes   |
| • application wizards                           | Yes   |
| • alternative run-down                          | Yes   |
| • emergency operation mode                      | Yes   |
| • reversing operation                           | Yes   |
| • soft starting at heavy starting conditions    | Yes   |

### Power Electronics

|   |  |
|---|--|
| <b>operational current</b>  |  |
| • at 40 °C rated value  | 570 A  |
| • at 40 °C rated value minimum  | 114 A  |
| • at 50 °C rated value  | 504 A  |
| • at 60 °C rated value  | 460 A  |
| <b>operational current at inside-delta circuit</b>                                  |  |
| • at 40 °C rated value  | 987 A  |
| • at 50 °C rated value  | 873 A  |
| • at 60 °C rated value  | 796 A  |
| <b>operating voltage</b>  |  |
| • rated value   | 200 ... 480 V  |
| • at inside-delta circuit rated value   | 200 ... 480 V  |
| <b>relative negative tolerance of the operating voltage</b>                         | -15 %  |
| <b>relative positive tolerance of the operating voltage</b>                         | 10 %   |
| <b>relative negative tolerance of the operating voltage at inside-delta circuit</b> | -15 %  |
| <b>relative positive tolerance of the operating voltage at inside-delta circuit</b> | 10 %   |
| <b>operating power for 3-phase motors</b>   |  |
| • at 230 V at 40 °C rated value   | 160 kW   |
| • at 230 V at inside-delta circuit at 40 °C rated value                             | 315 kW   |
| • at 400 V at 40 °C rated value   | 315 kW   |
| • at 400 V at inside-delta circuit at 40 °C rated value                             | 560 kW   |
| <b>Operating frequency 1 rated value</b>  | 50 Hz  |
| <b>Operating frequency 2 rated value</b>  | 60 Hz  |
| <b>relative negative tolerance of the operating frequency</b>                       | -10 %  |
| <b>relative positive tolerance of the operating frequency</b>                       | 10 %   |
| <b>minimum load [%]</b>   | 10 %; Relative to set Ie   |
| <b>power loss [W] for rated value of the current at AC</b>                          |  |
| • at 40 °C after startup  | 171 W  |
| • at 50 °C after startup  | 151 W  |
| • at 60 °C after startup  | 141 W  |
| <b>power loss [W] at AC at current limitation 350 %</b>                             |  |
| • at 40 °C during startup   | 10 229 W   |
| • at 50 °C during startup   | 8 488 W  |
| • at 60 °C during startup   | 7 651 W  |
| <b>type of the motor protection</b>   | Electronic, tripping in the event of thermal overload of the motor |

### Control circuit/ Control

|  |               |
|--|---------------|
| <b>type of voltage of the control supply voltage</b> | AC            |
| <b>control supply voltage at AC</b>                  |               |
| • at 50 Hz   | 110 ... 250 V |

|  |  |
|--|--|
| • at 60 Hz   | 110 ... 250 V  |
| relative negative tolerance of the control supply voltage at AC at 50 Hz | -15 %  |
| relative positive tolerance of the control supply voltage at AC at 50 Hz | 10 %   |
| relative negative tolerance of the control supply voltage at AC at 60 Hz | -15 %  |
| relative positive tolerance of the control supply voltage at AC at 60 Hz | 10 %   |
| control supply voltage frequency   | 50 ... 60 Hz   |
| relative negative tolerance of the control supply voltage frequency      | -10 %  |
| relative positive tolerance of the control supply voltage frequency      | 10 %   |
| control supply current in standby mode rated value                       | 100 mA   |
| holding current in bypass operation rated value                          | 150 mA   |
| inrush current by closing the bypass contacts maximum                    | 0.87 A   |
| inrush current peak at application of control supply voltage maximum     | 43 A   |
| duration of inrush current peak at application of control supply voltage | 1.6 ms   |
| design of the overvoltage protection                                     | Varistor   |
| design of short-circuit protection for control circuit                   | 4 A gG fuse (I <sub>cu</sub> =1 kA), 6 A quick-acting fuse (I <sub>cu</sub> =1 kA), C1 miniature circuit breaker (I <sub>cu</sub> = 600 A), C6 miniature circuit breaker (I <sub>cu</sub> = 300 A); Is not part of scope of supply |

#### Inputs/ Outputs

|   |  |
|---|--|
| number of digital inputs                        | 4  |
| • with fail-safe                                | 1  |
| • parameterizable                               | 4  |
| • number of digital outputs                     | 3  |
| • Number of digital outputs with fail-safe      | 1  |
| • number of digital outputs parameterizable     | 2  |
| • number of digital outputs not parameterizable | 1  |
| digital output version                          | 2 normally-open contacts (NO) / 1 normally-closed contact (NC) / 1 changeover contact (CO) |
| number of analog outputs                        | 1  |
| switching capacity current of the relay outputs |  |
| • at AC-15 at 250 V rated value                 | 3 A  |
| • at DC-13 at 24 V rated value                  | 1 A  |

#### Response times

|   |        |
|---|--------|
| OFF-delay time with safety-related request when switched off via control inputs maximum | 100 ms |
|---|--------|

#### Installation/ mounting/ dimensions

|   |  |
|---|--|
| mounting position                           | Vertical (can be rotated +/- 90° and tilted forward or backward +/- 22.5°) |
| fastening method                            | screw fixing   |
| height                                      | 393 mm   |
| width                                       | 210 mm   |
| depth                                       | 203 mm   |
| required spacing with side-by-side mounting |  |
| • forwards                                  | 10 mm  |
| • backwards                                 | 0 mm   |
| • upwards                                   | 100 mm   |
| • downwards                                 | 75 mm  |
| • at the side                               | 5 mm   |
| weight without packaging                    | 10.9 kg  |

#### Connections/ Terminals

|                                       |                      |
|---------------------------------------|----------------------|
| type of electrical connection         |                      |
| • for main current circuit            | busbar connection    |
| • for control circuit                 | screw-type terminals |
| width of connection bar maximum       | 45 mm                |
| wire length for thermistor connection |                      |

|   |   |
|---|---|
| <ul style="list-style-type: none"> <li>with conductor cross-section = 0.5 mm<sup>2</sup> maximum</li> <li>with conductor cross-section = 1.5 mm<sup>2</sup> maximum</li> <li>with conductor cross-section = 2.5 mm<sup>2</sup> maximum</li> </ul>   | 50 m<br>150 m<br>250 m  |
| <b>type of connectable conductor cross-sections</b> <ul style="list-style-type: none"> <li>for DIN cable lug for main contacts stranded</li> <li>for DIN cable lug for main contacts finely stranded</li> </ul>   | 2x (50 ... 240 mm <sup>2</sup> )<br>2x (70 ... 240 mm <sup>2</sup> )  |
| <b>type of connectable conductor cross-sections</b> <ul style="list-style-type: none"> <li>for control circuit solid</li> <li>for control circuit finely stranded with core end processing</li> <li>for AWG cables for control circuit solid</li> </ul>   | 1x (0.5 ... 4.0 mm <sup>2</sup> ), 2x (0.5 ... 2.5 mm <sup>2</sup> )<br>1x (0.5 ... 2.5 mm <sup>2</sup> ), 2x (0.5 ... 1.5 mm <sup>2</sup> )<br>1x (20 ... 12), 2x (20 ... 14)  |
| <b>wire length</b> <ul style="list-style-type: none"> <li>between soft starter and motor maximum</li> <li>at the digital inputs at DC maximum</li> </ul>  | 800 m<br>1 000 m  |
| <b>tightening torque</b> <ul style="list-style-type: none"> <li>for main contacts with screw-type terminals</li> <li>for auxiliary and control contacts with screw-type terminals</li> </ul>  | 14 ... 24 N·m<br>0.8 ... 1.2 N·m  |
| <b>tightening torque [lbf·in]</b> <ul style="list-style-type: none"> <li>for main contacts with screw-type terminals</li> <li>for auxiliary and control contacts with screw-type terminals</li> </ul>   | 124 ... 210 lbf·in<br>7 ... 10.3 lbf·in   |
| <b>Ambient conditions</b>   |   |
| installation altitude at height above sea level maximum   | 2 000 m; Derating as of 1000 m, see catalog   |
| <b>ambient temperature</b> <ul style="list-style-type: none"> <li>during operation</li> <li>during storage and transport</li> </ul>   | -25 ... +60 °C; Please observe derating at temperatures of 40 °C or above<br>-40 ... +80 °C   |
| <b>environmental category</b> <ul style="list-style-type: none"> <li>during operation according to IEC 60721</li> <li>during storage according to IEC 60721</li> <li>during transport according to IEC 60721</li> </ul>   | 3K6 (no ice formation, only occasional condensation), 3C3 (no salt mist), 3S2 (sand must not get into the devices), 3M6<br>1K6 (only occasional condensation), 1C2 (no salt mist), 1S2 (sand must not get inside the devices), 1M4<br>2K2, 2C1, 2S1, 2M2 (max. fall height 0.3 m) |
| <b>Environmental footprint</b>  |   |
| global warming potential [CO <sub>2</sub> eq] total   | 833 kg  |
| global warming potential [CO <sub>2</sub> eq] during manufacturing  | 95.3 kg   |
| global warming potential [CO <sub>2</sub> eq] during sales  | 2.8 kg  |
| global warming potential [CO <sub>2</sub> eq] during operation  | 756 kg  |
| global warming potential [CO <sub>2</sub> eq] after end of life   | -21 kg  |
| Siemens Eco Profile (SEP)   | Siemens EcoTech   |
| <b>Electromagnetic compatibility</b>  |   |
| <b>EMC emitted interference</b>   | acc. to IEC 60947-4-2: Class A  |
| <b>Communication/ Protocol</b>  |   |
| <b>communication module is supported</b> <ul style="list-style-type: none"> <li>PROFINET standard</li> <li>PROFINET high-feature</li> <li>EtherNet/IP</li> <li>Modbus RTU</li> <li>Modbus TCP</li> <li>PROFIBUS</li> </ul>  | Yes<br>Yes<br>Yes<br>Yes<br>Yes<br>Yes  |
| <b>UL/CSA ratings</b>   |   |
| <b>manufacturer's article number</b> <ul style="list-style-type: none"> <li><b>of the fuse</b> <ul style="list-style-type: none"> <li>usable for Standard Faults up to 575/600 V according to UL</li> <li>usable for High Faults up to 575/600 V according to UL</li> <li>usable for Standard Faults at inside-delta circuit up to 575/600 V according to UL</li> <li>usable for High Faults at inside-delta circuit up to 575/600 V according to UL</li> </ul> </li> </ul> | Type: Class J / L, max. 1600 A; I <sub>q</sub> = 30 kA<br>Type: Class J / L, max. 1200 A; I <sub>q</sub> = 100 kA<br>Type: Class J / L, max. 1600 A; I <sub>q</sub> = 30 kA<br>Type: Class J / L, max. 1200 A; I <sub>q</sub> = 100 kA  |
| <b>operating power [hp] for 3-phase motors</b>  |   |

|  |  |
|--|--|
| <ul style="list-style-type: none"> <li>• at 200/208 V at 50 °C rated value</li> <li>• at 220/230 V at 50 °C rated value</li> <li>• at 460/480 V at 50 °C rated value</li> <li>• at 200/208 V at inside-delta circuit at 50 °C rated value</li> <li>• at 220/230 V at inside-delta circuit at 50 °C rated value</li> <li>• at 460/480 V at inside-delta circuit at 50 °C rated value</li> </ul> | <p>150 hp</p> <p>200 hp</p> <p>400 hp</p> <p>300 hp</p> <p>350 hp</p> <p>750 hp</p>          |
| <b>contact rating of auxiliary contacts according to UL</b>  | R300-B300  |
| <b>Safety related data</b>   |  |
| product function suitable for safety function  | Yes  |
| <b>suitability for use</b>   |  |
| <ul style="list-style-type: none"> <li>• safety-related switching on</li> <li>• safety-related switching OFF</li> </ul>  | <p>No</p> <p>Yes</p>   |
| <b>safe state</b>  | Open load circuit  |
| <b>function test interval maximum</b>  | 1 a  |
| <b>diagnostics test interval by internal test function maximum</b>   | 1 000 s  |
| <b>stop category according to IEC 60204-1</b>  | 0  |
| <b>B10d value</b>  | 648 000  |
| <b>average diagnostic coverage level (DCavg)</b>   | 90 %   |
| <b>MTTFd</b>   | 39 a   |
| <b>IEC 62061</b>   |  |
| <b>Safety Integrity Level (SIL) according to IEC 62061</b>   | SIL 1  |
| PFHD with high demand rate according to IEC 62061  | 1E-6 1/h   |
| <b>ISO 13849</b>   |  |
| <b>performance level (PL) according to ISO 13849-1</b>   | PL c   |
| <b>category according to ISO 13849-1</b>   | 2  |
| <b>IEC 61508</b>   |  |
| <b>Safety Integrity Level (SIL)</b>  |  |
| <ul style="list-style-type: none"> <li>• according to IEC 61508</li> </ul>   | SIL 1  |
| <b>safety device type according to IEC 61508-2</b>   | Type B   |
| <b>PFHD with high demand rate according to IEC 61508</b>   | 1E-6 1/h   |
| PFDAvg with low demand rate according to IEC 61508   | 0.09   |
| <b>Safe failure fraction (SFF)</b>   | 60 %   |
| hardware fault tolerance according to IEC 61508  | 0  |
| T1 value of service life according to IEC 61508  | 20 a   |
| <b>Electrical Safety</b>   |  |
| <b>protection class IP on the front according to IEC 60529</b>   | IP00; IP20 with cover  |
| <b>touch protection on the front according to IEC 60529</b>  | finger-safe, for vertical contact from the front with cover                                  |
| <b>ATEX</b>  |  |
| <b>Safety Integrity Level (SIL) according to IEC 61508 relating to ATEX</b>  | SIL 1  |
| <b>PFHD with high demand rate according to IEC 61508 relating to ATEX</b>  | 5E-7 1/h   |
| <b>PFDAvg with low demand rate according to IEC 61508 relating to ATEX</b>   | 0.008  |
| <b>hardware fault tolerance according to IEC 61508 relating to ATEX</b>  | 0  |
| <b>T1 value for proof test interval or service life according to IEC 61508 relating to ATEX</b>  | 3 a  |
| <b>certificate of suitability</b>  |  |
| <ul style="list-style-type: none"> <li>• ATEX</li> <li>• IECEx</li> <li>• according to ATEX directive 2014/34/EU</li> </ul>  | <p>Yes</p> <p>Yes</p> <p>BVS 18 ATEX F 003 X</p>   |
| <b>type of protection according to ATEX directive 2014/34/EU</b>   | II (2)G [Ex eb Gb] [Ex db Gb] [Ex pxb Gb], II (2)D [Ex tb Db] [Ex pxb Db], I (M2) [Ex db Mb] |
| <b>Approvals Certificates</b>  |  |
| <b>General Product Approval</b>  | EMV  |



|  |   |  |  |   |
|--|---|--|--|---|
| EMV  | For use in hazardous locations  | Functional Safety  | Test Certificates  | Maritime application  |
| <a href="#">KC</a>   | <br>ATEX | <br>IECEX | <a href="#">Type Examination Certificate</a>   | <a href="#">Type Test Certificates/Test Report</a>  |
|  |   |  |  | <br>ABS                |
| Maritime application   | other   |  |  | Environment   |
| <br>BUREAU<br>VERITAS | <br>LRS  | <br>PRS   | <br>产品合格<br>QC PASS | <a href="#">Confirmation</a>  |
|  |   |  |  | <br>Siemens<br>EcoTech |

**Environment**



[Environmental Confirmations](#)

**Further information**

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information for data generation and storage

<https://support.industry.siemens.com/cs/ww/en/view/109995012>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RW5548-6HF14>

Cax online generator

<https://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RW5548-6HF14>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RW5548-6HF14>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

[https://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3RW5548-6HF14&lang=en](https://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RW5548-6HF14&lang=en)

Characteristic: Tripping characteristics, I<sub>t</sub>, Let-through current

<https://support.industry.siemens.com/cs/ww/en/ps/3RW5548-6HF14/char>

Characteristic: Installation altitude

<https://www.automation.siemens.com/bilddb/index.aspx?view=Search&mlfb=3RW5548-6HF14&objecttype=14&gridview=view1>

Simulation Tool for Soft Starters (STS)

<https://support.industry.siemens.com/cs/ww/en/view/101494917>





