



Power semiconductor module 600 V, for 3RW52/50, 470 A

product designation	Power semiconductor module
design of the product	600 V, 470 A
product type designation	3RW59
manufacturer's article number of soft starter	
•	3RW5075 (2x), 3RW5076 (2x)
•	3RW5146 (3x), 3RW5147 (3x)
•	3RW5246 (3x), 3RW5247 (3x)

**General technical data**

Substance Prohibitation (Date)	02/15/2018
Weight	1.55 kg

**Ambient conditions**

ambient temperature during storage	-40 ... +80 °C
------------------------------------	----------------

**Approvals Certificates**

General Product Approval	EMV	For use in hazardous locations	Test Certificates
--------------------------	-----	--------------------------------	-------------------








[KC](#)

[Miscellaneous](#)

[Type Test Certificates/Test Report](#)

**Maritime application**

   	<p><a href="#">Confirmation</a></p> 
---	---

**Environment**

[Environmental Confirmations](#)

**Further information**

Information on the packaging  
<https://support.industry.siemens.com/cs/ww/en/view/109813875>  
 Information for data generation and storage  
<https://support.industry.siemens.com/cs/ww/en/view/109995012>  
 Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

**Industry Mall (Online ordering system)**

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RW5924-0SS05>

**Cax online generator**

<https://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RW5924-0SS05>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<https://support.industry.siemens.com/cs/ww/en/ps/3RW5924-0SS05>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)**

[https://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3RW5924-0SS05&lang=en](https://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RW5924-0SS05&lang=en)

**Characteristic: Tripping characteristics, I<sup>2</sup>t, Let-through current**

<https://support.industry.siemens.com/cs/ww/en/ps/3RW5924-0SS05/char>

**Characteristic: Installation altitude**

<https://www.automation.siemens.com/bilddb/index.aspx?view=Search&mlfb=3RW5924-0SS05&objecttype=14&gridview=view1>

**Simulation Tool for Soft Starters (STS)**

<https://support.industry.siemens.com/cs/ww/en/view/101494917>

---

last modified:

4/2/2025 

