



Cover control cable duct yellow

product designation	Cover for control cable duct
design of the product	Yellow
product type designation	3RW59
manufacturer's article number of soft starter	3RW55...HF..

General technical data	
Substance Prohibittance (Date)	09/23/2019
Weight	0.026 kg
Ambient conditions	
ambient temperature during storage	-40 ... +80 °C

Approvals Certificates		
General Product Approval	EMV	For use in hazardous locations



EG-Konf.



UL



[KC](#)

[Miscellaneous](#)

Test Certificates	Maritime application	other
Type Test Certificates/Test Report	 	  

other	Environment
Confirmation	Environmental Confirmations

Further information

Information on the packaging
<https://support.industry.siemens.com/cs/ww/en/view/109813875>
 Information for data generation and storage
<https://support.industry.siemens.com/cs/ww/en/view/109995012>
 Information- and Downloadcenter (Catalogs, Brochures,...)
<https://www.siemens.com/ic10>
 Industry Mall (Online ordering system)
<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mfb=3RW5950-0GD30>

Cax online generator

<https://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RW5950-0GD30>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RW5950-0GD30>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

https://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RW5950-0GD30&lang=en

Characteristic: Tripping characteristics, I²t, Let-through current

<https://support.industry.siemens.com/cs/ww/en/ps/3RW5950-0GD30/char>

Characteristic: Installation altitude

<https://www.automation.siemens.com/bilddb/index.aspx?view=Search&mlfb=3RW5950-0GD30&objecttype=14&gridview=view1>

Simulation Tool for Soft Starters (STS)

<https://support.industry.siemens.com/cs/ww/en/view/101494917>

last modified:

4/2/2025 

