

Pushbutton, 16 mm, round, plastic, yellow, pushbutton, flat



Figure similar

|  |                        |
|--|------------------------|
| product brand name                                     | SIRIUS                 |
| product designation                                    | Pushbuttons            |
| design of the product                                  | Single device round    |
| product type designation                               | 3SB2                   |
| <b>Enclosure</b>                                       |                        |
| number of command points                               | 1                      |
| <b>Actuator</b>  |                        |
| design of the actuating element                        | Pushbutton             |
| principle of operation of the actuating element        | momentary contact type |
| product extension optional light source                | No                     |
| color of the actuating element                         | yellow                 |
| material of the actuating element                      | plastic                |
| shape of the actuating element                         | Flat pushbutton        |
| outer diameter of the actuating element                | 19 mm                  |
| type of unlocking device                               | without                |
| number of switching positions                          | 2                      |
| <b>Front ring</b>                                      |                        |
| product component front ring                           | Yes                    |
| design of the front ring                               | Standard               |
| material of the front ring                             | plastic                |
| color of the front ring                                | black                  |
| <b>Holder</b>  |                        |
| material of the holder                                 | Plastic                |
| <b>General technical data</b>                          |                        |
| product function                                       |                        |
| • EMERGENCY OFF function                               | No                     |
| • EMERGENCY STOP function                              | No                     |
| protection class IP                                    | IP65                   |
| vibration resistance according to IEC 60068-2-6        | 20 ... 200 Hz: 5g      |
| operating frequency maximum                            | 1 000 1/h              |
| mechanical service life (operating cycles) typical     | 10 000 000             |
| reference code according to IEC 81346-2                | S                      |
| Substance Prohibitance (Date)                          | 07/01/2006             |
| Weight   | 0.008 kg               |
| <b>Connections/ Terminals</b>                          |                        |
| tightening torque of the screws in the bracket maximum | 0.4 N·m                |
| <b>Ambient conditions</b>                              |                        |
| ambient temperature                                    |                        |
| • during operation                                     | -25 ... +70 °C         |

|  |                |
|--|----------------|
| • during storage   | -40 ... +80 °C |
| environmental category during operation according to IEC 60721 | 3K6            |

#### Installation/ mounting/ dimensions

|                                   |                      |
|-----------------------------------|----------------------|
| fastening method                  | front plate mounting |
| shape of the installation opening | round                |
| mounting diameter                 | 16 mm                |
| mounting height                   | 8 mm                 |
| installation width                | 19 mm                |
| installation depth                | 50 mm                |

#### Approvals Certificates

|                          |                   |
|--------------------------|-------------------|
| General Product Approval | Test Certificates |
|--------------------------|-------------------|



[Type Test Certificates/Test Report](#)

[Special Test Certificate](#)

|                   |       |             |
|-------------------|-------|-------------|
| Test Certificates | other | Environment |
|-------------------|-------|-------------|

[Miscellaneous](#)



[Confirmation](#)

[Environmental Confirmations](#)

#### Further information

##### Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

##### Information for data generation and storage

<https://support.industry.siemens.com/cs/ww/en/view/109995012>

##### Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

##### Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SB2000-0AD01>

##### Cax online generator

<https://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SB2000-0AD01>

##### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3SB2000-0AD01>

##### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

[https://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3SB2000-0AD01&lang=en](https://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SB2000-0AD01&lang=en)

last modified:

4/2/2025