

Indicator light, 16 mm, round, plastic, clear, Lampholder W2 x 4.6 d, without lamp




Figure similar

<b>product brand name</b>	SIRIUS
<b>product designation</b>	Indicator lights
<b>design of the product</b>	Complete unit round
<b>product type designation</b>	3SB2
<b>Enclosure</b>	
<b>number of command points</b>	0
<b>Actuator</b>	
<b>design of the actuating element</b>	indicator light
product extension optional light source	Yes
color of the actuating element	clear
<b>material of the actuating element</b>	plastic
<b>type of unlocking device</b>	without
<b>number of switching positions</b>	2
<b>Front ring</b>	
<b>product component front ring</b>	No
<b>Holder</b>	
<b>material of the holder</b>	Plastic
<b>Contact block/ lampholder</b>	
<b>socket design</b>	W2 x 4.6d without lamp
<b>number of lampholders</b>	1
<b>number of switching elements</b>	0
<b>General technical data</b>	
<b>product function</b>	
• positive opening	No
• EMERGENCY STOP function	No
product component light source	No
type of voltage of the operating voltage	AC/DC
<b>protection class IP</b>	IP65
<b>vibration resistance according to IEC 60068-2-6</b>	20 ... 200 Hz: 5g
<b>reference code according to IEC 81346-2</b>	P
<b>Substance Prohibitance (Date)</b>	07/01/2006
<b>Weight</b>	0.022 kg
operating voltage rated value	5 ... 60 V
<b>Auxiliary circuit</b>	
<b>number of NC contacts for auxiliary contacts</b>	0
<b>number of NO contacts for auxiliary contacts</b>	0
number of CO contacts for auxiliary contacts	0
<b>Connections/ Terminals</b>	
<b>type of electrical connection</b>	tab terminals

<b>tightening torque of the screws in the bracket maximum</b>	0.4 N·m
<b>Ambient conditions</b>	
<b>ambient temperature</b>	
• during operation	-25 ... +60 °C
• during storage	-40 ... +80 °C
environmental category during operation according to IEC 60721	3K6
<b>Installation/ mounting/ dimensions</b>	
<b>fastening method</b>	front plate mounting
<b>shape of the installation opening</b>	round
<b>mounting diameter</b>	16 mm
<b>mounting height</b>	9 mm
<b>installation width</b>	19 mm
<b>installation depth</b>	50 mm
<b>Approvals Certificates</b>	
General Product Approval	



Test Certificates	other	Environment
<a href="#">Type Test Certificates/Test Report</a>	<a href="#">Miscellaneous</a>	<a href="#">Special Test Certificate</a>
		<a href="#">Confirmation</a>
		<a href="#">Environmental Confirmations</a>

Further information
<b>Information on the packaging</b> <a href="https://support.industry.siemens.com/cs/ww/en/view/109813875">https://support.industry.siemens.com/cs/ww/en/view/109813875</a>
<b>Information for data generation and storage</b> <a href="https://support.industry.siemens.com/cs/ww/en/view/109995012">https://support.industry.siemens.com/cs/ww/en/view/109995012</a>
<b>Information- and Downloadcenter (Catalogs, Brochures,...)</b> <a href="https://www.siemens.com/ic10">https://www.siemens.com/ic10</a>
<b>Industry Mall (Online ordering system)</b> <a href="https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SB2204-6BH06">https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SB2204-6BH06</a>
<b>Cax online generator</b> <a href="https://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&amp;mlfb=3SB2204-6BH06">https://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&amp;mlfb=3SB2204-6BH06</a>
<b>Service&amp;Support (Manuals, Certificates, Characteristics, FAQs,...)</b> <a href="https://support.industry.siemens.com/cs/ww/en/ps/3SB2204-6BH06">https://support.industry.siemens.com/cs/ww/en/ps/3SB2204-6BH06</a>
<b>Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)</b> <a href="https://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SB2204-6BH06&amp;lang=en">https://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SB2204-6BH06&amp;lang=en</a>

last modified:

4/2/2025 