



SIRIUS safety relay Safety-oriented Speed monitoring 110-240 V AC/DC, 45 mm overall width Spring-type terminal EC instantaneous: 2 NO EC delayed: 0 SC: 2 electrical Auto-start/manual start Basic device Maximum achievable PL according to EN 13849-1: e Maximum achievable SIL according to IEC 61508: 3

product brand name	SIRIUS
product designation	Speed monitor
design of the product	standstill and speed monitoring
product type designation	3TK28
Product Function	
product function	
<ul style="list-style-type: none"> • automatic start • light barrier monitoring • standstill monitoring • protective door monitoring • magnetically operated switch monitoring NC-NO • magnetically operated switch monitoring NC-NC • rotation speed monitoring • laser scanner monitoring • light array monitoring • EMERGENCY OFF function • monitored start-up • pressure-sensitive mat monitoring 	<ul style="list-style-type: none"> Yes No Yes Yes No No Yes No No Yes Yes No
suitability for interaction press control	No
suitability for use	
<ul style="list-style-type: none"> • monitoring of floating sensors • monitoring of non-floating sensors • position switch monitoring • EMERGENCY-OFF circuit monitoring • valve monitoring • opto-electronic protection device monitoring • tactile sensor monitoring • magnetically operated switch monitoring • proximity switch monitoring • safety switch • safety-related circuits 	<ul style="list-style-type: none"> Yes No Yes No No No No No No Yes Yes Yes
General technical data	
certificate of suitability UL approval	Yes
product feature cross-circuit-proof	Yes
insulation voltage rated value	300 V
surge voltage resistance rated value	4 000 V
protection class IP	
<ul style="list-style-type: none"> • of the enclosure 	IP20
shock resistance	8g / 10 ms

vibration resistance according to IEC 60068-2-6	10 ... 55 Hz: 0.35 mm
mechanical service life (operating cycles) typical	50 000 000
electrical endurance (operating cycles) typical	100 000
thermal current of the switching element with contacts maximum	5 A
Substance Prohibitance (Date)	05/01/2012
SVHC substance name	Lead - 7439-92-1 Lead monoxide (lead oxide) - 1317-36-8
Weight	0.63 kg
Ambient conditions	
installation altitude at height above sea level maximum	2 000 m; installation altitude: 5000 m with derating
ambient temperature	
• during operation	0 ... 60 °C; from an operating altitude > 2000 m, the maximum permissible temperature is reduced by 0.5 °C / 100 m
• during storage	-20 ... +70 °C
relative humidity during operation	10 ... 95 %
air pressure according to SN 31205	90 ... 106 kPa
Electromagnetic compatibility	
installation environment regarding EMC	This product is suitable for Class A environments only. In household environments, this device can cause unwanted radio interference. The user is required to implement appropriate measures in this case.
EMC emitted interference	EN 60947-5-1
Safety related data	
stop category according to IEC 60204-1	0
IEC 62061	
SIL Claim Limit (subsystem) according to EN 62061	3
Safety Integrity Level (SIL) according to IEC 62061	SIL 3
PFHD with high demand rate according to IEC 62061	3.4E-9 1/h
ISO 13849	
category according to EN ISO 13849-1	4
performance level (PL)	
• according to ISO 13849-1	PL e
• for delayed release circuit according to ISO 13849-1	e
IEC 61508	
Safety Integrity Level (SIL)	
• according to IEC 61508	3
• for delayed release circuit according to IEC 61508	SIL3
safety device type according to IEC 61508-2	Type B
hardware fault tolerance according to IEC 61508	1
T1 value for proof test interval or service life according to IEC 61508	20 a
Electrical Safety	
touch protection against electrical shock	finger-safe
Short-circuit protection	
design of the fuse link for short-circuit protection of the NO contacts of the relay outputs required	gL/gG: 4 A
Inputs	
design of input	
• cascading input/functional switching	No
• feedback input	Yes
• start input	Yes
number of sensor inputs	
• 1-channel or 2-channel	0
• 2-channel	3
Outputs	
number of outputs as contact-affected switching element	
• as NC contact	
— for signaling function instantaneous contact	0
— for signaling function delayed switching	0
— safety-related instantaneous contact	0
— safety-related delayed switching	0

<ul style="list-style-type: none"> ● as NO contact <ul style="list-style-type: none"> — for signaling function instantaneous contact — for signaling function delayed switching — safety-related instantaneous contact — safety-related delayed switching 	<p>0</p> <p>0</p> <p>1</p> <p>1</p>
number of outputs as contact-less semiconductor switching element <ul style="list-style-type: none"> ● for signaling function <ul style="list-style-type: none"> — delayed switching — instantaneous contact ● safety-related <ul style="list-style-type: none"> — delayed switching — instantaneous contact 	<p>1</p> <p>1</p> <p>0</p> <p>0</p>
switching capacity current of semiconductor outputs <ul style="list-style-type: none"> ● for signaling function at DC-13 at 24 V 	0.02 A
switching capacity current of the NO contacts of the relay outputs at DC-13 <ul style="list-style-type: none"> ● at 24 V ● at 115 V 	<p>2 A</p> <p>2 A</p>
switching capacity current of the NO contacts of the relay outputs at AC-15 <ul style="list-style-type: none"> ● at 24 V ● at 230 V 	<p>3 A</p> <p>3 A</p>
switching capacity current of the NC contacts of the relay outputs at AC-15 <ul style="list-style-type: none"> ● at 24 V ● at 115 V ● at 230 V 	<p>3 A</p> <p>3 A</p> <p>2 A</p>
type of switching output	optionally PNP or NPN
Encoder	
encoder signal evaluation	two signal tracks each with inverted signals
type of signal level of the encoder	optionally TTL, HTL or sin/cos (U _a = 1V _{ss})
type of failure response of the encoder	high-resistance
Proximity switch	
type of voltage of the supply voltage of proximity switches	DC
supply voltage of proximity switches	24 V; provided by the device
current consumption of proximity switches maximum	30 mA
input voltage for proximity switch minimum	10 V
pulse duration of proximity switches minimum	75 μs
interpulse period of proximity switches minimum	75 μs
adjustment range of signal frequency of proximity switches	1 Hz ... 2 kHz
measuring precision	+2 %
switching hysteresis	6.25 %
Control circuit/ Control	
type of voltage of the control supply voltage	AC/DC
control supply voltage 1 at AC <ul style="list-style-type: none"> ● at 50 Hz ● at 60 Hz 	<p>110 ... 240 V</p> <p>110 ... 240 V</p>
control supply voltage frequency <ul style="list-style-type: none"> ● 1 rated value ● 2 rated value 	<p>50 Hz</p> <p>60 Hz</p>
control supply voltage 1 at DC	110 ... 240 V
operating range factor control supply voltage rated value of magnet coil at DC <ul style="list-style-type: none"> ● initial value ● full-scale value 	<p>0.8</p> <p>1.1</p>
operating range factor control supply voltage rated value of magnet coil at AC <ul style="list-style-type: none"> ● at 50 Hz ● at 60 Hz 	<p>0.8 ... 1.1</p> <p>0.8 ... 1.1</p>

Installation/ mounting/ dimensions	
mounting position	any
fastening method	screw and snap-on mounting
height	107.7 mm
width	45 mm
depth	124.3 mm

Connections/ Terminals	
type of electrical connection	spring-loaded terminals
type of connectable conductor cross-sections	<ul style="list-style-type: none"> • solid 1x (0.5 ... 4 mm²) • finely stranded with core end processing 2 x (0.25 ... 1.5 mm²) • finely stranded without core end processing 2x (0.25 ... 1.5 mm²) • for AWG cables solid 2x (24 ... 16) • for AWG cables stranded 2x (20 ... 16)
connectable conductor cross-section	<ul style="list-style-type: none"> • solid 0.25 ... 1.5 mm² • finely stranded with core end processing 0.25 ... 1.5 mm² • finely stranded without core end processing 0.25 ... 1.5 mm²
AWG number as coded connectable conductor cross section	<ul style="list-style-type: none"> • solid 24 ... 16 • stranded 24 ... 16

Approvals Certificates	
General Product Approval	Functional Safety



[Type Examination Certificate](#)

Test Certificates	other	Railway	Environment
-------------------	-------	---------	-------------

[Special Test Certificate](#)



[Confirmation](#)

[Confirmation](#)

[Environmental Conformations](#)

Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information for data generation and storage

<https://support.industry.siemens.com/cs/ww/en/view/109995012>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3TK2810-1KA42>

Cax online generator

<https://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3TK2810-1KA42>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3TK2810-1KA42>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

https://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3TK2810-1KA42&lang=en



