

Surge suppressor RC element with cable spacer 127-240 V AC / 150-250 V DC for mounting to coil terminal for contactors size S0-S2



| | |
|---|------------------|
| product category | Surge suppressor |
| product designation | RC element |
| product type designation | 3TX7 |
| suitability for use | for 3TH4 |
| General technical data | |
| certificate of suitability | CE / UL / CSA |
| Substance Prohibition (Date) | 03/01/2017 |
| Weight | 0.021 kg |
| type of voltage of the control supply voltage | AC/DC |
| control supply voltage at AC | |
| • at 50 Hz rated value | 127 ... 240 V |
| • at 60 Hz rated value | 127 ... 240 V |
| control supply voltage frequency | |
| • 1 rated value | 50 Hz |
| • 2 rated value | 60 Hz |
| control supply voltage at DC rated value | 150 ... 250 V |
| design of the surge suppressor | RC element |
| Ambient conditions | |
| ambient temperature | |
| • during operation | -25 ... +55 °C |
| • during storage | -40 ... +80 °C |

| | |
|-------------------------------|-------|
| Approvals Certificates | |
| General Product Approval | other |



[Confirmation](#)

Environment

[Environmental Confirmations](#)

Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information for data generation and storage

<https://support.industry.siemens.com/cs/ww/en/view/109995012>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3TX7402-3T>

Cax online generator

<https://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3TX7402-3T>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3TX7402-3T>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

https://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3TX7402-3T&lang=en

last modified:

4/2/2025 