



Figure similar

Surge suppressor RC element for snapping on 48-127 V AC / 70-150 V DC for contactors Size 8-12, AC operation Size 3-6, DC operation

product category	Surge suppressor	
product designation	RC element	
product type designation	3TX7	
General technical data		
certificate of suitability	CE / UL / CSA	
Substance Prohibition (Date)	07/01/2006	
Weight	0.09 kg	
type of voltage of the control supply voltage	AC/DC	
control supply voltage at AC		
• at 50 Hz rated value	48 ... 127 V	
• at 60 Hz rated value	48 ... 127 V	
control supply voltage frequency		
• 1 rated value	50 Hz	
• 2 rated value	60 Hz	
control supply voltage at DC rated value	70 ... 150 V	
design of the surge suppressor	RC element	
Ambient conditions		
ambient temperature		
• during operation	-25 ... +55 °C	
• during storage	-40 ... +80 °C	
Approvals Certificates		
General Product Approval	other	Environment



[Confirmation](#)

[Environmental Confirmations](#)

Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information for data generation and storage

<https://support.industry.siemens.com/cs/ww/en/view/109995012>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3TX7522-3S>

Cax online generator

<https://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3TX7522-3S>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3TX7522-3S>

last modified:

4/2/2025 