

Siemens  
EcoTech



circuit breaker 3VA6 UL Frame 600 breaking capacity class M 35 kA @ 480 V 4-pole, line protection ETU850, LSI,  $I_n=400$  A overload protection, 100% rated  $I_r=160$  A...400 A short-circuit protection  $I_{sd}=0.6..10 \times I_n$ ,  $I_i=1.5..12 \times I_n$  neutral conductor protection adjustable (OFF, up to 160%) without connection



| Model  |                             |
|--|-----------------------------|
| product brand name   | SENTRON                     |
| product designation  | Molded-case circuit breaker |
| product designation / according to UL file   | MLAE                        |
| design of the product  | System protection           |
| design of the load switch / according to UL 489 / Heating, Air Conditioning, and Refrigeration circuit breaker (HACR Type) | Yes                         |
| design of the overcurrent release  | ETU850                      |
| protection function of the overcurrent release   | LSI                         |
| number of poles  | 4                           |
| General technical data   |                             |
| insulation voltage / rated value   | 800 V                       |
| operating voltage / at AC / rated value  | 690 V                       |
| power loss [W] / maximum   | 70 W                        |
| power loss [W] / for rated value of the current / at AC / in hot operating state / per pole                                | 23.33 W                     |
| mechanical service life (operating cycles) / typical   | 20 000                      |
| electrical endurance (operating cycles) / at AC-1 / at 380/415 V   | 4 000                       |
| electrical endurance (operating cycles) / at AC-1 / at 690 V   | 3 500                       |
| electrical endurance (operating cycles) / at 480 V   | 4 000                       |
| electrical endurance (operating cycles) / at 600 V   | 3 500                       |
| product feature / for neutral conductors / upgradable/retrofitable / short-circuit and overload proof                      | No                          |
| ground-fault monitoring version  | without                     |
| product function   |                             |
| • communication function   | Yes                         |
| • other measurement function   | Yes                         |
| Net Weight   | 6.9 kg                      |
| Current  |                             |
| marking / according to UL 489 / 100%-rated breaker   | Yes                         |
| operational current  |                             |
| • at 40 °C   | 400 A                       |
| • at 45 °C   | 400 A                       |
| • at 50 °C   | 400 A                       |
| • at 55 °C   | 400 A                       |
| • at 60 °C   | 400 A                       |
| • at 65 °C   | 400 A                       |

|   |                             |
|---|-----------------------------|
| <ul style="list-style-type: none"> <li>• at 70 °C</li> </ul>  | 400 A                       |
| <b>Switching capacity according to IEC 60947</b>  |                             |
| switching capacity class of the circuit breaker   | M                           |
| maximum short-circuit current breaking capacity (I <sub>cu</sub> )  |                             |
| <ul style="list-style-type: none"> <li>• at 240 V</li> <li>• at 415 V</li> <li>• at 690 V</li> </ul>                          | 85 kA<br>55 kA<br>6 kA      |
| operating short-circuit current breaking capacity (I <sub>cs</sub> )  |                             |
| <ul style="list-style-type: none"> <li>• at 240 V</li> <li>• at 415 V</li> <li>• at 690 V</li> </ul>                          | 85 kA<br>55 kA<br>6 kA      |
| short-circuit current making capacity (I <sub>cm</sub> )  |                             |
| <ul style="list-style-type: none"> <li>• at 240 V</li> <li>• at 415 V</li> <li>• at 690 V</li> </ul>                          | 187 kA<br>121 kA<br>9 kA    |
| <b>Switching capacity according to UL 489</b>   |                             |
| current breaking capacity   |                             |
| <ul style="list-style-type: none"> <li>• at 240 V</li> <li>• at 480 V</li> <li>• at 600 V</li> </ul>                          | 100 kA<br>35 kA<br>18 kA    |
| <b>Adjustable parameters</b>  |                             |
| adjustable response value setting current (I <sub>r</sub> ) / of the L-trip / with I <sub>2t</sub> characteristic             |                             |
| <ul style="list-style-type: none"> <li>• minimum</li> <li>• maximum</li> </ul>  | 150 A<br>400 A              |
| adjustable response value delay time (t <sub>r</sub> ) / for L-tripping / with I <sub>2t</sub> characteristic                 |                             |
| <ul style="list-style-type: none"> <li>• minimum</li> <li>• maximum</li> </ul>  | 0.5 s<br>25 s               |
| adjustable response value setting current (I <sub>sd</sub> ) / of S-trip / with I <sub>0t</sub> characteristic                |                             |
| <ul style="list-style-type: none"> <li>• minimum</li> <li>• maximum</li> </ul>  | 240 A<br>4 000 A            |
| adjustable response value setting current (I <sub>sd</sub> ) / of S-trip / with I <sub>2t</sub> characteristic                |                             |
| <ul style="list-style-type: none"> <li>• minimum</li> <li>• maximum</li> </ul>  | 240 A<br>4 000 A            |
| adjustable response value delay time (t <sub>sd</sub> ) / for S-tripping / with I <sub>0t</sub> characteristic                |                             |
| <ul style="list-style-type: none"> <li>• minimum</li> <li>• maximum</li> </ul>  | 0.05 s<br>0.5 s             |
| adjustable response value delay time (t <sub>sd</sub> ) / for S-tripping / with I <sub>2t</sub> characteristic                |                             |
| <ul style="list-style-type: none"> <li>• minimum</li> <li>• maximum</li> </ul>  | 0.05 s<br>0.5 s             |
| adjustable response value setting current (I <sub>l</sub> ) / for I-tripping  |                             |
| <ul style="list-style-type: none"> <li>• minimum</li> <li>• maximum</li> </ul>  | 600 A<br>4 800 A            |
| adjustable setting current (I <sub>nN</sub> ) / for N-tripping  |                             |
| <ul style="list-style-type: none"> <li>• minimum</li> <li>• maximum</li> </ul>  | 80 A<br>600 A               |
| design of the N-conductor protection  | adjustable OFF; 20% to 150% |
| product function / grounding protection   | No                          |
| <b>Mechanical Design</b>  |                             |
| product component   |                             |
| <ul style="list-style-type: none"> <li>• undervoltage release</li> <li>• voltage trigger</li> <li>• trip indicator</li> </ul> | No<br>No<br>No              |
| height [in]   | 9.76 in                     |
| height  | 248 mm                      |

|            |         |
|------------|---------|
| width [in] | 7.24 in |
| width      | 184 mm  |
| depth [in] | 4.33 in |
| depth      | 110 mm  |

### Connections

|   |                    |
|---|--------------------|
| arrangement of electrical connectors / for main current circuit | Without connection |
| type of electrical connection / for main current circuit        | Without            |

### Auxiliary circuit

|  |   |
|--|---|
| number of CO contacts / for auxiliary contacts | 0 |
|--|---|

### Accessories

|  |     |
|--|-----|
| product extension / optional / motor drive | Yes |
|--|-----|

### Environmental conditions

|                                    |        |
|------------------------------------|--------|
| protection class IP / on the front | IP40   |
| ambient temperature                |        |
| • during operation / minimum       | -25 °C |
| • during operation / maximum       | 70 °C  |
| • during storage / minimum         | -40 °C |
| • during storage / maximum         | 80 °C  |

### Environmental footprint

|  |                 |
|--|-----------------|
| Environmental Product Declaration (EPD)                  | Yes             |
| global warming potential [CO2 eq] / total                | 495 kg          |
| global warming potential [CO2 eq] / during manufacturing | 28.7 kg         |
| global warming potential [CO2 eq] / during operation     | 470 kg          |
| global warming potential [CO2 eq] / after end of life    | -4.07 kg        |
| Siemens Eco Profile (SEP)                                | Siemens EcoTech |
| reference code / according to IEC 81346-2                | Q               |

### Approvals / Certificates

#### General Product Approval



[Confirmation](#)



EG-Konf.



UL



UL

| General Product Approval | EMV | Test Certificates | Maritime application |
|--------------------------|-----|-------------------|----------------------|
|--------------------------|-----|-------------------|----------------------|

[Miscellaneous](#)



RCM

[Type Test Certificates/Test Report](#)



ABS

| Maritime application | other | Dangerous goods | Environment |
|----------------------|-------|-----------------|-------------|
|----------------------|-------|-----------------|-------------|



DNV



LRS

[Confirmation](#)

[Miscellaneous](#)

[Transport Information](#)



### Environment

Siemens EcoTech



[Environmental Confirmations](#)

### Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information for data generation and storage

<https://support.industry.siemens.com/cs/ww/en/view/109995012>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VA6440-5KP41-2AA0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3VA6440-5KP41-2AA0>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

[https://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=3VA6440-5KP41-2AA0](https://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VA6440-5KP41-2AA0)

CAX-Online-Generator

<https://www.siemens.com/cax>

Tender specifications

<https://www.siemens.com/specifications>





