



circular conduc. terminal TA2.3 2 x 25...150 mm<sup>2</sup> for 2 cables; 3 units auxiliary conductor voltage tap 3 units accessory for: 3VA12

Model		
product brand name	SETRON	
product designation	circular conductor terminal	
accessories	Wire connector	
General technical data		
designation / of the terminal	TA2.3	
type of electrical connection / with control wire tap	Yes	
Mechanical Design		
Net Weight	544 g	
Connections according IEC		
connectable conductor cross-section		
<ul style="list-style-type: none"> <li>for copper cable / stranded / minimum</li> <li>for copper cable / stranded / maximum</li> <li>for aluminum cable / stranded / minimum</li> <li>for aluminum cable / stranded / maximum</li> </ul>	25 mm <sup>2</sup> 150 mm <sup>2</sup> 25 mm <sup>2</sup> 150 mm <sup>2</sup>	
stripped length	26 / 51 mm	
tightening torque / when using copper cables		
<ul style="list-style-type: none"> <li>stranded</li> <li>finely stranded</li> <li>finely stranded / with core end processing</li> </ul>	25 - 150 mm <sup>2</sup> : 31.1 Nm 25 - 150 mm <sup>2</sup> : 31.1 Nm 25 - 70 mm <sup>2</sup> : 31.1 Nm	
Connections according UL		
permissible temperature / of connectable conductor / according to UL 486A-486B	75 °C	
stripped length	1.0 / 2.0 in	
connectable conductor cross-section		
<ul style="list-style-type: none"> <li>for copper cable / stranded / minimum</li> <li>for copper cable / stranded / maximum</li> <li>for aluminum cable / stranded / minimum</li> <li>for aluminum cable / stranded / maximum</li> </ul>	4 AWG 300 kcmil 4 AWG 300 kcmil	
tightening torque / when using copper cables		
<ul style="list-style-type: none"> <li>stranded</li> </ul>	4 AWG - 300 kcmil: 275 lb-in	
Certificates		
General Product Approval	EMV	Test Certificates




Miscellaneous



[Type Test Certificates/Test Report](#)



LRS

[Confirmation](#)[Miscellaneous](#)[Environmental Con-  
firmations](#)[Environmental Con-  
firmations](#)**Further information****Information on the packaging**<https://support.industry.siemens.com/cs/ww/en/view/109813875>**Information for data generation and storage**<https://support.industry.siemens.com/cs/ww/en/view/109995012>**Information- and Downloadcenter (Catalogs, Brochures,...)**<https://www.siemens.com/lowvoltage/catalogs>**Industry Mall (Online ordering system)**<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VA9213-0JC22>**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**<https://support.industry.siemens.com/cs/ww/en/ps/3VA9213-0JC22>**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**[https://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=3VA9213-0JC22](https://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VA9213-0JC22)**CAX-Online-Generator**<https://www.siemens.com/cax>**Tender specifications**<https://www.siemens.com/specifications>

last modified:

8/8/2025

