

Compact pin busbar, 10mm² connection 3p/N 9x compact device 1 MW touch protected 9 MW fixed length



product brand name	SENTRON
product designation	Pin busbar
design of the product	9x (1PH+N)
design of the phase tap	L1/N/L2/N/L3/N
General technical data	
compatibility	for compact devices
design of pole	3P+N
phase number	4
operational current rated value	63 A
suitability for interaction devices with auxiliary switch	No
suitability for interaction devices with N conductor	Yes
color	light grey
Product details	
product component with end cap	Yes
product feature attachable arc fault detection device	No
product feature insulated	Yes
product function	
• suitable for compact devices	Yes
• can be cut	No
number of devices suitable for fitting	9
type of electrical connection	Pin
Mechanical Design	
module width	18 mm
height	14 mm
width	42 mm
length	166 mm
number of modular width units	9
cross-section	10 mm ²
angle of the pin of busbar	0°
Net Weight	100 g

Approvals Certificates	
General Product Approval	Environment

[Confirmation](#)

[Miscellaneous](#)



[Confirmation](#)



[Environmental Confirmations](#)

Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information for data generation and storage

<https://support.industry.siemens.com/cs/ww/en/view/109995012>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5ST3673-7>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5ST3673-7>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

https://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5ST3673-7

CAX-Online-Generator

<https://www.siemens.com/cax>

Tender specifications

<https://www.siemens.com/specifications>



