



Connection terminal Cable entry right 690V AC, 1000 V DC, 80 A IP20

Model	
product brand name	SENTRON
product designation	Busbar systems
design of the product	Accessories
Supply voltage	
operating voltage at AC rated value	690 V
Connections	
tightening torque	
• minimum	1 N·m
• maximum	2 N·m
type of connectable conductor cross-sections for copper conductor stranded	6 - 25 mm <sup>2</sup>
Mechanical Design	
height	17.7 mm
width	17.5 mm
depth	13 mm
length	26.5 mm
Net Weight	13 g
Approvals Certificates	
General Product Approval	other



[Miscellaneous](#)



[Confirmation](#)

### Environment

[Environmental Con-  
firmations](#)

[Environmental Con-  
firmations](#)

### Further information

Information on the packaging  
<https://support.industry.siemens.com/cs/ww/en/view/109813875>  
 Information for data generation and storage  
<https://support.industry.siemens.com/cs/ww/en/view/109995012>  
 Information- and Downloadcenter (Catalogs, Brochures,...)  
<https://www.siemens.com/lowvoltage/catalogs>  
[Industry Mall \(Online ordering system\)](#)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5ST3768-5>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<https://support.industry.siemens.com/cs/ww/en/ps/5ST3768-5>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**

[https://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=5ST3768-5](https://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5ST3768-5)

**CAX-Online-Generator**

<https://www.siemens.com/cax>

**Tender specifications**

<https://www.siemens.com/specifications>

---

last modified:

4/11/2025 

