



Profibox I-System Schuko Increased protection 100 units Electrical white

| Model | |
|---|---|
| product brand name | DELTA |
| design of the product | SCHUKO socket outlet CEE 7/3 (type F) |
| cover version | central plate |
| design of the special power supply unit | without special current supply |
| design of the socket according to VDE 0620 for severe conditions | No |
| design of the phase tap | No |
| General technical data | |
| marking of socket outlet | without imprint |
| mounting type | fixing with claw and screw |
| surface processing | others |
| material | thermoplastic |
| Supply voltage | |
| operating voltage rated value | 250 V |
| supply voltage frequency rated value | 50 Hz |
| Protection class | |
| protection class IP | IP20 |
| Main circuit | |
| operational current rated value | 16 A |
| Appearance | |
| RAL color number (similar) | 1 013 |
| color | electric white |
| Product details | |
| product component | |
| <ul style="list-style-type: none"> • ejection equipment • labeling field • increased touch protection • residual current device • miniature fuse • integrated functional lighting • integrated light source • integrated orientation lighting • hinged lid | <ul style="list-style-type: none"> No No Yes No No No No No No |
| product feature lockable | No |
| product feature halogen-free | Yes |
| product feature transparent | No |
| Product function | |
| product function | |

| | | |
|--|----------------|-------------|
| • socket selectable | No | |
| • overvoltage protection | No | |
| Number | | |
| number of units | 1 | |
| number of sockets switchable | 0 | |
| Connections | | |
| arrangement of contacts diagonal | No | |
| type of electrical connection | plug terminal | |
| Mechanical Design | | |
| height | 500 mm | |
| width | 400 mm | |
| depth | 200 mm | |
| fastening method | flush mounting | |
| Net Weight | 8.5 kg | |
| material of the enclosure | plastic | |
| Environmental footprint | | |
| Environmental Product Declaration(EPD) | Yes | |
| global warming potential [CO2 eq] total | 4.77 kg | |
| global warming potential [CO2 eq] during manufacturing | 0.284 kg | |
| global warming potential [CO2 eq] during operation | 4.48 kg | |
| global warming potential [CO2 eq] after end of life | 7.42E-5 kg | |
| Approvals Certificates | | |
| General Product Approval | other | Environment |



[Confirmation](#)



[Environmental Confirmations](#)

Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information for data generation and storage

<https://support.industry.siemens.com/cs/ww/en/view/109995012>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mifb=5UB1558-0KE>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5UB1558-0KE>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

https://www.automation.siemens.com/bilddb/cax_en.aspx?mifb=5UB1558-0KE

CAX-Online-Generator

<https://www.siemens.com/cax>

Tender specifications

<https://www.siemens.com/specifications>

last modified:

8/19/2025

