



Style, SCHUKO socket outlet 10/16 A 250 V cover plate 68 x 68 mm malt gold

Model	
product brand name	DELTA
design of the product	SCHUKO socket outlet CEE 7/3 (type F)
cover version	central plate
design of the special power supply unit	without special current supply
design of the socket according to VDE 0620 for severe conditions	No
design of the phase tap	No
General technical data	
marking of socket outlet	without imprint
mounting type	fixing with claw and screw
surface processing	others
material	thermoplastic
Supply voltage	
operating voltage rated value	250 V
supply voltage frequency rated value	50 Hz
Protection class	
protection class IP	IP20
Main circuit	
operational current rated value	16 A
Appearance	
RAL color number (similar)	1 036
color	gold
Product details	
product component	
<ul style="list-style-type: none"> <li>● ejection equipment</li> <li>● labeling field</li> <li>● increased touch protection</li> <li>● residual current device</li> <li>● miniature fuse</li> <li>● integrated functional lighting</li> <li>● integrated light source</li> <li>● integrated orientation lighting</li> <li>● hinged lid</li> </ul>	<ul style="list-style-type: none"> <li>No</li> <li>No</li> <li>Yes</li> <li>No</li> <li>No</li> <li>No</li> <li>No</li> <li>No</li> <li>No</li> </ul>
product feature lockable	No
product feature halogen-free	Yes
product feature transparent	No
Product function	
product function	

• socket selectable	No	
• overvoltage protection	No	
<b>Number</b>		
number of units	1	
number of sockets switchable	0	
<b>Connections</b>		
arrangement of contacts diagonal	No	
type of electrical connection	plug terminal	
<b>Mechanical Design</b>		
height	70 mm	
width	70 mm	
depth	45 mm	
fastening method	flush mounting	
<b>Net Weight</b>	85 g	
material of the enclosure	plastic	
<b>Environmental footprint</b>		
Environmental Product Declaration(EPD)	Yes	
global warming potential [CO2 eq] total	4.77 kg	
global warming potential [CO2 eq] during manufacturing	0.284 kg	
global warming potential [CO2 eq] during operation	4.48 kg	
global warming potential [CO2 eq] after end of life	7.42E-5 kg	
<b>Approvals Certificates</b>		
General Product Approval	other	Environment



[Confirmation](#)



[Environmental Confirmations](#)

#### Further information

##### Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

##### Information for data generation and storage

<https://support.industry.siemens.com/cs/ww/en/view/109995012>

##### Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/lowvoltage/catalogs>

##### Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mifb=5UB1853-0MG01>

##### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5UB1853-0MG01>

##### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

[https://www.automation.siemens.com/bilddb/cax\\_en.aspx?mifb=5UB1853-0MG01](https://www.automation.siemens.com/bilddb/cax_en.aspx?mifb=5UB1853-0MG01)

##### CAX-Online-Generator

<https://www.siemens.com/cax>

##### Tender specifications

<https://www.siemens.com/specifications>

last modified:

8/19/2025

