



Figure similar

spare part SIPLUS S7-300 SM 332 4 AO U/I based on 6ES7332-5HD01-0AB0 with conformal coating, -25...+70 °C, analog output SM 332, isolated, 4 AO, U/I; diagnostics; resolution 11/12 bits, 20-pole, removing and inserting with active backplane bus possible

General information	
based on	6ES7332-5HD01-0AB0
Supply voltage	
Load voltage L+	
<ul style="list-style-type: none"> Rated value (DC) 	24 V
<ul style="list-style-type: none"> Reverse polarity protection 	Yes
Input current	
from load voltage L+ (without load), max.	240 mA
from backplane bus 5 V DC, max.	60 mA
Power loss	
Power loss, typ.	3 W
Analog outputs	
Number of analog outputs	4
Voltage output, short-circuit protection	Yes
Voltage output, short-circuit current, max.	25 mA
Current output, no-load voltage, max.	18 V
Output ranges, voltage	
<ul style="list-style-type: none"> 0 to 10 V 	Yes
<ul style="list-style-type: none"> 1 V to 5 V 	Yes
<ul style="list-style-type: none"> -10 V to +10 V 	Yes
Output ranges, current	
<ul style="list-style-type: none"> 0 to 20 mA 	Yes
<ul style="list-style-type: none"> -20 mA to +20 mA 	Yes
<ul style="list-style-type: none"> 4 mA to 20 mA 	Yes
Load impedance (in rated range of output)	
<ul style="list-style-type: none"> with voltage outputs, min. 	1 kΩ
<ul style="list-style-type: none"> with voltage outputs, capacitive load, max. 	1 μF
<ul style="list-style-type: none"> with current outputs, max. 	500 Ω
<ul style="list-style-type: none"> with current outputs, inductive load, max. 	10 mH
Cable length	
<ul style="list-style-type: none"> shielded, max. 	200 m
Analog value generation for the outputs	
Integration and conversion time/resolution per channel	
<ul style="list-style-type: none"> Resolution with overrange (bit including sign), max. 	12 bit; ±10 V, ±20 mA, 4 mA to 20 mA, 1 V to 5 V: 11 bit + sign; 0 V to 10 V, 0 mA to 20 mA: 12 bit
<ul style="list-style-type: none"> Conversion time (per channel) 	0.8 ms
Settling time	
<ul style="list-style-type: none"> for resistive load 	0.2 ms

<ul style="list-style-type: none"> • for capacitive load 	3.3 ms
<ul style="list-style-type: none"> • for inductive load 	0.5 ms; 0.5 ms (1 mH); 3.3 ms (10 mH)
Errors/accuracies	
Operational error limit in overall temperature range	
<ul style="list-style-type: none"> • Voltage, relative to output range, (+/-) 	0.5 %; ±0.6 % @ < 0 °C or > 60 °C
<ul style="list-style-type: none"> • Current, relative to output range, (+/-) 	0.6 %; ±0.7 % @ < 0 °C or > 60 °C
Basic error limit (operational limit at 25 °C)	
<ul style="list-style-type: none"> • Voltage, relative to output range, (+/-) 	0.4 %
<ul style="list-style-type: none"> • Current, relative to output range, (+/-) 	0.5 %
Interrupts/diagnostics/status information	
Diagnostics function	Yes; Parameterizable
Alarms	
<ul style="list-style-type: none"> • Diagnostic alarm 	Yes; Parameterizable
Diagnoses	
<ul style="list-style-type: none"> • Diagnostic information readable 	Yes
Diagnostics indication LED	
<ul style="list-style-type: none"> • Group error SF (red) 	Yes
Potential separation	
Potential separation analog outputs	
<ul style="list-style-type: none"> • between the channels 	No
<ul style="list-style-type: none"> • between the channels and backplane bus 	Yes
<ul style="list-style-type: none"> • Between the channels and load voltage L+ 	Yes
<ul style="list-style-type: none"> • between the channels and the power supply of the electronics 	Yes
Isolation	
Isolation tested with	500 V DC
Standards, approvals, certificates	
CE mark	Yes
UL approval	Yes; File E239877
RCM (formerly C-TICK)	Yes
KC approval	Yes
EAC (formerly Gost-R)	Yes
Railway application	
<ul style="list-style-type: none"> • EN 50121-4 	No
<ul style="list-style-type: none"> • EN 50155 	No
Ambient conditions	
Ambient temperature during operation	
<ul style="list-style-type: none"> • min. 	-25 °C; = Tmin
<ul style="list-style-type: none"> • max. 	70 °C; = Tmax; 60 °C @ UL/cUL, ATEX and FM use
Ambient temperature during storage/transportation	
<ul style="list-style-type: none"> • min. 	-40 °C
<ul style="list-style-type: none"> • max. 	70 °C
Altitude during operation relating to sea level	
<ul style="list-style-type: none"> • Installation altitude above sea level, max. 	5 000 m
<ul style="list-style-type: none"> • Ambient air temperature-barometric pressure-altitude 	Tmin ... Tmax at 1 140 hPa ... 795 hPa (-1 000 m ... +2 000 m) // Tmin ... (Tmax - 10 K) at 795 hPa ... 658 hPa (+2 000 m ... +3 500 m) // Tmin ... (Tmax -20 K) at 658 hPa ... 540 hPa (+3 500 m ... +5 000 m)
Relative humidity	
<ul style="list-style-type: none"> • With condensation, tested in accordance with IEC 60068-2-38, max. 	100 %; RH incl. condensation/frost (no commissioning under condensation conditions)
Resistance	
Use in stationary industrial systems	
<ul style="list-style-type: none"> — to biologically active substances according to EN 60721-3-3 	Yes; Class 3B2 mold, fungus and dry rot spores (with the exception of fauna); Class 3B3 on request
<ul style="list-style-type: none"> — to chemically active substances according to EN 60721-3-3 	Yes; Class 3C4 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *
<ul style="list-style-type: none"> — to mechanically active substances according to EN 60721-3-3 	Yes; Class 3S4 incl. sand, dust, *
Use on ships/at sea	
<ul style="list-style-type: none"> — to biologically active substances according to EN 60721-3-6 	Yes; Class 6B2 mold and fungal spores (excluding fauna); Class 6B3 on request

— to chemically active substances according to EN 60721-3-6
 — to mechanically active substances according to EN 60721-3-6

Yes; Class 6C3 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *
 Yes; Class 6S3 incl. sand, dust; *

Usage in industrial process technology

— Against chemically active substances acc. to EN 60654-4

Yes; Class 3 (excluding trichlorethylene)

— Environmental conditions for process, measuring and control systems acc. to ANSI/ISA-71.04

Yes; Level GX group A/B (excluding trichlorethylene; harmful gas concentrations up to the limits of EN 60721-3-3 class 3C4 permissible); level LC3 (salt spray) and level LB3 (oil)

Remark

— Note regarding classification of environmental conditions acc. to EN 60721, EN 60654-4 and ANSI/ISA-71.04

* The supplied plug covers must remain in place over the unused interfaces during operation!

Connection method

required front connector 20-pin

Dimensions

Width 40 mm
 Height 125 mm
 Depth 120 mm

Weights

Weight, approx. 220 g

Classifications

	Version	Classification
eClass	14	27-24-22-01
eClass	12	27-24-22-01
eClass	9.1	27-24-22-01
eClass	9	27-24-22-01
eClass	8	27-24-22-01
eClass	7.1	27-24-22-01
eClass	6	27-24-22-01
ETIM	10	EC001420
ETIM	9	EC001420
ETIM	8	EC001420
ETIM	7	EC001420
IDEA	4	3562
UNSPSC	15	32-15-17-05

Approvals / Certificates

General Product Approval

EMV



[Manufacturer Declaration](#)



[China RoHS](#)



[KC](#)

EMV

For use in hazardous locations



[CCC-Ex](#)

last modified:

5/29/2024