

SIMATIC HMI MTP1900 PRO, for support arm (not expandable, flange on top), 18.5" widescreen TFT display, 16 million colors, PROFINET interface, configurable as of WinCC Unified Comfort V18, contains open-source software, which is provided free of charge



| General information | |
|---|-----------------------------|
| Product type designation | MTP1900 Unified Comfort PRO |
| Display | |
| Design of display | TFT |
| Screen diagonal | 18.5 in |
| Display width | 409 mm |
| Display height | 230 mm |
| Number of colors | 16 777 216 |
| Resolution (pixels) | |
| • Horizontal image resolution | 1 920 pixel |
| • Vertical image resolution | 1 080 pixel |
| Backlighting | |
| • MTBF backlighting (at 25 °C) | 50 000 h |
| • Backlight dimmable | Yes; 10 ... 100% |
| Control elements | |
| Keyboard fonts | |
| • Numeric keyboard | Yes; Onscreen keyboard |
| • alphanumeric keyboard | Yes; Onscreen keyboard |
| Touch operation | |
| • Design as touch screen | Yes |
| • Design as multi-touch screen | Yes |
| Installation type/mounting | |
| Mounting | Support arm |
| Mounting position | vertical |
| Mounting in portrait format possible | No |
| Mounting in landscape format possible | Yes |
| maximum permissible angle of inclination without external ventilation | 35° |
| Supply voltage | |
| Type of supply voltage | DC |
| Rated value (DC) | 24 V |
| permissible range, lower limit (DC) | 19.2 V |
| permissible range, upper limit (DC) | 28.8 V |
| Input current | |
| Current consumption (rated value) | 1.2 A |
| Current consumption, max. | 1.7 A |
| Starting current inrush I ² t | 0.5 A ² ·s |
| Power | |
| Active power input, typ. | 28.8 W |
| Processor | |

| | |
|--|---|
| Processor type | X86 |
| Memory | |
| Flash | Yes |
| RAM | Yes |
| Type of output | |
| Info LED | No |
| Power LED | No |
| Error LED | No |
| Acoustics | |
| • Buzzer | Yes |
| • Speaker | No |
| Time of day | |
| Clock | |
| • Hardware clock (real-time) | Yes |
| • Software clock | Yes |
| • retentive | Yes; Back-up duration typically 6 weeks |
| • synchronizable | Yes |
| Interfaces | |
| Number of industrial Ethernet interfaces | 2; 2 ports (switch) + independent port |
| Number of RS 485 interfaces | 1; RS 422 / 485 combined |
| Number of RS 422 interfaces | 0; together with RS 485 |
| Number of USB interfaces | 4; USB 3.1 Gen. 1 (type A) |
| Number of SD card slots | 2 |
| Industrial Ethernet | |
| • Industrial Ethernet status LED | 2 |
| • Number of ports of the integrated switch | 2 |
| Protocols | |
| PROFINET | Yes |
| Supports protocol for PROFINET IO | No |
| Protocols (Ethernet) | |
| • TCP/IP | Yes |
| • DHCP | Yes |
| • SNMP | Yes |
| • DCP | Yes |
| • LLDP | Yes |
| Redundancy mode | |
| Media redundancy | |
| — MRP | Yes |
| Further protocols | |
| • CAN | No |
| EMC | |
| Emission of radio interference acc. to EN 55 011 | |
| • Limit class A, for use in industrial areas | Yes |
| • Limit class B, for use in residential areas | No |
| Degree and class of protection | |
| IP (at the front) | IP65 |
| IP (rear) | IP65 |
| NEMA (front) | |
| • Enclosure Type 4 at the front | Yes |
| • Enclosure Type 4x at the front | Yes |
| • Enclosure Type 12 at the front | Yes |
| Standards, approvals, certificates | |
| CE mark | Yes |
| UKCA mark | Yes |
| cULus | Yes |
| FM approval | Yes |
| RCM (formerly C-TICK) | Yes |
| KC approval | Yes |
| EAC (formerly Gost-R) | Yes |
| CCC | Yes |

| | |
|--|-----------------------|
| Use in hazardous areas | |
| • ATEX Zone 2 | Yes |
| • ATEX Zone 22 | Yes |
| • IECEx Zone 2 | Yes |
| • IECEx Zone 22 | Yes |
| • cULus Class I Zone 2, Division 2 | Yes |
| • cULus Class II Division 2 | No |
| • FM Class I Division 2 | Yes |
| • FM Class II Division 2 | No |
| Marine approval | |
| • Germanischer Lloyd (GL) | No |
| • American Bureau of Shipping (ABS) | No |
| • Bureau Veritas (BV) | No |
| • Det Norske Veritas (DNV) | No |
| • Korean Register of Shipping (KRS) | No |
| • Lloyds Register of Shipping (LRS) | No |
| • Nippon Kaiji Kyokai (Class NK) | No |
| • Polski Rejestr Statkow (PRS) | No |
| • Chinese Classification Society (CCS) | No |
| Ambient conditions | |
| Ambient temperature during operation | |
| Operation (vertical installation) | |
| — For vertical installation, min. | 0 °C |
| — For vertical installation, max. | 45 °C |
| Operation (max. tilt angle) | |
| — At maximum tilt angle, min. | 0 °C |
| — At maximum tilt angle, max. | 40 °C |
| Ambient temperature during storage/transportation | |
| • min. | -20 °C |
| • max. | 60 °C |
| Relative humidity | |
| • Operation, max. | 90 %; no condensation |
| Operating systems | |
| proprietary | Yes |
| configuration / header | |
| Message indicator | Yes |
| Alarm system (incl. buffer and acknowledgment) | Yes |
| Process value display (output) | Yes |
| Process value default (input) possible | Yes |
| Recipe management | Yes |
| Configuration software | |
| • STEP 7 Basic (TIA Portal) | No |
| • STEP 7 Professional (TIA Portal) | No |
| • WinCC flexible Compact | No |
| • WinCC flexible Standard | No |
| • WinCC flexible Advanced | No |
| • WinCC Basic (TIA Portal) | No |
| • WinCC Comfort (TIA Portal) | No |
| • WinCC Advanced (TIA Portal) | No |
| • WinCC Professional (TIA Portal) | No |
| • WinCC Unified Basic Engineering (TIA Portal) | No |
| • WinCC Unified Comfort Engineering (TIA Portal) | Yes; V18 or higher |
| • WinCC Unified PC Engineering (TIA Portal) | Yes; V18 or higher |
| Languages | |
| Online languages | |
| • Number of online/runtime languages | 32 |
| Project languages | |
| • Languages per project | 32 |
| Functionality under WinCC Unified | |
| Libraries | Yes |

| | |
|--|----------------------------------|
| Applications/options | |
| • Writer | Yes |
| • Calc | Yes |
| • Web browser | Yes |
| • PDF Viewer | Yes |
| • Media Player | Yes |
| • SIMATIC WinCC Sm@rtServer | Yes |
| • SIMATIC WinCC Audit | Yes |
| • Unified Collaboration | Yes |
| Number of Visual Basic Scripts | No |
| JavaScript | Yes |
| Task planner | |
| • time-controlled | Yes |
| • task-controlled | Yes |
| Help system | |
| • Number of characters per info text | 70 |
| • Number of message texts per message | 10 |
| functionality under WinCC Unified / alarm system / header | |
| • Number of alarm classes | 32 |
| • Bit messages | |
| — Number of bit messages | 9 000 |
| • Analog messages | |
| — Number of analog messages | 300 |
| • S7 alarm number procedure | Yes |
| • System messages HMI | Yes |
| • System event, more (SIMATIC S7, SINUMERIK, SIMOTION, ...) | Yes |
| • Number of characters per message | 512 |
| • Number of process values per message | 10 |
| • Acknowledgment groups | Yes |
| • Message indicator | No |
| • Message buffer | Yes; Configured as alarm archive |
| — Circulating buffer | Yes |
| — retentive | Yes |
| — maintenance-free | Yes |
| Parameter set management (recipes) | |
| • Number of parameter set types | 750 |
| • Parameter sets per parameter set type | 2 000 |
| • Entries per parameter set | 1 000 |
| • Size of internal parameter set memory | 12 Mbyte |
| • Parameter set memory expandable | Yes |
| functionality under WinCC Unified / variables / header | |
| • Number of variables per device | 8 000 |
| • Number of variables per screen | 800 |
| • Limit values | Yes |
| • Structures | Yes |
| • Arrays | Yes |
| functionality under WinCC Unified / screens / header | |
| • Number of configurable images | 1 200 |
| • Faceplate | Yes |
| Image objects | |
| • Number of objects per image | 1 200 |
| • Picture window | Yes |
| • Text fields | Yes |
| • I/O fields | Yes |
| • Graphic I/O fields (graphics list) | Yes |
| • Symbolic I/O fields (text list) | Yes |
| • Scalable Vector Graphics (SVG) | Yes |
| • Date/time fields | Yes |
| • Checkbox | Yes |
| • Option button | Yes |

| | |
|---|--|
| • Switches | Yes |
| • Buttons | Yes |
| • Graphic display | Yes |
| • Icons | Yes |
| • Custom web display | Yes |
| • Geometric objects | Yes |
| functionality under WinCC Unified / complex screen objects / header | |
| • Number of complex objects per screen | 80 |
| • Alarm view | Yes |
| • Trend view | Yes |
| • User view | Yes |
| • Status/control | Yes |
| • Parameter set display | Yes |
| • HTML browser | Yes |
| • Bar graphs | Yes |
| • Sliders | Yes |
| • Pointer instruments | Yes |
| • Analog/digital clock | Yes |
| functionality under WinCC Unified / lists / header | |
| • Number of text lists per project | 750 |
| • Number of entries per text list | 750 |
| • Number of graphics lists per project | 750 |
| • Number of entries per graphics list | 750 |
| functionality under WinCC Unified / archiving / header | |
| • Number of archives per device | 50 |
| • Number of entries per archive | 500 000 |
| • Message archive | Yes |
| • Process value archive | Yes |
| • type of archiving / for WinCC Unified | |
| — Sequential archive | Yes |
| — Short-term archive | Yes |
| • storage location / of archiving / for WinCC Unified | |
| — Memory card | Yes |
| — USB memory | Yes |
| — Ethernet | No |
| Security | |
| • Number of roles | 50 |
| • Number of function rights | 20; number of predefined function rights |
| • Number of users | 200 |
| • Password export/import | Yes |
| • Central user administration | Yes |
| functionality under WinCC Unified / transfer (upload/download) / header | |
| • USB | No |
| • Ethernet | Yes |
| • using external storage medium | Yes |
| Process coupling | |
| • S7-1200 | Yes |
| • S7-1500 | Yes |
| • S7-200 | No |
| • S7-300/400 | Yes |
| • Number of S7 connections | 16 |
| • LOGO! | No |
| • SIMOTION | No |
| • OPC UA Client | Yes |
| • OPC UA Server | Yes |
| • Software Controller/Open Controller | Yes |
| functionality under WinCC Unified / service tools/configuration tools / header | |
| • Backup/Restore manually | Yes |
| • Backup/Restore automatically | Yes |
| • Simulation | Yes |
| • Device switchover | Yes |

Peripherals/Options

| | |
|--|-------------------------|
| Peripherals | Printer, barcode reader |
| Printer | Yes |
| SIMATIC HMI MM memory card: Multi Media Card | No |
| SIMATIC HMI SD memory card: Secure Digital memory card | Yes |
| SIMATIC HMI CF memory card Compact Flash Card | No |
| USB memory | Yes |
| SIMATIC IPC USB Flashdrive (USB stick) | Yes |
| SIMATIC HMI USB stick | Yes |
| Network camera | Yes |

Mechanics/material

| | |
|--|--------------------------------|
| Enclosure material (front) | |
| <ul style="list-style-type: none"> • Plastic • Aluminum • Stainless steel | <p>No</p> <p>Yes</p> <p>No</p> |

Dimensions

| | |
|----------------------------|-------------------------------|
| Width of the housing front | 462 mm |
| Height of housing front | 292 mm; Without basic adapter |

Weights

| | |
|----------------------------|--------|
| Weight (without packaging) | 7.1 kg |
|----------------------------|--------|

Classifications

| | Version | Classification |
|--------|---------|----------------|
| eClass | 14 | 27-33-02-01 |
| eClass | 12 | 27-33-02-01 |
| eClass | 9.1 | 27-33-02-01 |
| eClass | 9 | 27-33-02-01 |
| eClass | 8 | 27-24-23-02 |
| eClass | 7.1 | 27-24-23-02 |
| eClass | 6 | 27-24-23-02 |
| ETIM | 10 | EC001412 |
| ETIM | 9 | EC001412 |
| ETIM | 8 | EC001412 |
| ETIM | 7 | EC001412 |

Approvals / Certificates

General Product Approval



[Miscellaneous](#)



[KC](#)

For use in hazardous locations



[FM](#)

For use in hazardous locations

[CCC-Ex](#)

last modified:

6/24/2025