

service pack for PP7, PP17 I, PP17 II, scope of supply: 1 built-in seal PP7, 1 built-in seal PP17, 5 plastic mounting clips 1 24 V DC plug 2-pole, 1 24 V DC plug 3-pole, 1 plug 4-pole, 2 plugs 16-pole



General information	
Product type designation	Service pack
Standards, approvals, certificates	
CE mark	Yes
Ambient conditions	
Ambient temperature during operation	
• min.	0 °C
• max.	55 °C
Ambient temperature during storage/transportation	
• min.	-20 °C
• max.	70 °C
Relative humidity	
• Operation, max.	95 %
Scope of supply	
Delivery quantity in pieces	
• Parts per unit	1; Content: 1x mounting seal PP7, 1x mounting seal PP17, 5x plastic mounting clip, 1x 2-pin female connector, 1x 3-pin female connector, 1x 4-pin female connector, 2x 16-pin female connector
Other	
Note:	for PP7, PP17-I, PP17-II

Classifications			
		Version	Classification
	eClass	14	27-33-02-92
	eClass	12	27-33-02-92
	eClass	9.1	27-33-02-92
	eClass	9	27-33-02-92
	eClass	8	27-24-92-03
	eClass	7.1	27-24-92-03
	eClass	6	27-24-92-03
	ETIM	10	EC002584
	ETIM	9	EC002584
	ETIM	8	EC002584
	ETIM	7	EC002584
	IDEA	4	3552
	UNSPSC	15	32-15-17-03

Further information	
Usable in the following products: Detailed information can be found in the cross-list, which is available for download in the following SIOS	

note: 40466415

<https://support.industry.siemens.com/cs/document/40466415/status-of-the-simatic-hmi-accessories-and-cross-list-update?dti=0&lc=en-VW>

last modified:

5/22/2024 