

icotek cable sleeve, 8+8 mm, color: gray, scope of supply: 5 cable sleeves



| General information                                |  |
|--|--|
| Product type designation                           | icotek cable grommet, 8+8                    |
| Control elements                                   |  |
| Frame size/design                                  |  |
| • Standard   | Yes; icotek cable grommet                    |
| Degree and class of protection                     |  |
| IP (all-round)                                     | IP54 (EN60529)                               |
| Standards, approvals, certificates                 |  |
| UL approval  | Yes; UL Type12 (UL 50E)                      |
| REACH  | Yes  |
| RoHS conformity                                    | Yes  |
| Ambient conditions                                 |  |
| Ambient temperature during operation               |  |
| • min.   | -40 °C                                       |
| • max.   | 100 °C                                       |
| Operation (vertical installation)                  |  |
| — For vertical installation, min.                  | -40 °C                                       |
| — For vertical installation, max.                  | 100 °C                                       |
| Operation (max. tilt angle)                        |  |
| — At maximum tilt angle, min.                      | -40 °C                                       |
| — At maximum tilt angle, max.                      | 100 °C                                       |
| Operation (vertical installation, portrait format) |  |
| — For vertical installation, min.                  | -40 °C                                       |
| — For vertical installation, max.                  | 100 °C                                       |
| Operation (max. tilt angle, portrait format)       |  |
| — At maximum tilt angle, min.                      | -40 °C                                       |
| — At maximum tilt angle, max.                      | 100 °C                                       |
| Ambient temperature during storage/transportation  |  |
| • min.   | -20 °C                                       |
| • max.   | 60 °C  |
| Mechanics/material                                 |  |
| Material   |  |
| • Plastic  | Yes  |
| Enclosure material (front)                         |  |
| • Plastic  | Yes; fire class: UL94-V0, self-extinguishing |
| Color  | gray (similar to RAL 7035)                   |
| Dimensions   |  |
| Width  | 21 mm  |
| Height   | 21 mm  |

|                             |  |
|-----------------------------|--|
| Depth                       | 19 mm  |
| Diameter                    | 8 mm; 2x 8 mm, cable in a grommet                                |
| <b>Weights</b>              |  |
| Weight, approx.             | 8 g; Per unit  |
| Weight (without packaging)  | 40 g   |
| Weight (with packaging)     | 45 g   |
| <b>Scope of supply</b>      |  |
| Delivery quantity in pieces | 5; Units per set   |
| <b>Other</b>                |  |
| Merchandise                 | Yes; KT2/8gy 39917   |
| Manufacturer name           | icotek GmbH  |
| Manufacturer's address      | Bischof-von-Lipp-Str. 1, 73569 Eschach, Deutschland              |
| Target devices              | icotek cable entry and cable gland                               |
| Note:                       | further information is available on the manufacturer's homepage. |

| <b>Classifications</b> |        |                |                       |
|------------------------|--------|----------------|-----------------------|
|                        |        | <b>Version</b> | <b>Classification</b> |
|                        | eClass | 14             | 27-33-02-92           |
|                        | eClass | 12             | 27-33-02-92           |
|                        | eClass | 9.1            | 27-33-02-92           |
|                        | eClass | 9              | 27-33-02-92           |
|                        | eClass | 8              | 27-24-92-03           |
|                        | eClass | 7.1            | 27-24-92-03           |
|                        | eClass | 6              | 27-24-92-03           |
|                        | ETIM   | 10             | EC002584              |
|                        | ETIM   | 9              | EC002584              |
|                        | ETIM   | 8              | EC002584              |
|                        | ETIM   | 7              | EC002584              |
|                        | IDEA   | 4              | 3552                  |
|                        | UNSPSC | 15             | 32-15-17-03           |

**Further information**

Usable in the following products: Detailed information can be found in the cross-list, which is available for download in the following SIOS note: **40466415**  
<https://support.industry.siemens.com/cs/document/40466415/status-of-the-simatic-hmi-accessories-and-cross-list-update?dti=0&lc=en-VW>

last modified:

5/6/2025 