



SIMATIC ET 200SP HA, terminal block, type N0, 64 push-in terminals, Width: 45 mm

Figure similar

General information		
Product type designation	Type N0	
Product function		
• I&M data	Yes	
Supply voltage		
Rated value (DC)	24 V	
Current carrying capacity		
up to 70 °C, max.	10 A; Permitted load current of the potential group depending on the number of terminal blocks	
For process terminals, max.	2 A	
Hardware configuration		
Formation of potential groups		
• support of potential groups	Yes	
• New potential group	No	
• Potential group continued from the left	Yes	
Slots		
• Number of slots	1	
Potential separation		
between backplane bus and supply voltage	Yes; 3 000 V DC/1 min, type test	
between potential groups (power bus)	Yes; 1 500 V DC/1 min, type test (SELV / PELV to functional ground FE)	
between process terminals and supply voltage	Yes; 1 500 V DC/1 min, type test	
Ambient conditions		
Ambient temperature during operation		
• horizontal installation, min.	-40 °C	
• horizontal installation, max.	70 °C	
• vertical installation, min.	-40 °C	
• vertical installation, max.	60 °C	
Dimensions		
Width	45 mm	
Height	175 mm	
Depth	77 mm	
Weights		
Weight, approx.	155 g	
Classifications		
	Version	Classification
eClass	14	27-24-26-07
eClass	12	27-24-26-07

eClass	9.1	27-24-26-07
eClass	9	27-24-26-07
eClass	8	27-24-26-07
eClass	7.1	27-24-26-07
eClass	6	27-24-26-07
ETIM	10	EC001603
ETIM	9	EC001603
ETIM	8	EC001603
ETIM	7	EC001603

Approvals / Certificates

General Product Approval



[Miscellaneous](#)



[China RoHS](#)



[KC](#)

General Product Approval

For use in hazardous locations



[Declaration of Con-
formity](#)



For use in hazardous locations

Maritime application



[Miscellaneous](#)



Maritime application

Environment



[NK / Nippon Kaiji Ky-
okai](#)

[CCS \(China Classifica-
tion Society\)](#)

Siemens
EcoTech



last modified:

10/23/2025