



LOGO! AM2 RTD expansion module, PS: 12/24 V DC, 2AI-50...+200°C
Pt100/1000 for LOGO! 8

Installation type/mounting	
Mounting	on 35 mm DIN rail, 2 spacing units wide
Supply voltage	
Rated value (DC)	
• 12 V DC	Yes; 10.8 V DC to 28.8 V DC
• 24 V DC	Yes; 10.8 V DC to 28.8 V DC
Input current	
Current consumption, typ.	30 mA
Analog inputs	
Number of analog inputs	2; 2 or 3 wire connection
Input ranges	
• Voltage	No
• Current	No
• Resistance thermometer	Yes; For PT100/PT1000 sensors
Input ranges (rated values), voltages	
• 0 to +10 V	No
Input ranges (rated values), currents	
• 0 to 20 mA	No
Input ranges (rated values), resistance thermometer	
• Pt 100	Yes
EMC	
Emission of radio interference acc. to EN 55 011	
• Limit class B, for use in residential areas	Yes
Degree and class of protection	
IP degree of protection	IP20
Standards, approvals, certificates	
CE mark	Yes
CSA approval	Yes
UL approval	Yes
FM approval	Yes
developed in accordance with IEC 61131	Yes
Marine approval	Yes
Ecological footprint	
• environmental product declaration	Yes
Global warming potential	
— global warming potential, (total) [CO2 eq]	16.5 kg
— global warming potential, (during production) [CO2 eq]	3.22 kg
— global warming potential, (during operation) [CO2 eq]	13.4 kg

— global warming potential, (after end of life cycle) [CO2 eq]		-0.124 kg	
Ambient conditions			
Ambient temperature during operation			
• min.		-20 °C; No condensation	
• max.		55 °C	
Dimensions			
Width		35.5 mm	
Height		90 mm	
Depth		58 mm	
Classifications			
		Version	Classification
	eClass	14	27-24-22-01
	eClass	12	27-24-22-01
	eClass	9.1	27-24-22-01
	eClass	9	27-24-22-01
	eClass	8	27-24-22-01
	eClass	7.1	27-24-22-01
	eClass	6	27-24-22-01
	ETIM	10	EC001420
	ETIM	9	EC001420
	ETIM	8	EC001420
	ETIM	7	EC001420
	IDEA	4	3562
	UNSPSC	15	32-15-17-05
Approvals / Certificates			
General Product Approval			



[China RoHS](#)



[Miscellaneous](#)