



SIMATIC ET 200SP, digital combined module, DI 8x/DQ 8x24 V DC/0.5 A standard, DI: sink input, (sinking input), DQ: source output (sourcing output) suitable for BU type A0, color code CC00, substitute value output for DQ, module diagnostics for: short circuit to L+ and M, wire break, supply voltage

General information	
Product type designation	DI 8x/DQ 8x24VDC/0,5A ST
HW functional status	FS01
Firmware version	V1.0
• FW update possible	Yes
usable BaseUnits	BU type A0
Color code for module-specific color identification plate	CC00
Product function	
• I&M data	Yes; I&M0 to I&M3
• Isochronous mode	No
Engineering with	
• STEP 7 TIA Portal configurable/integrated from version	STEP 7 V18 or higher with HSP 0401
• PROFIBUS from GSD version/GSD revision	One GSD file each, Revision 3 and 5 and higher
• PROFINET from GSD version/GSD revision	GSDML V2.42
Operating mode	
• DI	Yes
• DQ	Yes
• DQ with energy-saving function	No
• PWM	No
• Oversampling	No
• MSO	No
Redundancy	
• Redundancy capability	No
Supply voltage	
Rated value (DC)	24 V
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V
Reverse polarity protection	Yes
Input current	
Current consumption, max.	35 mA; without load
output voltage / header	
Rated value (DC)	24 V
Power loss	
Power loss, typ.	1 W
Address area	
Address space per module	
• Inputs	1 byte; + 1 byte for QI information
• Outputs	1 byte
Hardware configuration	
Automatic encoding	Yes

<ul style="list-style-type: none"> • Mechanical coding element 	Yes
<ul style="list-style-type: none"> • Type of mechanical coding element 	Type A
Selection of BaseUnit for connection variants	
<ul style="list-style-type: none"> • 1-wire connection 	BU type A0
<ul style="list-style-type: none"> • 2-wire connection 	BU type A0 with AUX terminals or potential distributor module
<ul style="list-style-type: none"> • 3-wire connection 	BU type A0 with AUX terminals or potential distributor module
Digital inputs	
Number of digital inputs	8
Digital inputs, parameterizable	Yes
Source/sink input	P-reading
Input characteristic curve in accordance with IEC 61131, type 1	Yes
Input characteristic curve in accordance with IEC 61131, type 3	Yes
Input voltage	
<ul style="list-style-type: none"> • Rated value (DC) 	24 V
<ul style="list-style-type: none"> • for signal "0" 	-30 to +5 V
<ul style="list-style-type: none"> • for signal "1" 	+11 to +30V
Input current	
<ul style="list-style-type: none"> • for signal "1", typ. 	2.5 mA
Input delay (for rated value of input voltage)	
for standard inputs	
— parameterizable	Yes; 0.05 / 0.1 / 0.4 / 0.8 / 1.6 / 3.2 / 12.8 / 20 ms
— at "0" to "1", min.	0.05 ms
— at "0" to "1", max.	20 ms
— at "1" to "0", min.	0.05 ms
— at "1" to "0", max.	20 ms
Cable length	
<ul style="list-style-type: none"> • shielded, max. 	1 000 m
<ul style="list-style-type: none"> • unshielded, max. 	600 m
Digital outputs	
Type of digital output	Source output (PNP, current-sourcing)
Number of digital outputs	8
Current-sourcing	Yes
Digital outputs, parameterizable	Yes
output type acc. to IEC 61131, type 0.5	Yes
Short-circuit protection	Yes; Electronic
<ul style="list-style-type: none"> • Response threshold, typ. 	1 A
Limitation of inductive shutdown voltage to	Typ. L+ (-50 V)
Controlling a digital input	Yes
Switching capacity of the outputs	
<ul style="list-style-type: none"> • with resistive load, max. 	0.5 A
<ul style="list-style-type: none"> • with inductive load, max. 	0.5 A; max. 1 H inductance
<ul style="list-style-type: none"> • on lamp load, max. 	5 W
Load resistance range	
<ul style="list-style-type: none"> • lower limit 	48 Ω
<ul style="list-style-type: none"> • upper limit 	12 kΩ
Output voltage	
<ul style="list-style-type: none"> • for signal "1", min. 	L+ (-0.8 V)
Output current	
<ul style="list-style-type: none"> • for signal "1" rated value 	0.5 A
<ul style="list-style-type: none"> • for signal "1" permissible range, max. 	0.5 A
<ul style="list-style-type: none"> • for signal "0" residual current, max. 	0.1 mA
Output delay with resistive load	
<ul style="list-style-type: none"> • "0" to "1", max. 	50 μs
<ul style="list-style-type: none"> • "1" to "0", max. 	100 μs
Parallel switching of two outputs	
<ul style="list-style-type: none"> • for uprating 	No
<ul style="list-style-type: none"> • for redundant control of a load 	Yes
Switching frequency	
<ul style="list-style-type: none"> • with resistive load, max. 	100 Hz
<ul style="list-style-type: none"> • with inductive load (acc. to IEC 60947-5-1, DC13), max. 	0.1 Hz; higher frequencies are possible, see Equipment Manual "Maximum permitted switching frequency of inductive loads"

<ul style="list-style-type: none"> • on lamp load, max. 	10 Hz
Total current of the outputs	
<ul style="list-style-type: none"> • Current per channel, max. 	0.5 A
<ul style="list-style-type: none"> • Current per module, max. 	4 A
Total current of the outputs (per module)	
horizontal installation	
<ul style="list-style-type: none"> — up to 60 °C, max. 	4 A
vertical installation	
<ul style="list-style-type: none"> — up to 50 °C, max. 	4 A
Cable length	
<ul style="list-style-type: none"> • shielded, max. 	1 000 m
<ul style="list-style-type: none"> • unshielded, max. 	600 m
Encoder	
Connectable encoders	
<ul style="list-style-type: none"> • 2-wire sensor 	Yes
<ul style="list-style-type: none"> — permissible quiescent current (2-wire sensor), max. 	1.5 mA
Interrupts/diagnostics/status information	
Diagnostics function	Yes
Substitute values connectable	Yes
Alarms	
<ul style="list-style-type: none"> • Diagnostic alarm 	Yes
Diagnoses	
<ul style="list-style-type: none"> • Monitoring the supply voltage 	Yes
<ul style="list-style-type: none"> • Wire-break 	Yes; module-by-module, for DI: optional protective circuit for preventing wire-break diagnostics in the case of simple encoder contacts: 25 kOhm to 45 kOhm
<ul style="list-style-type: none"> • Short-circuit to M 	Yes; module-by-module for DQ
<ul style="list-style-type: none"> • Short-circuit to L+ 	Yes; module-by-module for DQ
<ul style="list-style-type: none"> • Group error 	Yes
Diagnostics indication LED	
<ul style="list-style-type: none"> • Monitoring of the supply voltage (PWR-LED) 	Yes; green PWR LED
<ul style="list-style-type: none"> • Channel status display 	Yes; green LED
<ul style="list-style-type: none"> • for channel diagnostics 	No
<ul style="list-style-type: none"> • for module diagnostics 	Yes; green/red DIAG LED
Potential separation	
Potential separation channels	
<ul style="list-style-type: none"> • between the channels 	No
<ul style="list-style-type: none"> • between the channels and backplane bus 	Yes
<ul style="list-style-type: none"> • between the channels and the power supply of the electronics 	No
Isolation	
Isolation tested with	707 V DC (type test)
Standards, approvals, certificates	
Suitable for safety functions	No
Ecological footprint	
<ul style="list-style-type: none"> • environmental product declaration 	Yes
Global warming potential	
<ul style="list-style-type: none"> — global warming potential, (total) [CO2 eq] 	21 kg
<ul style="list-style-type: none"> — global warming potential, (during production) [CO2 eq] 	4.25 kg
<ul style="list-style-type: none"> — global warming potential, (during operation) [CO2 eq] 	1.75 kg
<ul style="list-style-type: none"> — global warming potential, (after end of life cycle) [CO2 eq] 	-0.743 kg
Ambient conditions	
Ambient temperature during operation	
<ul style="list-style-type: none"> • horizontal installation, min. 	-30 °C
<ul style="list-style-type: none"> • horizontal installation, max. 	60 °C
<ul style="list-style-type: none"> • vertical installation, min. 	-30 °C
<ul style="list-style-type: none"> • vertical installation, max. 	50 °C
Altitude during operation relating to sea level	
<ul style="list-style-type: none"> • Installation altitude above sea level, max. 	5 000 m; restrictions for installation altitudes > 2 000 m, see ET 200SP system manual

Dimensions	
Width	15 mm
Height	73 mm
Depth	58 mm

Weights	
Weight, approx.	30 g

Classifications			
		Version	Classification
	eClass	14	27-24-26-04
	eClass	12	27-24-26-04
	eClass	9.1	27-24-26-04
	eClass	9	27-24-26-04
	eClass	8	27-24-26-04
	eClass	7.1	27-24-26-04
	eClass	6	27-24-26-04
	ETIM	10	EC001599
	ETIM	9	EC001599
	ETIM	8	EC001599
	ETIM	7	EC001599

Approvals / Certificates

General Product Approval



[Manufacturer Declaration](#)

[KC](#)

[Miscellaneous](#)



General Product Approval	EMV	For use in hazardous locations
--------------------------	-----	--------------------------------



[KC](#)



[FM](#)

[CCC-Ex](#)



For use in hazardous locations	Maritime application
--------------------------------	----------------------



[Miscellaneous](#)

[Type Examination Certificate](#)



Maritime application	Environment
----------------------	-------------

[NK / Nippon Kaiji Kyokai](#)



[CCS \(China Classification Society\)](#)



last modified:

10/23/2025