



Figure similar

SIMATIC, electronic module for ET200iSP, 4 AI, TC: for connection of thermocouples (voltage measurement), Ex ib (ia Ga) IIC T4 Gb, Ex ib [ia IIIC Da] IIC T4 Gb, Ex ib [ia] I Mb

General information	
Product brand name	SIMATIC
Product family	ET 200iSP
Product category	Analog module input
Product type designation	4AI TC
HW functional status	7
Firmware version	V1.0.1
CiR - Configuration in RUN	
Reparameterization possible in RUN	Yes
Installation type/mounting	
Rack mounting	No
Front mounting	Yes
Rail mounting	Yes
Wall mounting/direct mounting	No
Supply voltage	
Type of supply voltage	DC
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V
Input current	
Current consumption, typ.	17 mA
from load voltage (power bus), max.	30 mA
Power loss	
Power loss, typ.	0.4 W
Hardware configuration	
Fieldbus connection via separate transceiver	Yes
Analog inputs	
Number of analog inputs	4
Cycle time (all channels) max.	320 ms; 66 ms basic conversion time x 4 channels with interference frequency suppression 60 Hz, 80 ms basic conversion time x 4 channels with interference frequency suppression 50 Hz
Technical unit for temperature measurement adjustable	Yes
Input ranges	
<ul style="list-style-type: none"> <li>• Voltage</li> <li>• Current</li> <li>• Thermocouple</li> <li>• Resistance thermometer</li> <li>• Resistance</li> </ul>	<ul style="list-style-type: none"> <li>Yes</li> <li>No</li> <li>Yes</li> <li>No</li> <li>No</li> </ul>
Input ranges (rated values), voltages	
<ul style="list-style-type: none"> <li>• -80 mV to +80 mV</li> </ul>	Yes

— Input resistance (-80 mV to +80 mV)	1 000 kΩ
<b>Input ranges (rated values), thermocouples</b>	
• Type B	Yes
— Input resistance (Type B)	1 000 kΩ
• Type C	Yes
— Input resistance (Type C)	1 000 kΩ
• Type E	Yes
— Input resistance (Type E)	1 000 kΩ
• Type J	Yes
— Input resistance (type J)	1 000 kΩ
• Type K	Yes
— Input resistance (Type K)	1 000 kΩ
• Type L	Yes
— Input resistance (Type L)	1 000 kΩ
• Type N	Yes
— Input resistance (Type N)	1 000 kΩ
• Type R	Yes
— Input resistance (Type R)	1 000 kΩ
• Type S	Yes
— Input resistance (Type S)	1 000 kΩ
• Type T	Yes
— Input resistance (Type T)	1 000 kΩ
• Type U	Yes
— Input resistance (Type U)	1 000 kΩ
<b>Thermocouple (TC)</b>	
<b>Temperature compensation</b>	
— internal temperature compensation	Yes; via supplied TC sensor module
— external temperature compensation with compensations socket	Yes; via temperature value, acquired by an analog module of the same ET 200iSP station
<b>Characteristic linearization</b>	
• parameterizable	Yes
— for thermocouples	Yes
<b>Cable length</b>	
• shielded, max.	50 m
<b>Analog value generation for the inputs</b>	
Measurement principle	integrating (Sigma-Delta)
<b>Integration and conversion time/resolution per channel</b>	
• Resolution with overrange (bit including sign), max.	16 bit
• Integration time, parameterizable	Yes
• Basic conversion time, including integration time (ms)	80 ms at 50 Hz; 66 ms at 60 Hz
— additional conversion time for wire-break monitoring	5 ms
• Interference voltage suppression for interference frequency $f_1$ in Hz	50 / 60 Hz
<b>Smoothing of measured values</b>	
• parameterizable	Yes; in 4 stages
• Step: None	Yes; 1x cycle time
• Step: low	Yes; 4x cycle time
• Step: Medium	Yes; 32x cycle time
• Step: High	Yes; 64x cycle time
<b>Errors/accuracies</b>	
Linearity error (relative to input range), (+/-)	0.015 %
Temperature error (relative to input range), (+/-)	0.02 %/K
Crosstalk between the inputs, min.	-50 dB
Repeat accuracy in steady state at 25 °C (relative to input range), (+/-)	0.01 %
<b>Operational error limit in overall temperature range</b>	
• Voltage, relative to input range, (+/-)	0.15 %
<b>Basic error limit (operational limit at 25 °C)</b>	
• Voltage, relative to input range, (+/-)	0.1 %
<b>Interference voltage suppression for <math>f = n \times (f_1 \pm 1 \%)</math>, <math>f_1 =</math> interference frequency</b>	
• Series mode interference (peak value of interference < rated value of input range), min.	70 dB

• Common mode interference, min.	90 dB
<b>Interfaces</b>	
Number of PROFINET interfaces	0
<b>Protocols</b>	
Supports protocol for PROFINET IO	No
PROFIsafe	No
PROFIBUS	No
<b>Further protocols</b>	
• other bus systems	No
<b>Interrupts/diagnostics/status information</b>	
<b>Alarms</b>	
• Diagnostic alarm	Yes; Parameterizable
• Limit value alarm	Yes; Parameterizable
<b>Diagnoses</b>	
• Diagnostic information readable	Yes
• Wire-break	Yes; R > 1.7 kOhm
<b>Diagnostics indication LED</b>	
• Group error SF (red)	Yes
<b>Ex(i) characteristics</b>	
Module for Ex(i) protection	Yes; for more Co/Lo combinations, see certificate IECEx KEM 05.0008
<b>maximum values for connecting terminals for gas group IIC</b>	
• U <sub>o</sub> (no-load voltage), max.	5.9 V
• I <sub>o</sub> (short-circuit current), max.	15 mA
• P <sub>o</sub> (power output), max.	23 mW
• C <sub>o</sub> (permissible external capacity), max.	43 µF
• L <sub>o</sub> (permissible external inductivity), max.	100 mH
<b>Potential separation</b>	
between channels and powerbus	Yes
<b>Potential separation analog inputs</b>	
• between the channels	Yes; Functional
• between the channels and backplane bus	Yes
<b>Degree and class of protection</b>	
IP degree of protection	IP30
<b>Standards, approvals, certificates</b>	
CE mark	CE 0344
UKCA mark	DEKRA 21UKEX0086 Importer UK: Siemens plc Manchester M20 2UR
cULus	LISTED E334384
FM approval	CLASSIFIED 3025852
Suitable for safety functions	No
INMETRO certificate	UL-BR 12.0071
reference designation according to IEC 81346-2 (2009)	K
<b>Highest safety class achievable in safety mode</b>	
• acc. to EN 954	n.a.
• Performance level according to ISO 13849-1	none
• SIL acc. to IEC 61508	No
<b>Use in hazardous areas</b>	
• ATEX marking	II 2 G (1) G Ex ib [ia Ga] IIC T4 Gb II 2 G (1) D Ex ib [ia IIIC Da] IIC T4 Gb I M2 Ex ib [ia] I Mb
• IECEx	IECEx KEM 05.0008
• CCC Ex	2020322316002943
• EAC Ex	PB Ex ib [ia] I Mb 1Ex ib [ia Ga] IIC T4 Gb [Ex ia Da] IIIC
• FM marking	Class I, Zone 1 AEx ib [ia] IIC T4 Ex ib IIC T4 NI, Class I, DIV.2, GP. A,B,C,D T4 AIS, Class I, DIV.1, GP. A,B,C,D T4 DIP Class II, III, GP. E,F,G
• Explosion protection category for gas	ATEX gas explosion protection, Zone 1
• Explosion protection category for dust	ATEX dust explosion protection, Zone 21 always install in corresponding enclosure
• associated equipment (Ex ia)	Yes
• associated equipment (Ex ib)	Yes
<b>Marine approval</b>	
• Germanischer Lloyd (GL)	Yes
• American Bureau of Shipping (ABS)	Yes

- Bureau Veritas (BV)
- Det Norske Veritas (DNV)

Yes  
Yes

**connection method**

Design of electrical connection      Screw/spring-type terminal

**Dimensions**

Width      30 mm  
Height      129 mm  
Depth      136.5 mm

**Weights**

Weight, approx.      230 g

**Classifications**

	Version	Classification
eClass	14	27-24-26-01
eClass	12	27-24-26-01
eClass	9.1	27-24-26-01
eClass	9	27-24-26-01
eClass	8	27-24-26-01
eClass	7.1	27-24-26-01
eClass	6	27-24-26-01
ETIM	10	EC001596
ETIM	9	EC001596
ETIM	8	EC001596
ETIM	7	EC001596
IDEA	4	3562
UNSPSC	15	32-15-17-05

**Approvals / Certificates**

**General Product Approval**



[Miscellaneous](#)

[China RoHS](#)

[Metrological Approval](#)

[KC](#)

**General Product Approval**

**For use in hazardous locations**



[FM](#)



[Miscellaneous](#)

**For use in hazardous locations**



[CCC-Ex](#)



[Miscellaneous](#)



**For use in hazardous locations**

**Maritime application**



[NK / Nippon Kaiji Kyokai](#)

**Maritime application**

**Environment**



---

last modified:

7/3/2025 