



Figure similar

SIMATIC ET 200SP, CM PTP communication module for serial connection RS-422, RS-485 and RS-232, freeport, 3964 (R), USS, MODBUS RTU master, slave, max. 250 Kbit/s, suitable for BU type A0, pack quantity: 1 unit

General information	
Product type designation	CM PtP
Firmware version	
• FW update possible	Yes
usable BaseUnits	BU type A0
Product function	
• I&M data	Yes; I&M0 to I&M3
• Isochronous mode	No
Engineering with	
• STEP 7 TIA Portal configurable/integrated from version	STEP 7 V17 or higher
• STEP 7 configurable/integrated from version	via GSD as of V5.6 HF4
• PROFIBUS from GSD version/GSD revision	GSD as of Revision 5
• PROFINET from GSD version/GSD revision	GSDML V2.34
Supply voltage	
Rated value (DC)	24 V
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V
Reverse polarity protection	Yes
Input current	
Current consumption (rated value)	31 mA
Current consumption, max.	35 mA
Power loss	
Power loss, typ.	0.7 W
Address area	
Address space per module	
• Inputs	8 byte; performance mode: 32 byte
• Outputs	0 byte; performance mode: 32 byte
Hardware configuration	
Automatic encoding	Yes
• Mechanical coding element	Yes
• Type of mechanical coding element	type D
1. Interface	
Interface types	
• RS 485	Yes
• RS 422	Yes
• RS 232	Yes
• Design of the connection	Push-in terminal
Interface types	
RS 232	

<ul style="list-style-type: none"> • Transmission rate, max. • Cable length, max. • RS 232 auxiliary signals 	115.2 kbit/s 15 m RTS, CTS, DTR, DSR, RI, DCD
RS 485	
<ul style="list-style-type: none"> • Transmission rate, max. • Cable length, max. 	250 kbit/s 1 200 m; 100 to 1200 m, depending on transmission speed
RS 422	
<ul style="list-style-type: none"> • Transmission rate, max. • Cable length, max. • 4-wire full duplex connection • 4-wire multipoint connection 	115.2 kbit/s 1 200 m Yes Yes
Protocols	
Integrated protocols	
Freeport	
<ul style="list-style-type: none"> — Telegram length, max. — Bits per character — Number of stop bits — Parity 	2 kbyte; performance mode: receive data max. 24 byte and send data max. 30 byte 7 or 8 1 or 2 bit None, even, odd, always 1, always 0, any
3964 (R)	
<ul style="list-style-type: none"> — Telegram length, max. — Bits per character — Number of stop bits — Parity 	2 kbyte; performance mode: receive data max. 24 byte and send data max. 30 byte 7 or 8 1 or 2 bit None, even, odd, always 1, always 0, any
Modbus RTU master	
<ul style="list-style-type: none"> — Address area — max. number of devices 	1 to 247, extended 1 to 65535 32
protocols / Modbus RTU device / header	
<ul style="list-style-type: none"> — Address area 	1 to 247, extended 1 to 65535
Telegram buffer	
<ul style="list-style-type: none"> • Buffer memory for telegrams • Number of telegrams which can be buffered 	4 kbyte 255
Interrupts/diagnostics/status information	
Diagnostics function	Yes
Alarms	
<ul style="list-style-type: none"> • Diagnostic alarm • Hardware interrupt 	Yes No
Diagnoses	
<ul style="list-style-type: none"> • Wire-break 	Yes
Diagnostics indication LED	
<ul style="list-style-type: none"> • Monitoring of the supply voltage (PWR-LED) • for module diagnostics • Receive RxD • Transmit TxD 	Yes; green PWR LED Yes; green/red DIAG LED Yes; green LED Yes; green LED
Potential separation	
<ul style="list-style-type: none"> between backplane bus and interface 	Yes
Isolation	
<ul style="list-style-type: none"> Isolation tested with 	707 V DC (type test)
Standards, approvals, certificates	
Ecological footprint	
<ul style="list-style-type: none"> • environmental product declaration 	Yes
Global warming potential	
<ul style="list-style-type: none"> — global warming potential, (total) [CO2 eq] — global warming potential, (during production) [CO2 eq] — global warming potential, (during operation) [CO2 eq] — global warming potential, (after end of life cycle) [CO2 eq] 	25.2 kg 6.15 kg 19.4 kg -0.289 kg
Ambient conditions	
<ul style="list-style-type: none"> Ambient temperature during operation 	

- horizontal installation, min. -30 °C
- horizontal installation, max. 60 °C
- vertical installation, min. -30 °C
- vertical installation, max. 50 °C

Altitude during operation relating to sea level	
• Installation altitude above sea level, max.	5 000 m

Decentralized operation

to SIMATIC S7-300	Yes
to SIMATIC S7-400	Yes
to SIMATIC S7-1200	Yes
to SIMATIC S7-1500	Yes
to standard PROFINET controller	Yes

Dimensions

Width	15 mm
Height	73 mm
Depth	58 mm

Weights

Weight, approx.	30 g
-----------------	------

Classifications

	Version	Classification
eClass	14	27-24-26-08
eClass	12	27-24-26-08
eClass	9.1	27-24-26-08
eClass	9	27-24-26-08
eClass	8	27-24-26-08
eClass	7.1	27-24-26-08
eClass	6	27-24-26-08
ETIM	10	EC001604
ETIM	9	EC001604
ETIM	8	EC001604
ETIM	7	EC001604
IDEA	4	3564
UNSPSC	15	32-15-17-05

Approvals / Certificates

General Product Approval

[Manufacturer Declaration](#)



[Miscellaneous](#)



General Product Approval	EMV	For use in hazardous locations
--------------------------	-----	--------------------------------

[KC](#)

[KC](#)



[CCC-Ex](#)

[FM](#)



For use in hazardous locations	Maritime application
--------------------------------	----------------------



[Miscellaneous](#)

[Type Examination Certificate](#)



Maritime application



[NK / Nippon Kaiji Kyokai](#)



[CCS \(China Classification Society\)](#)



Environment



last modified:

10/23/2025