



SIMATIC, fail-safe electronic module for ET200iSP, 4F-AI HART Ex I, up to category 4 (EN954-1)/ SIL3 (IEC61508)/PLE (ISO13849), for connecting (HART) 2-wire transmitters, supported HART protocol version 7.0, Ex ib (ia Ga) IIC T4 Gb, Ex ib [ia IIC Da] IIC T4 Gb, Ex ib [ia] I Mb

General information	
Product brand name	SIMATIC
Product family	ET 200iSP
Product category	Analog module input
Product type designation	4F-AI I Ex HART
Installation type/mounting	
Rack mounting	No
Front mounting	Yes
Rail mounting	Yes
Wall mounting/direct mounting	Yes
Supply voltage	
Type of supply voltage	DC
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	30 V
Input current	
Current consumption, typ.	315 mA
from supply voltage L+, max.	490 mA; int. Powerbus
output voltage / header	
supply voltage of the transmitters / header	
<ul style="list-style-type: none"> • short-circuit proof 	Yes
<ul style="list-style-type: none"> • Supply current, max. 	25 mA; Plus 4 mA per channel
Power loss	
Power loss, typ.	3.8 W
Power loss, max.	5.4 W
Address area	
Address space per module	
<ul style="list-style-type: none"> • Address space per module, max. 	16 byte; 12 bytes in the I area / 4 bytes in the O area
Hardware configuration	
Fieldbus connection via separate transceiver	Yes
Analog inputs	
Number of analog inputs	4
Cycle time (all channels) max.	See data in manual
Input ranges	
<ul style="list-style-type: none"> • Voltage 	No
<ul style="list-style-type: none"> • Current 	Yes
<ul style="list-style-type: none"> • Thermocouple 	No
<ul style="list-style-type: none"> • Resistance thermometer 	No
<ul style="list-style-type: none"> • Resistance 	No
Input ranges (rated values), currents	

• 0 to 20 mA	Yes
• 4 mA to 20 mA	Yes
Cable length	
• shielded, max.	500 m
Analog value generation for the inputs	
Measurement principle	integrating (Sigma-Delta)
Integration and conversion time/resolution per channel	
• Resolution with overrange (bit including sign), max.	16 bit
• Integration time, parameterizable	Yes
• Interference voltage suppression for interference frequency f_1 in Hz	50 / 60 Hz
Smoothing of measured values	
• parameterizable	Yes; in 4 stages
• Step: None	Yes; 1x cycle time
• Step: low	Yes; 4x cycle time
• Step: Medium	Yes; 16x cycle time
• Step: High	Yes; 64x cycle time
Encoder	
Connection of signal encoders	
• for current measurement as 2-wire transducer	Yes
— Burden of 2-wire transmitter, max.	750 Ω
Errors/accuracies	
Linearity error (relative to input range), (+/-)	0.015 %
Temperature error (relative to input range), (+/-)	0.005 %/K
Crosstalk between the inputs, min.	-50 dB
Repeat accuracy in steady state at 25 °C (relative to input range), (+/-)	0.015 %
Operational error limit in overall temperature range	
• Current, relative to input range, (+/-)	0.35 %
Basic error limit (operational limit at 25 °C)	
• Current, relative to input range, (+/-)	0.1 %
Interference voltage suppression for $f = n \times (f_1 \pm 1 \%)$, f_1 = interference frequency	
• Series mode interference (peak value of interference < rated value of input range), min.	40 dB
• Common mode interference, min.	50 dB
Interfaces	
Number of PROFINET interfaces	0
Protocols	
Supports protocol for PROFINET IO	No
PROFIsafe	Yes
PROFIBUS	No
Further protocols	
• other bus systems	No
Interrupts/diagnostics/status information	
Alarms	
• Diagnostic alarm	Yes; Parameterizable
Diagnoses	
• Diagnostic information readable	Yes
• Wire-break	Yes
• Short-circuit	Yes
Diagnostics indication LED	
• Group error SF (red)	Yes
Potential separation	
Potential separation analog inputs	
• between the channels	No
• between the channels and backplane bus	Yes
• Between the channels and load voltage L+	Yes; Power bus
Permissible potential difference	
between different circuits	60 V DC/30 V AC

Degree and class of protection	
IP degree of protection	IP30
Standards, approvals, certificates	
CE mark	Yes
Suitable for safety functions	Yes
reference designation according to IEC 81346-2 (2009)	K
Highest safety class achievable in safety mode	
<ul style="list-style-type: none"> • acc. to EN 954 • Performance level according to ISO 13849-1 • SIL acc. to IEC 61508 	4 PLe SIL 3
Use in hazardous areas	
<ul style="list-style-type: none"> • ATEX marking • ATEX certificate • Explosion protection category for gas • Explosion protection category for dust • associated equipment (Ex ia) • associated equipment (Ex ib) 	II 2 G (1) GD Ex ib[ja Ga][ja IIIC Da] IIC T4 GB and I M2 Ex ib[ja Ma] I Mb 10 ATEX 0058 ATEX gas explosion protection, Zone 1 ATEX dust explosion protection, Zone 21 always install in corresponding enclosure Yes Yes
Connection method	
Design of electrical connection	Screw/spring-type terminal
Dimensions	
Width	30 mm
Height	129 mm
Depth	136.5 mm
Weights	
Weight, approx.	299 g
Classifications	

	Version	Classification
eClass	14	27-24-26-01
eClass	12	27-24-26-01
eClass	9.1	27-24-26-01
eClass	9	27-24-26-01
eClass	8	27-24-26-01
eClass	7.1	27-24-26-01
eClass	6	27-24-26-01
ETIM	10	EC001596
ETIM	9	EC001596
ETIM	8	EC001596
ETIM	7	EC001596
IDEA	4	3562
UNSPSC	15	32-15-17-05

Approvals / Certificates

General Product Approval



EG-Konf.

[Miscellaneous](#)



[China RoHS](#)

[Metrological Approval](#)

[KC](#)

General Product Approval For use in hazardous locations



RCM



ATEX



IECEX

[FM](#)



IECEX

[Miscellaneous](#)

For use in hazardous locations Functional Safety



[Miscellaneous](#)

[TUEV](#)

[Type Examination Certificate](#)

Functional Safety Maritime application Environment

[TUEV](#)



last modified:

4/29/2025