



SIMATIC DP, ET 200AL, F-DI 4+F-DQ 2x24 V DC/2 A, 4xM12, PROFIsafe, up to PL e (ISO 13849), up to SIL 3 (IEC 61508), degree of protection IP67, including eCoding plug-in connector

| General information | |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product type designation | F-DI 4+F-DQ 2x24VDC/2A, 4xM12 |
| Product function | |
| <ul style="list-style-type: none"> I&M data | Yes; I&M0 to I&M3 |
| Engineering with | |
| <ul style="list-style-type: none"> STEP 7 TIA Portal configurable/integrated from version | STEP 7 V17 or higher |
| Operating mode | |
| <ul style="list-style-type: none"> DI DQ | Yes Yes |
| Supply voltage | |
| Rated value (DC) | 24 V |
| power supply according to NEC Class 2 required | No |
| Load voltage 1L+ | |
| <ul style="list-style-type: none"> Rated value (DC) permissible range, lower limit (DC) permissible range, upper limit (DC) Reverse polarity protection | 24 V 20.4 V 28.8 V Yes; against destruction |
| Load voltage 2L+ | |
| <ul style="list-style-type: none"> Rated value (DC) permissible range, lower limit (DC) permissible range, upper limit (DC) Reverse polarity protection | 24 V 20.4 V 28.8 V Yes; against destruction; outputs applied with reversed polarity for loads connected between M-switch and 2L+ will conduct |
| Input current | |
| Current consumption (rated value) | 55 mA (1L+) / 40 mA (2L+); without load |
| from load voltage 1L+ (unswitched voltage) | 4 A; Maximum value |
| from load voltage 2L+, max. | 4 A; Maximum value |
| Encoder supply | |
| Number of outputs | 2 |
| 24 V encoder supply | |
| <ul style="list-style-type: none"> Short-circuit protection Output current, max. | Yes; per load voltage, electronic (response threshold 0.7 A to 1.7 A) 1 A; total current of all encoders, max. 0.5 A per load voltage; maximum of 2.0 V drop |
| Power loss | |
| Power loss, typ. | 4.7 W |
| Address area | |
| Address space per module | |
| <ul style="list-style-type: none"> Inputs Outputs | 8 byte 6 byte |
| Digital inputs | |

| | |
|-------------------------------------------------------|--------------------------------------------------------------------------|
| Number of digital inputs | 4 |
| Input characteristic according to IEC 61131 | Type 1 |
| Number of simultaneously controllable inputs | |
| all mounting positions | |
| — up to 55 °C, max. | 4 |
| Input voltage | |
| • Rated value (DC) | 24 V |
| • for signal "0" | -30 to +5 V |
| • for signal "1" | +15 to +30 V |
| Input current | |
| • for signal "1", typ. | 4.85 mA |
| Input delay (for rated value of input voltage) | |
| for standard inputs | |
| — parameterizable | Yes |
| — at "0" to "1", min. | 0.8 ms |
| — at "0" to "1", max. | 12.8 ms |
| — at "1" to "0", min. | 0.8 ms |
| — at "1" to "0", max. | 12.8 ms |
| Cable length | |
| • unshielded, max. | 30 m |
| Digital outputs | |
| Number of digital outputs | 2 |
| • in groups of | 2 |
| Short-circuit protection | Yes; per channel, electronic |
| • Response threshold, typ. | 10 A; measured at M-switch, threshold for P-switch is higher |
| Open-circuit detection | Yes; per channel, only detects when output is off |
| Overload protection | Yes |
| • Response threshold, typ. | 3.4 A; measured at P-switch |
| Limitation of inductive shutdown voltage to | P-switch: -26 V DC referenced to 2M, M-switch: +48 V DC referenced to 2M |
| Switching capacity of the outputs | |
| • on lamp load, max. | 10 W |
| Load resistance range | |
| • lower limit | 12 Ω |
| • upper limit | 2 kΩ |
| Output voltage | |
| • for signal "1", min. | L+ (-2.0 V), P-switch is L+ (-1.5 V), M-switch is 0.5 V |
| Output current | |
| • for signal "1" rated value | 2 A |
| • for signal "0" residual current, max. | 0.5 mA |
| Switching frequency | |
| • with resistive load, max. | 30 Hz |
| • with inductive load, max. | 0.1 Hz |
| • on lamp load, max. | 10 Hz |
| Total current of the outputs | |
| • Current per group, max. | 4 A |
| Cable length | |
| • unshielded, max. | 30 m |
| Encoder | |
| Connectable encoders | |
| • 2-wire sensor | No |
| — permissible quiescent current (2-wire sensor), max. | 0.5 mA |
| Interrupts/diagnostics/status information | |
| Substitute values connectable | No |
| Alarms | |
| • Diagnostic alarm | Yes; Parameterizable |
| Diagnoses | |
| • Monitoring the supply voltage | Yes |
| • Wire-break | Yes; outputs when off |
| • Short-circuit | Yes; inputs, outputs, encoder supply |
| Diagnostics indication LED | |

| | |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <ul style="list-style-type: none"> • Channel status display • for channel diagnostics • for module diagnostics • For load voltage monitoring | <p>Yes; green LED</p> <p>Yes; red LED</p> <p>Yes; green/red LED</p> <p>Yes; green LED</p> |
| Potential separation | |
| between the load voltages | Yes |
| Potential separation channels | |
| <ul style="list-style-type: none"> • between the channels, in groups of • between the channels and backplane bus • between the channels and the power supply of the electronics | <p>4 DI channels are isolated from 2 DQ channels</p> <p>Yes</p> <p>DI channels are non-isolated from supply voltage 1L+ and DQ channels are isolated from the supply voltage 1L+</p> |
| Isolation | |
| Isolation tested with | 707 V DC (type test) |
| Degree and class of protection | |
| IP degree of protection | IP65/67 |
| Standards, approvals, certificates | |
| Highest safety class achievable in safety mode | |
| <ul style="list-style-type: none"> • Performance level according to ISO 13849-1 • Category according to ISO 13849-1 • SIL acc. to IEC 61508 | <p>PLd (DI single-channel), PLe (DI two-channel, DQ)</p> <p>Cat. 3 (DI single-channel), Cat. 4 (DI two-channel, DQ)</p> <p>SIL 2 (DI single-channel), SIL 3 (DI two-channel, DQ)</p> |
| Probability of failure (for service life of 20 years and repair time of 100 hours) | |
| — Low demand mode: PFDavg in accordance with SIL2 | < 1.00E-03 DI single-channel; < 1.00E-03 DQ with dark test disabled |
| — Low demand mode: PFDavg in accordance with SIL3 | < 1.00E-05 DI two-channel; < 2.00E-05 DQ with dark test enabled |
| — High demand/continuous mode: PFH in accordance with SIL2 | < 1.00E-08 1/h DI single-channel; < 1.00E-07 1/h DQ with dark test disabled |
| — High demand/continuous mode: PFH in accordance with SIL3 | < 1.00E-09 1/h DI two-channel; < 1.00E-08 1/h DQ with dark test enabled |
| Ambient conditions | |
| Ambient temperature during operation | |
| <ul style="list-style-type: none"> • min. • max. | <p>-30 °C</p> <p>55 °C</p> |
| connection method | |
| Design of electrical connection for the inputs and outputs | M12, 5-pole |
| Design of electrical connection for supply voltage | M8, 4-pin |
| ET-Connection | |
| <ul style="list-style-type: none"> • ET-Connection | M8, 4-pin, shielded |
| Dimensions | |
| Width | 45 mm |
| Height | 159 mm |
| Depth | 40 mm |
| Weights | |
| Weight, approx. | 220 g |
| Classifications | |

| | Version | Classification |
|--------|---------|----------------|
| eClass | 14 | 27-24-26-04 |
| eClass | 12 | 27-24-26-04 |
| eClass | 9.1 | 27-24-26-04 |
| eClass | 9 | 27-24-26-04 |
| eClass | 8 | 27-24-26-04 |
| eClass | 7.1 | 27-24-26-04 |
| eClass | 6 | 27-24-26-04 |
| ETIM | 10 | EC001599 |
| ETIM | 9 | EC001599 |
| ETIM | 8 | EC001599 |
| ETIM | 7 | EC001599 |
| IDEA | 4 | 3566 |
| UNSPSC | 15 | 32-15-17-05 |

Approvals / Certificates

| | | |
|--------------------------|-----|----------------------|
| General Product Approval | EMV | Maritime application |
|--------------------------|-----|----------------------|



| | | |
|----------------------|-------|-------------|
| Maritime application | other | Environment |
|----------------------|-------|-------------|



[Confirmation](#)

[Environmental Con-
firmations](#)

last modified:

10/23/2025