



SIMATIC DP, Pneumatic interface for ET 200 PRO, 16 DO pneumatics for coupling with Festo valve terminal CPV-14; incl. bus module

Supply voltage	
Load voltage 2L+	
• Rated value (DC)	24 V
• Short-circuit protection	Yes
• Reverse polarity protection	Yes
Input current	
from load voltage 2L+, max.	370 mA; Including valves
from backplane bus 3.3 V DC, max.	25 mA
Power loss	
Power loss, typ.	3.7 W
Address area	
Address space per module	
• Address space per module, max.	2 byte
Digital outputs	
Number of digital outputs	16
Load resistance range	
• lower limit	500 Ω
• upper limit	2 500 Ω
Output current	
• for signal "1" rated value	16 mA
• for signal "1" permissible range, min.	14 mA
• for signal "1" permissible range, max.	20 mA
Switching frequency	
• with inductive load, max.	20 Hz
Total current of the outputs (per group)	
all mounting positions	
— up to 55 °C, max.	330 mA; only up to 50 °C, limited by valves
Interrupts/diagnostics/status information	
Diagnostics function	Yes
Alarms	
• Diagnostic alarm	Yes
Diagnoses	
• Diagnostic information readable	Yes
Diagnostics indication LED	
• Group error SF (red)	Yes
• Status indicator digital output (green)	Yes
Pneumatics	
Number of connectable valves, max.	16
permissible working pressure, min.	3 bar
permissible working pressure, max.	8 bar

Rated flow rate	800 l/min
Valve switching times from "0" to "1"	24 ms
Valve switching times from "1" to "0"	30 ms
Parameter	
Remark	Diagnosis load voltage 2L+
Potential separation	
between backplane bus and all other circuit components	Yes
Potential separation digital outputs	
• between the channels and backplane bus	Yes
Isolation	
Isolation tested with	707 V DC (type test)
Standards, approvals, certificates	
Suitable for safety-related tripping of standard modules	Yes
Highest safety class achievable for safety-related tripping of standard modules	
• Performance level according to ISO 13849-1	PL d
• Category according to ISO 13849-1	Cat. 3
• SIL acc. to IEC 62061	SIL 2
• remark on safety-oriented shutdown	https://support.industry.siemens.com/cs/de/en/view/39198632
Dimensions	
Width	120 mm
Height	152 mm
Depth	47 mm
Classifications	

	Version	Classification
eClass	14	27-24-26-13
eClass	12	27-24-26-13
eClass	9.1	27-24-26-13
eClass	9	27-24-26-13
eClass	8	27-24-26-13
eClass	7.1	27-24-26-13
eClass	6	27-24-26-13
ETIM	10	EC002634
ETIM	9	EC002634
ETIM	8	EC002634
ETIM	7	EC002634
IDEA	4	3561
UNSPSC	15	32-15-17-05

Approvals / Certificates

General Product Approval

[Miscellaneous](#)

[Manufacturer Declaration](#)



[KC](#)

Maritime application



[NK / Nippon Kaiji Kyokai](#)



Maritime application



last modified:

10/23/2025 