

M8 connector for ET connection, 4-pole, shielded



General information		
Product type designation	Connection plug	
Product description	M8 plug connector with high degree of protection, 4-pin, metal version	
Suitability for use	for connecting ET-CONNECTION nodes (e.g. SIMATIC ET 200AL) in degree of protection IP65 / 67	
Degree and class of protection		
IP degree of protection	IP65/67	
Ambient conditions		
Ambient temperature during assembly, min.	-30 °C	
Ambient temperature during assembly, max.	80 °C	
Ambient temperature during storage/transportation		
• min.	-40 °C	
• max.	80 °C	
Mechanics/material		
Outgoing feeder type	180° cable outlet	
Material of housing	metal	
Dimensions		
Width	14 mm	
Depth	47 mm	
Classifications		
	Version	Classification
eClass	14	27-24-26-92
eClass	12	27-24-26-92
eClass	9.1	27-24-26-92
eClass	9	27-24-26-92
eClass	8	27-24-26-92
eClass	7.1	27-24-26-92
eClass	6	27-24-26-92
ETIM	10	EC002584
ETIM	9	EC002584
ETIM	8	EC002584
ETIM	7	EC002584
IDEA	4	3552
UNSPSC	15	32-15-17-03
Approvals / Certificates		
General Product Approval		

[Manufacturer Declaration](#)



last modified:

4/25/2025