



SIMATIC DP, connection module for PROFIBUS interface module ET 200 Pro; M12/7/8", 2x M12 and 2x 7/8", integrated address setter and terminating resistor for PROFIBUS DP; product phase-out planned – see SIOS 109989704

Input current	
from supply voltage 1L+, max.	8 A
from load voltage 2L+ (without load), max.	8 A
Accessories	
Function description	Terminal module M12 7/8": PROFIBUS DP and 24 V power; 2x M12 and 2x 7/8"
belongs to product	ET 200pro; IM154-1/2 DP
Dimensions	
Width	60 mm
Height	130 mm
Depth	60 mm
Weights	
Weight, approx.	440 g

Classifications			
	Version	Classification	
eClass	14	27-24-26-03	
eClass	12	27-24-26-03	
eClass	9.1	27-24-26-03	
eClass	9	27-24-26-03	
eClass	8	27-24-26-03	
eClass	7.1	27-24-26-03	
eClass	6	27-24-26-03	
ETIM	10	EC001598	
ETIM	9	EC001598	
ETIM	8	EC001598	
ETIM	7	EC001598	
IDEA	4	3560	
UNSPSC	15	32-15-17-04	

Approvals / Certificates	
General Product Approval	

[Miscellaneous](#)

[Manufacturer Declaration](#)



General Product Ap-	Maritime application
---------------------	----------------------

proval

[KC](#)



[NK / Nippon Kaiji Kyokai](#)

Maritime application



[CCS \(China Classification Society\)](#)



last modified:

4/7/2025 