

Siemens
EcoTech



SIMATIC S7-1200 G2: failsafe compact CPU 1214FC DC/DC/DC; power supply: DC 20.4-28.8 V DC; onboard I/O: 14x DI 24 V DC; 10x DO 24 V DC; memory: program 300 KB data: 750 KB, retentivity: 20 KB



Figure similar

General information	
Product type designation	CPU 1214FC DC/DC/DC
Firmware version	V1.0
<ul style="list-style-type: none"> FW update possible 	Yes
Product function	
<ul style="list-style-type: none"> I&M data 	Yes; I&M0 to I&M3
<ul style="list-style-type: none"> SysLog 	Yes
Engineering with	
<ul style="list-style-type: none"> Programming package 	STEP 7 V20 or higher
Supply voltage	
Rated value (DC)	
<ul style="list-style-type: none"> 24 V DC 	Yes
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V
Reverse polarity protection	Yes
Input current	
Current consumption (rated value)	145 mA; CPU only
Current consumption, max.	1 000 mA; CPU with all expansion modules
Inrush current, max.	12 A; at 28.8 V DC
I ² t	0.5 A ² ·s
Output current	
for backplane bus (5 V DC), max.	1 600 mA; Max. 5 V DC for SM and CM
Encoder supply	
24 V encoder supply	
<ul style="list-style-type: none"> 24 V 	Yes; L+ minus 4 V DC min.
<ul style="list-style-type: none"> Short-circuit protection 	Yes
<ul style="list-style-type: none"> Output current, max. 	400 mA
Power loss	
Power loss, typ.	3.5 W
Memory	
Work memory	
<ul style="list-style-type: none"> integrated 	1 050 kbyte
<ul style="list-style-type: none"> integrated (for program) 	300 kbyte
<ul style="list-style-type: none"> integrated (for data) 	750 kbyte
Load memory	
<ul style="list-style-type: none"> integrated 	8 Mbyte

• Plug-in (SIMATIC Memory Card), max.	32 Gbyte; with SIMATIC memory card
Backup	
• present	Yes
• maintenance-free	Yes
• without battery	Yes
CPU processing times	
for bit operations, typ.	37 ns; / instruction
for word operations, typ.	30 ns; / instruction
for floating point arithmetic, typ.	74 ns; / instruction
CPU-blocks	
Number of elements (total)	4 000; Blocks (OB, FB, FC, DB) and UDTs
OB	
• Number of free cycle OBs	100
• Number of time alarm OBs	20
• Number of delay alarm OBs	20
• Number of cyclic interrupt OBs	20; with minimum OB 3x cycle of 1 ms
• Number of process alarm OBs	50
• Number of DPV1 alarm OBs	3
• Number of isochronous mode OBs	1
• Number of startup OBs	100
• Number of asynchronous error OBs	4
• Number of synchronous error OBs	2
• Number of diagnostic alarm OBs	1
Data areas and their retentivity	
Retentive data area (incl. timers, counters, flags), max.	20 kbyte
Flag	
• Size, max.	8 kbyte; Size of bit memory address area
Local data	
• per priority class, max.	64 kbyte; max. 16 KB per block
Address area	
Process image	
• Inputs, adjustable	1 kbyte
• Outputs, adjustable	1 kbyte
Hardware configuration	
Number of modules per system, max.	10
Time of day	
Clock	
• Hardware clock (real-time)	Yes
• Backup time	480 h; Typical
• Deviation per day, max.	2 s; at 25 °C
Digital inputs	
Number of digital inputs	14; Integrated
• of which inputs usable for technological functions	8; HSC (High Speed Counting)
Source/sink input	Yes
Number of simultaneously controllable inputs	
all mounting positions	
— up to 40 °C, max.	14
Input voltage	
• Rated value (DC)	24 V
• for signal "0"	5 V DC or 0.5 mA
• for signal "1"	15 V DC at 2.5 mA
Input delay (for rated value of input voltage)	
for standard inputs	
— parameterizable	0.1 / 0.2 / 0.4 / 0.8 / 1.6 / 3.2 / 6.4 / 10.0 / 12.8 / 20.0 µs; 0.05 / 0.1 / 0.2 / 0.4 / 0.8 / 1.6 / 3.2 / 6.4 / 10.0 / 12.8 / 20.0 ms
— at "0" to "1", min.	0.1 µs
— at "0" to "1", max.	20 ms
for interrupt inputs	
— parameterizable	Yes
for technological functions	
— parameterizable	single phase: 6 HSCs @ 100 kHz & 2 standard @ 30 kHz, quadrature phase: 6

HSCs @ 80 kHz & 2 standard @ 20 kHz

Cable length	
• shielded, max.	500 m; 50 m for technological functions
• unshielded, max.	300 m; for technological functions: No
Digital outputs	
Number of digital outputs	10; 20 kHz or 100 kHz
• of which high-speed outputs	4; 100 kHz (Qa.0 - Qa.3)
Limitation of inductive shutdown voltage to	L+ (-40 V)
Switching capacity of the outputs	
• with resistive load, max.	0.5 A
• on lamp load, max.	5 W
Output voltage	
• for signal "0", max.	0.1 V; with 10 kOhm load
• for signal "1", min.	20 V
Output current	
• for signal "1" rated value	0.5 A
• for signal "0" residual current, max.	10 µA
Output delay with resistive load	
• "0" to "1", max.	1 µs; of the pulse outputs (Qa.0 to Qa.3), max. 1.0 µs; of the standard outputs (Qa.4 to Qb.1), max. 50 µs;
• "1" to "0", max.	3 µs; of the pulse outputs (Qa.0 to Qa.3), max. 3.0 µs; of the standard outputs (Qa.4 to Qb.1), max. 200 µs;
Switching frequency	
• of the pulse outputs, with resistive load, max.	100 kHz; 100 kHz max. (Qa.0 - Qa.3), 20 kHz max. (Qa.4 to Qb.1)
Relay outputs	
• Number of relay outputs	0
Cable length	
• shielded, max.	500 m
• unshielded, max.	150 m
Analog inputs	
Number of analog inputs	0
Analog outputs	
Number of analog outputs	0
Encoder	
Connectable encoders	
• 2-wire sensor	Yes
1. Interface	
Interface type	PROFINET
Isolated	Yes
automatic detection of transmission rate	Yes
Autonegotiation	Yes
Autocrossing	Yes
Interface types	
• RJ 45 (Ethernet)	Yes
• Number of ports	2
• integrated switch	Yes
Protocols	
• IP protocol	Yes; IPv4
• PROFINET IO Controller	Yes
• PROFINET IO Device	Yes
• SIMATIC communication	Yes
• Open IE communication	Yes; Optionally also encrypted
• Web server	Yes
• Media redundancy	Yes
PROFINET IO Controller	
• Transmission rate, max.	100 Mbit/s
Services	
— PG/OP communication	Yes; encryption with TLS V1.3 pre-selected
— Isochronous mode	Yes
— IRT	Yes
— PROFINergy	Yes; per user program

— Prioritized startup	Yes
— Number of IO devices with prioritized startup, max.	16
— Number of connectable IO Devices, max.	31
— Of which IO devices with IRT, max.	31
— Number of connectable IO Devices for RT, max.	31
— of which in line, max.	31
— Activation/deactivation of IO Devices	Yes
— Number of IO Devices that can be simultaneously activated/deactivated, max.	8
— Updating time	The minimum value of the update time also depends on the communication component set for PROFINET IO, on the number of IO devices and the quantity of configured user data.

Update time for IRT

— for send cycle of 1 ms	1 ms to 16 ms
— for send cycle of 2 ms	2 ms to 32 ms
— for send cycle of 4 ms	4 ms to 64 ms

Update time for RT

— for send cycle of 1 ms	1 ms to 512 ms
— for send cycle of 2 ms	2 ms to 512 ms
— for send cycle of 4 ms	4 ms to 512 ms

PROFINET IO Device

Services

— PG/OP communication	Yes; encryption with TLS V1.3 pre-selected
— Isochronous mode	No
— IRT	Yes
— PROFIenergy	Yes; per user program
— Shared device	Yes
— Number of IO Controllers with shared device, max.	2

Protocols

Supports protocol for PROFINET IO	Yes
PROFIsafe	Yes
PROFIBUS	No
OPC UA	No
AS-Interface	No

Protocols (Ethernet)

• TCP/IP	Yes
• DHCP	Yes
• SNMP	Yes
• DCP	Yes
• LLDP	Yes

Number of connections

• Number of connections, max.	128; via integrated interfaces of the CPU and connected CPs / CMs
• Number of connections reserved for ES/HMI/web	10
• Number of connections via integrated interfaces	88

Redundancy mode

Media redundancy

— MRP	Yes; as MRP redundancy manager and/or MRP client
— MRPD	Yes

SIMATIC communication

• S7 routing	No
• S7 communication, as server	Yes
• S7 communication, as client	Yes

Open IE communication

• TCP/IP	Yes
— Data length, max.	8 kbyte
— several passive connections per port, supported	Yes
• ISO-on-TCP (RFC1006)	Yes
— Data length, max.	8 kbyte
• UDP	Yes
— Data length, max.	2 kbyte; 1 472 bytes for UDP broadcast
• DHCP	Yes
• DNS	Yes

• SNMP	Yes
• DCP	Yes
• LLDP	Yes
• Encryption	Yes; Optional
Web server	
• supported	Yes
• HTTPS	Yes
• web API	Yes
— Number of sessions, max.	30
• User-defined websites	Yes
Further protocols	
• MODBUS	Yes
communication functions / header	
S7 communication	
• supported	Yes
• as server	Yes
• as client	Yes
• User data per job, max.	See online help (S7 communication, user data size)
Number of connections	
• overall	PG Connections: 4 reserved; HMI Connections: 4 reserved / 82 max; S7 Connections: 78 max; Open User Connections: 78 max; Web Connections: 2 reserved / 80 max; Total Connections: 10 reserved / 88 max
S7 message functions	
Number of login stations for message functions, max.	32
Program alarms	Yes
Number of configurable program messages, max.	5 000
Number of loadable program messages in RUN, max.	2 500
Number of simultaneously active program alarms	
• Number of program alarms	600
• Number of alarms for system diagnostics	100
• Number of alarms for motion technology objects	160
Test commissioning functions	
Status/control	
• Status/control variable	Yes
• Variables	Inputs/outputs, memory bits, DBs, distributed I/Os, timers, counters
Forcing	
• Forcing	Yes
Diagnostic buffer	
• present	Yes
Traces	
• Number of configurable Traces	4
• Memory size per trace, max.	512 kbyte
Interrupts/diagnostics/status information	
Diagnostics indication LED	
• RUN/STOP LED	Yes
• ERROR LED	Yes
• MAINT LED	Yes
Supported technology objects	
Motion Control	
• Number of available Motion Control resources for technology objects	800
• Required Motion Control resources	
— per speed-controlled axis	40
— per positioning axis	80
— per synchronous axis	160
— per external encoder	80
— per output cam	20
— per cam track	160
— per probe	40
• Number of available Extended Motion Control resources for technology objects	40
• Required Extended Motion Control resources	

— per cam (1 000 points and 50 segments)	2; 1000 points and 1 segment
— for each set of kinematics	30
• kinematics functions	
— kinematics with up to 4 interpolating axes	Yes
— kinematics with 5 or more interpolating axes	No
— user-defined kinematics	No
— SIMATIC Safe Kinematics	No
• Positioning axis	
— Number of positioning axes at motion control cycle of 4 ms (typical value)	10
— Number of positioning axes at motion control cycle of 8 ms (typical value)	10
Integrated Functions	
Counter	Yes
• Number of counters	8
• Counting frequency, max.	100 kHz; Ia.0 to Ia.5: 100 kHz (80 kHz in quadrature mode), Ia.6 to Ib.5: 30 kHz (20 kHz in quadrature mode)
Frequency measurement	Yes
PID controller	Yes
Number of pulse outputs	8; individually assigned to CPU and Signal Board
Limit frequency (pulse)	100 kHz
Potential separation	
Potential separation digital inputs	
• Potential separation digital inputs	Yes; field side to logic: 707 V DC (type test)
• between the channels	No
• Number of potential groups	1
Potential separation digital outputs	
• Potential separation digital outputs	Yes
• between the channels	No
• Number of potential groups	1
EMC	
Interference immunity against discharge of static electricity	
• Interference immunity against discharge of static electricity acc. to IEC 61000-4-2	Yes
— Test voltage at air discharge	8 kV
— Test voltage at contact discharge	6 kV
Interference immunity to cable-borne interference	
• Interference immunity on supply lines acc. to IEC 61000-4-4	Yes
• Interference immunity on signal cables acc. to IEC 61000-4-4	Yes
Interference immunity against voltage surge	
• Interference immunity on supply lines acc. to IEC 61000-4-5	Yes
Interference immunity against conducted variable disturbance induced by high-frequency fields	
• Interference immunity against high-frequency radiation acc. to IEC 61000-4-6	Yes
Emission of radio interference acc. to EN 55 011	
• Limit class A, for use in industrial areas	Yes; Group 1
• Limit class B, for use in residential areas	Yes; When appropriate measures are used to ensure compliance with the limits for Class B according to EN 55011
Degree and class of protection	
IP degree of protection	IP20
Standards, approvals, certificates	
Siemens Eco Profile (SEP)	Siemens EcoTech
CE mark	Yes
UL approval	Yes
cULus	Yes
FM approval	No
RCM (formerly C-TICK)	Yes
KC approval	Yes
Marine approval	No
Ecological footprint	

• environmental product declaration	Yes; type 2 acc. to ISO 14021
Global warming potential	
— global warming potential, (total) [CO2 eq]	68 kg
— global warming potential, (during production) [CO2 eq]	14.4 kg
— global warming potential, (during operation) [CO2 eq]	54.2 kg
— global warming potential, (after end of life cycle) [CO2 eq]	-0.723 kg
Highest safety class achievable in safety mode	
• Performance level according to ISO 13849-1	PLe
• SIL acc. to IEC 61508	SIL 3
Probability of failure (for service life of 20 years and repair time of 100 hours)	
— Low demand mode: PFDavg in accordance with SIL3	< 2.00E-05
— High demand/continuous mode: PFH in accordance with SIL3	< 1.00E-09 up to an operational altitude of 3 000 m or < 2.00E-09 at an operating altitude greater than 3 000 m up to 5 000 m
product functions / security / header	
signed firmware update	Yes
Secure Boot	Yes
safely removing data	No
Ambient conditions	
Free fall	
• Fall height, max.	0.3 m; five times, in product package
Ambient temperature during operation	
• min.	-20 °C; No condensation
• max.	40 °C; at max. voltages and max. specifications
• horizontal installation, min.	-20 °C; No condensation
• horizontal installation, max.	60 °C; at rated voltages, 50 % of max. specification and alternate IO active
• vertical installation, min.	-20 °C; No condensation
• vertical installation, max.	50 °C; at rated voltages, 50 % of max. specification and alternate IO active
Ambient temperature during storage/transportation	
• min.	-40 °C
• max.	70 °C
Air pressure acc. to IEC 60068-2-13	
• Operation, min.	540 hPa
• Operation, max.	1 140 hPa
• Storage/transport, min.	540 hPa
• Storage/transport, max.	1 140 hPa
Altitude during operation relating to sea level	
• Installation altitude, min.	-1 000 m
• Installation altitude, max.	5 000 m; Restrictions for installation altitudes > 2 000 m, see manual
Relative humidity	
• Operation, max.	95 %; no condensation
Vibrations	
• Vibration resistance during operation acc. to IEC 60068-2-6	3.5 mm from 5 - 8.4 Hz, 1g from 8.4 - 150 Hz
• Operation, tested according to IEC 60068-2-6	Yes
Shock testing	
• tested according to IEC 60068-2-27	Yes; IEC 68, Part 2-27 half-sine: strength of the shock 15 g (peak value), duration 11 ms
Pollutant concentrations	
• SO2 at RH < 60% without condensation	SO2: < 0.5 ppm; H2S: < 0.1 ppm; RH < 60 % condensation-free
configuration / header	
configuration / programming / header	
Programming language	
— LAD	Yes; incl. failsafe
— FBD	Yes; incl. failsafe
— SCL	Yes
Know-how protection	
• User program protection/password protection	Yes
Access protection	
• protection of confidential configuration data	Yes

- Protection level: Write protection Yes
- Protection level: Read/write protection Yes
- Protection level: Write protection for Failsafe Yes
- Protection level: Complete protection Yes
- User administration Yes; device-wide
- Number of users 100
- Number of groups 100
- Number of roles 50

programming / cycle time monitoring / header	
• adjustable	Yes

Dimensions	
Width	80 mm
Height	125 mm
Depth	100 mm

Weights	
Weight, approx.	352 g

Classifications			
		Version	Classification
	eClass	14	27-24-22-07
	eClass	12	27-24-22-07
	eClass	9.1	27-24-22-07
	eClass	9	27-24-22-07
	eClass	8	27-24-22-07
	eClass	7.1	27-24-22-07
	eClass	6	27-24-22-07
	ETIM	10	EC000236
	ETIM	9	EC000236
	ETIM	8	EC000236
	ETIM	7	EC000236

Approvals / Certificates

General Product Approval



[KC](#)

[Miscellaneous](#)

[Manufacturer Declaration](#)



General Product Approval	EMV	For use in hazardous locations
--------------------------	-----	--------------------------------

[TUEV](#)

[KC](#)



[CCC-Ex](#)

Functional Safety	Environment	Industrial Communication
-------------------	-------------	--------------------------

[Type Examination Certificate](#)

[TUEV](#)



[PROFINET](#)

last modified:

7/23/2025