



spare part SIMATIC S7-300, CPU 312C compact CPU with MPI, 10 DI/6 DO, 2 high-speed counters (10 kHz) integrated power supply 24 V DC, work memory 64 KB, front connector (1x 40-pole) and Micro Memory Card required

General information	
Product type designation	CPU 312C
HW functional status	01
Firmware version	V3.3
Engineering with	
• Programming package	STEP 7 V5.5 + SP1 or higher or STEP 7 V5.3 + SP2 or higher with HSP 203
Supply voltage	
Rated value (DC)	24 V
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V
external protection for power supply lines (recommendation)	Miniature circuit breaker, type C; min. 2 A; miniature circuit breaker type B, min. 4 A
Mains buffering	
• Mains/voltage failure stored energy time	5 ms
• Repeat rate, min.	1 s
Load voltage L+	
Digital outputs	
— Rated value (DC)	24 V
— Reverse polarity protection	No
Input current	
Current consumption (rated value)	570 mA
Current consumption (in no-load operation), typ.	90 mA
Inrush current, typ.	5 A
I^2t	0.7 A ² ·s
Digital outputs	
• from load voltage L+, max.	25 mA
Power loss	
Power loss, typ.	8 W
Memory	
Work memory	
• integrated	64 kbyte
• expandable	No
Load memory	
• Plug-in (MMC)	Yes
• Plug-in (MMC), max.	8 Mbyte
• Data management on MMC (after last programming), min.	10 a
Backup	
• present	Yes; Guaranteed by MMC (maintenance-free)
• without battery	Yes; Program and data

CPU processing times	
for bit operations, typ.	0.1 µs
for word operations, typ.	0.24 µs
for fixed point arithmetic, typ.	0.32 µs
for floating point arithmetic, typ.	1.1 µs
CPU-blocks	
Number of blocks (total)	1 024; (DBs, FCs, FBs); the maximum number of loadable blocks can be reduced by the MMC used.
DB	
• Number, max.	1 024; Number range: 1 to 16000
• Size, max.	64 kbyte
FB	
• Number, max.	1 024; Number range: 0 to 7999
• Size, max.	64 kbyte
FC	
• Number, max.	1 024; Number range: 0 to 7999
• Size, max.	64 kbyte
OB	
• Number, max.	see instruction list
• Size, max.	64 kbyte
• Number of free cycle OBs	1; OB 1
• Number of time alarm OBs	1; OB 10
• Number of delay alarm OBs	2; OB 20, 21
• Number of cyclic interrupt OBs	4; OB 32, 33, 34, 35
• Number of process alarm OBs	1; OB 40
• Number of startup OBs	1; OB 100
• Number of asynchronous error OBs	4; OB 80, 82, 85, 87
• Number of synchronous error OBs	2; OB 121, 122
Nesting depth	
• per priority class	16
• additional within an error OB	4
Counters, timers and their retentivity	
S7 counter	
• Number	256
Retentivity	
— adjustable	Yes
— preset	Z 0 to Z 7
Counting range	
— lower limit	0
— upper limit	999
IEC counter	
• present	Yes
• Type	SFB
• Number	Unlimited (limited only by RAM capacity)
S7 times	
• Number	256
Retentivity	
— adjustable	Yes
— preset	No retentivity
Time range	
— lower limit	10 ms
— upper limit	9 990 s
IEC timer	
• present	Yes
• Type	SFB
• Number	Unlimited (limited only by RAM capacity)
Data areas and their retentivity	
Retentive data area (incl. timers, counters, flags), max.	64 kbyte
Flag	
• Size, max.	256 byte
• Retentivity available	Yes; MB 0 to MB 255

<ul style="list-style-type: none"> • Retentivity preset 	MB 0 to MB 15
<ul style="list-style-type: none"> • Number of clock memories 	8; 1 memory byte
Data blocks	
<ul style="list-style-type: none"> • Retentivity adjustable 	Yes; via non-retain property on DB
<ul style="list-style-type: none"> • Retentivity preset 	Yes
Local data	
<ul style="list-style-type: none"> • per priority class, max. 	32 kbyte; Max. 2048 bytes per block
Address area	
I/O address area	
<ul style="list-style-type: none"> • Inputs 	1 024 byte
<ul style="list-style-type: none"> • Outputs 	1 024 byte
of which distributed	
<ul style="list-style-type: none"> — Inputs 	none
<ul style="list-style-type: none"> — Outputs 	none
Process image	
<ul style="list-style-type: none"> • Inputs 	1 024 byte
<ul style="list-style-type: none"> • Outputs 	1 024 byte
<ul style="list-style-type: none"> • Inputs, adjustable 	1 024 byte
<ul style="list-style-type: none"> • Outputs, adjustable 	1 024 byte
<ul style="list-style-type: none"> • Inputs, default 	128 byte
<ul style="list-style-type: none"> • Outputs, default 	128 byte
Default addresses of the integrated channels	
<ul style="list-style-type: none"> — Digital inputs 	124.0 to 125.1
<ul style="list-style-type: none"> — Digital outputs 	124.0 to 124.5
Digital channels	
<ul style="list-style-type: none"> • Inputs 	266
<ul style="list-style-type: none"> — of which central 	266
<ul style="list-style-type: none"> • Outputs 	262
<ul style="list-style-type: none"> — of which central 	262
Analog channels	
<ul style="list-style-type: none"> • Inputs 	64
<ul style="list-style-type: none"> — of which central 	64
<ul style="list-style-type: none"> • Outputs 	64
<ul style="list-style-type: none"> — of which central 	64
Hardware configuration	
Number of expansion units, max.	0
Number of DP masters	
<ul style="list-style-type: none"> • integrated 	none
<ul style="list-style-type: none"> • via CP 	4
Number of operable FMs and CPs (recommended)	
<ul style="list-style-type: none"> • FM 	8
<ul style="list-style-type: none"> • CP, PtP 	8
<ul style="list-style-type: none"> • CP, LAN 	4
Rack	
<ul style="list-style-type: none"> • Racks, max. 	1
<ul style="list-style-type: none"> • Modules per rack, max. 	8
Time of day	
Clock	
<ul style="list-style-type: none"> • Software clock 	Yes
<ul style="list-style-type: none"> • retentive and synchronizable 	No; Buffered: No, Can be synchronized: Yes
<ul style="list-style-type: none"> • Deviation per day, max. 	10 s; Typ.: 2 s
<ul style="list-style-type: none"> • Behavior of the clock following POWER-ON 	the clock continues at the time of day it had when power was switched off
Operating hours counter	
<ul style="list-style-type: none"> • Number 	1
<ul style="list-style-type: none"> • Number/Number range 	0
<ul style="list-style-type: none"> • Range of values 	0 to 2 ³¹ hours (when using SFC 101)
<ul style="list-style-type: none"> • Granularity 	1 h
<ul style="list-style-type: none"> • retentive 	Yes; Must be restarted at each restart
Clock synchronization	
<ul style="list-style-type: none"> • supported 	Yes

• to MPI, master	Yes
• on MPI, device	Yes
• in AS, master	Yes
• in AS, device	No
Digital inputs	
Number of digital inputs	10
• of which inputs usable for technological functions	8
integrated channels (DI)	10
Input characteristic curve in accordance with IEC 61131, type 1	Yes
Number of simultaneously controllable inputs	
horizontal installation	
— up to 40 °C, max.	10
— up to 60 °C, max.	5
vertical installation	
— up to 40 °C, max.	5
Input voltage	
• Rated value (DC)	24 V
• for signal "0"	-3 to +5V
• for signal "1"	+15 to +30 V
Input current	
• for signal "1", typ.	8 mA
Input delay (for rated value of input voltage)	
for standard inputs	
— parameterizable	Yes; 0.1 / 0.3 / 3 / 15 ms (You can reconfigure the input delay of the standard inputs during program runtime. Please note that under certain circumstances your newly set filter time may not be effective until the next filter cycle.)
— Rated value	3 ms
for technological functions	
— at "0" to "1", max.	48 µs; Minimum pulse width/minimum pause between pulses at maximum counting frequency
Cable length	
• shielded, max.	1 000 m; 100 m for technological functions
• unshielded, max.	600 m; for technological functions: No
for technological functions	
— shielded, max.	100 m; at maximum count frequency
— unshielded, max.	not allowed
Digital outputs	
Number of digital outputs	6
• of which high-speed outputs	2; Notice: You cannot connect the fast outputs of your CPU in parallel
integrated channels (DO)	6
Short-circuit protection	Yes; Clocked electronically
• Response threshold, typ.	1 A
Limitation of inductive shutdown voltage to	L+ (-48 V)
Controlling a digital input	Yes
Switching capacity of the outputs	
• on lamp load, max.	5 W
Load resistance range	
• lower limit	48 Ω
• upper limit	4 kΩ
Output voltage	
• for signal "1", min.	L+ (-0.8 V)
Output current	
• for signal "1" rated value	500 mA
• for signal "1" permissible range, min.	5 mA
• for signal "1" permissible range, max.	0.6 A
• for signal "1" minimum load current	5 mA
• for signal "0" residual current, max.	0.5 mA
Parallel switching of two outputs	
• for uprating	No
• for redundant control of a load	Yes
Switching frequency	

<ul style="list-style-type: none"> • with resistive load, max. 	100 Hz
<ul style="list-style-type: none"> • with inductive load, max. 	0.5 Hz
<ul style="list-style-type: none"> • on lamp load, max. 	100 Hz
<ul style="list-style-type: none"> • of the pulse outputs, with resistive load, max. 	2.5 kHz
Total current of the outputs (per group)	
horizontal installation	
— up to 40 °C, max.	2 A
— up to 60 °C, max.	1.5 A
vertical installation	
— up to 40 °C, max.	1.5 A
Cable length	
<ul style="list-style-type: none"> • shielded, max. 	1 000 m
<ul style="list-style-type: none"> • unshielded, max. 	600 m
Analog inputs	
Number of analog inputs	0
integrated channels (AI)	0
Analog outputs	
integrated channels (AO)	0
Encoder	
Connectable encoders	
<ul style="list-style-type: none"> • 2-wire sensor 	Yes
— permissible quiescent current (2-wire sensor), max.	1.5 mA
Interfaces	
Number of PROFINET interfaces	0
Number of RS 485 interfaces	1; MPI
Number of RS 422 interfaces	0
1. Interface	
Interface type	Integrated RS 485 interface
Isolated	No
Interface types	
<ul style="list-style-type: none"> • RS 485 	Yes
<ul style="list-style-type: none"> • Output current of the interface, max. 	200 mA
Protocols	
<ul style="list-style-type: none"> • MPI 	Yes
<ul style="list-style-type: none"> • PROFIBUS DP master 	No
<ul style="list-style-type: none"> • PROFIBUS DP device 	No
<ul style="list-style-type: none"> • Point-to-point connection 	No
MPI	
<ul style="list-style-type: none"> • Transmission rate, max. 	187.5 kbit/s
Services	
— PG/OP communication	Yes
— Routing	No
— Global data communication	Yes
— S7 basic communication	Yes
— S7 communication	Yes; Only server, configured on one side
— S7 communication, as client	No; but via CP and loadable FB
— S7 communication, as server	Yes
Protocols	
PROFIsafe	No
communication functions / header	
PG/OP communication	Yes
Data record routing	No
Global data communication	
<ul style="list-style-type: none"> • supported 	Yes
<ul style="list-style-type: none"> • Number of GD loops, max. 	8
<ul style="list-style-type: none"> • Number of GD packets, max. 	8
<ul style="list-style-type: none"> • Number of GD packets, transmitter, max. 	8
<ul style="list-style-type: none"> • Number of GD packets, receiver, max. 	8
<ul style="list-style-type: none"> • Size of GD packets, max. 	22 byte
<ul style="list-style-type: none"> • Size of GD packet (of which consistent), max. 	22 byte

S7 basic communication	
<ul style="list-style-type: none"> supported User data per job, max. User data per job (of which consistent), max. 	Yes 76 byte 76 byte; 76 bytes (with X_SEND or X_RCV); 64 bytes (with X_PUT or X_GET as server)
S7 communication	
<ul style="list-style-type: none"> supported as server as client User data per job, max. User data per job (of which consistent), max. 	Yes Yes Yes; Via CP and loadable FB 180 byte; (with PUT/GET) 240 byte; as server
S5 compatible communication	
<ul style="list-style-type: none"> supported 	Yes; via CP and loadable FC
Number of connections	
<ul style="list-style-type: none"> overall usable for PG communication <ul style="list-style-type: none"> reserved for PG communication adjustable for PG communication, min. adjustable for PG communication, max. usable for OP communication <ul style="list-style-type: none"> reserved for OP communication adjustable for OP communication, min. adjustable for OP communication, max. usable for S7 basic communication <ul style="list-style-type: none"> reserved for S7 basic communication adjustable for S7 basic communication, min. adjustable for S7 basic communication, max. 	6 5 1 1 5 5 1 1 5 2 0 0 2
S7 message functions	
Number of login stations for message functions, max.	6; Depending on the configured connections for PG/OP and S7 basic communication
Process diagnostic messages	Yes
simultaneously active Alarm_S blocks, max.	300
Test commissioning functions	
Status block	Yes; Up to 2 simultaneously
Single step	Yes
Number of breakpoints	4
Status/control	
<ul style="list-style-type: none"> Status/control variable Variables Number of variables, max. <ul style="list-style-type: none"> of which status variables, max. of which control variables, max. 	Yes Inputs, outputs, memory bits, DB, times, counters 30 30 14
Forcing	
<ul style="list-style-type: none"> Forcing Forcing, variables Number of variables, max. 	Yes Inputs, outputs 10
Diagnostic buffer	
<ul style="list-style-type: none"> present Number of entries, max. <ul style="list-style-type: none"> adjustable of which powerfail-proof Number of entries readable in RUN, max. <ul style="list-style-type: none"> adjustable preset 	Yes 500 No 100; Only the last 100 entries are retained 499 Yes; From 10 to 499 10
Service data	
<ul style="list-style-type: none"> can be read out 	Yes
Interrupts/diagnostics/status information	
Diagnostics indication LED	
<ul style="list-style-type: none"> Status indicator digital input (green) Status indicator digital output (green) 	Yes Yes
Integrated Functions	

Counter			
• Number of counters		2; See "Technological Functions" manual	
• Counting frequency, max.		10 kHz	
Frequency measurement		Yes	
• Number of frequency meters		2; up to 10 kHz (see "Technological Functions" manual)	
controlled positioning		No	
integrated function blocks (closed-loop control)		No	
PID controller		No	
Number of pulse outputs		2; Pulse width modulation up to 2.5 kHz (see "Technological Functions" Manual)	
Limit frequency (pulse)		2.5 kHz	
Potential separation			
Potential separation digital inputs			
• Potential separation digital inputs		Yes	
• between the channels		No	
• between the channels and backplane bus		Yes	
Potential separation digital outputs			
• Potential separation digital outputs		Yes	
• between the channels		No	
• between the channels and backplane bus		Yes	
Isolation			
Isolation tested with		600 V DC	
Ambient conditions			
Ambient temperature during operation			
• min.		0 °C	
• max.		60 °C	
configuration / header			
Configuration software			
• STEP 7		Yes; STEP 7 V5.5 + SP1 or higher or STEP 7 V5.3 + SP2 or higher with HSP 203	
• STEP 7 Lite		No	
configuration / programming / header			
• Command set		see instruction list	
• Nesting levels		8	
• System functions (SFC)		see instruction list	
• System function blocks (SFB)		see instruction list	
Programming language			
— LAD		Yes	
— FBD		Yes	
— STL		Yes	
— SCL		Yes	
— GRAPH		Yes	
— HiGraph®		Yes	
Know-how protection			
• User program protection/password protection		Yes	
• Block encryption		Yes; With S7 block Privacy	
Dimensions			
Width		80 mm	
Height		125 mm	
Depth		130 mm	
Weights			
Weight, approx.		410 g	
Classifications			
		Version	Classification
	eClass	14	27-24-22-07
	eClass	12	27-24-22-07
	eClass	9.1	27-24-22-07
	eClass	9	27-24-22-07
	eClass	8	27-24-22-07

eClass	7.1	27-24-22-07
eClass	6	27-24-22-07
ETIM	10	EC000236
ETIM	9	EC000236
ETIM	8	EC000236
ETIM	7	EC000236
IDEA	4	3565
UNSPSC	15	32-15-17-05

Approvals / Certificates

General Product Approval



[Miscellaneous](#)

[Manufacturer Declaration](#)



EMV

For use in hazardous locations



[EM](#)



For use in hazardous locations

Maritime application

[Miscellaneous](#)

[CCC-Ex](#)



Maritime application



[CCS \(China Classification Society\)](#)

last modified:

4/7/2025