



Figure similar

\*\*\*spare part\*\*\* SIMATIC S7-300, digital input SM 321, isolated, 16 DI; 24 V DC, 1x 20-pole, hardware interrupt, diagnostics, suitable for isochronous mode

Supply voltage	
Load voltage L+	
• Rated value (DC)	24 V
• permissible range, lower limit (DC)	20.4 V
• permissible range, upper limit (DC)	28.8 V
• Reverse polarity protection	Yes
Input current	
from load voltage L+ (without load), max.	90 mA
from backplane bus 5 V DC, max.	130 mA
Encoder supply	
Number of outputs	2
Type of output voltage	L+ (-2.5 V)
Short-circuit protection	Yes; Electronic
additional (redundant) feed	Yes
Output current	
• Rated value	120 mA
• permissible range, lower limit	0 mA
• permissible range, upper limit	150 mA
Power loss	
Power loss, typ.	4 W
Digital inputs	
Number of digital inputs	16
Input characteristic curve in accordance with IEC 61131, type 2	Yes
Number of simultaneously controllable inputs	
horizontal installation	
— up to 40 °C, max.	16
— up to 60 °C, max.	16
vertical installation	
— up to 40 °C, max.	16
Input voltage	
• Type of input voltage	DC
• Rated value (DC)	24 V
• for signal "0"	-30 to +5 V
• for signal "1"	13 to 30V
Input current	
• for signal "1", typ.	7 mA
Input delay (for rated value of input voltage)	
for standard inputs	
— parameterizable	Yes; 0.1 / 0.5 / 3 / 15 / 20 ms

<b>Encoder connection</b>		
• Fixed current limitation for wire-break monitoring, min.	10 kΩ	
• Fixed current limitation for wire-break monitoring, max.	18 kΩ	
<b>Cable length</b>		
• shielded, max.	1 000 m	
• unshielded, max.	600 m	
<b>Encoder</b>		
<b>Connectable encoders</b>		
• 2-wire sensor	Yes	
— permissible quiescent current (2-wire sensor), max.	2 mA	
<b>Interrupts/diagnostics/status information</b>		
Alarms	Yes	
Diagnostics function	Yes; Parameterizable	
<b>Alarms</b>		
• Diagnostic alarm	Yes; Parameterizable	
• Hardware interrupt	Yes; Parameterizable	
<b>Diagnoses</b>		
• Diagnostic information readable	Yes	
• Wire-break	Yes; to I < 1 mA	
<b>Diagnostics indication LED</b>		
• Group error SF (red)	Yes	
• Status indicator digital input (green)	Yes	
• Encoder supply Vs (green)	Yes	
<b>Potential separation</b>		
<b>Potential separation digital inputs</b>		
• between the channels	No	
• between the channels, in groups of	16	
• between the channels and backplane bus	Yes; Optocoupler	
<b>Isolation</b>		
Isolation tested with	500 V DC	
<b>connection method</b>		
required front connector	20-pin	
<b>Dimensions</b>		
Width	40 mm	
Height	125 mm	
Depth	120 mm	
<b>Weights</b>		
Weight, approx.	200 g	
<b>Classifications</b>		
	<b>Version</b>	<b>Classification</b>
eClass	14	27-24-22-04
eClass	12	27-24-22-04
eClass	9.1	27-24-22-04
eClass	9	27-24-22-04
eClass	8	27-24-22-04
eClass	7.1	27-24-22-04
eClass	6	27-24-22-04
ETIM	10	EC001419
ETIM	9	EC001419
ETIM	8	EC001419
ETIM	7	EC001419
IDEA	4	3566
UNSPSC	15	32-15-17-05
<b>Approvals / Certificates</b>		
<b>General Product Approval</b>		

[Miscellaneous](#)

[Manufacturer Declaration](#)



EMV

For use in hazardous locations



[EM](#)



For use in hazardous locations

Maritime application



[Miscellaneous](#)

[CCC-Ex](#)



Maritime application



[NK / Nippon Kaiji Kyokai](#)



[CCS \(China Classification Society\)](#)

last modified:

4/7/2025