

SIMATIC S7-1500H, CPU 1517H-3 PN, central processing unit with 2 MB work memory for program and 8 MB for data, 1st interface: PROFINET RT with 2-port switch, 2nd interface: PROFINET, 3rd/4th interface: H-SYNC, SIMATIC Memory Card required



| General information | |
|--|---|
| Product type designation | CPU 1517H-3 PN |
| HW functional status | FS06 |
| Firmware version | V3.1 |
| <ul style="list-style-type: none"> FW update possible | Yes |
| Product function | |
| <ul style="list-style-type: none"> I&M data | Yes; I&M0 to I&M3 |
| <ul style="list-style-type: none"> Isochronous mode | No |
| <ul style="list-style-type: none"> SysLog | Yes |
| Engineering with | |
| <ul style="list-style-type: none"> STEP 7 TIA Portal configurable/integrated from version | V19 (FW V3.1) / V15.1 (FW V2.6) or higher |
| Display | |
| Screen diagonal [cm] | 6.1 cm |
| Control elements | |
| Number of keys | 6 |
| Mode selector switch | 1 |
| Supply voltage | |
| Rated value (DC) | 24 V |
| permissible range, lower limit (DC) | 19.2 V |
| permissible range, upper limit (DC) | 28.8 V |
| Reverse polarity protection | Yes |
| Mains buffering | |
| <ul style="list-style-type: none"> Mains/voltage failure stored energy time | 5 ms |
| <ul style="list-style-type: none"> Repeat rate, min. | 1/s |
| Input current | |
| Current consumption (rated value) | 1.5 A |
| Current consumption, max. | 1.9 A |
| Inrush current, max. | 1.9 A; Rated value |
| I^2t | 0.4 A ² ·s |
| Power | |
| Infeed power to the backplane bus | 12 W |
| Power consumption from the backplane bus (balanced) | 30 W |
| Power loss | |
| Power loss, typ. | 24 W |
| Memory | |
| Number of slots for SIMATIC memory card | 1 |
| SIMATIC memory card required | Yes |
| Work memory | |
| <ul style="list-style-type: none"> integrated (for program) | 2 Mbyte |
| <ul style="list-style-type: none"> integrated (for data) | 8 Mbyte |

| | |
|---|---|
| Load memory | |
| • Plug-in (SIMATIC Memory Card), max. | 32 Gbyte |
| Backup | |
| • maintenance-free | Yes |
| CPU processing times | |
| for bit operations, typ. | 4 ns |
| for word operations, typ. | 6 ns |
| for fixed point arithmetic, typ. | 6 ns |
| for floating point arithmetic, typ. | 24 ns |
| CPU-blocks | |
| Number of elements (total) | 12 000; Blocks (OB, FB, FC, DB) and UDTs |
| DB | |
| • Number range | Number range: 1 to 59 999 |
| • Size, max. | 8 Mbyte; For non-optimized block accesses, the max. size of the DB is 64 KB |
| FB | |
| • Number range | 0 ... 65 535 |
| • Size, max. | 1 Mbyte |
| FC | |
| • Number range | 0 ... 65 535 |
| • Size, max. | 1 Mbyte |
| OB | |
| • Size, max. | 1 Mbyte |
| • Number of free cycle OBs | 100 |
| • Number of time alarm OBs | 20 |
| • Number of delay alarm OBs | 20 |
| • Number of cyclic interrupt OBs | 20; with minimum OB 3x cycle of 1 ms |
| • Number of process alarm OBs | 50 |
| • Number of DPV1 alarm OBs | 3 |
| • Number of startup OBs | 100 |
| • Number of asynchronous error OBs | 4 |
| • Number of synchronous error OBs | 2 |
| • Number of diagnostic alarm OBs | 1 |
| Nesting depth | |
| • per priority class | 24 |
| Counters, timers and their retentivity | |
| S7 counter | |
| • Number | 2 048 |
| Retentivity | |
| — adjustable | Yes |
| IEC counter | |
| • Number | Any (only limited by the main memory) |
| Retentivity | |
| — adjustable | Yes |
| S7 times | |
| • Number | 2 048 |
| Retentivity | |
| — adjustable | Yes |
| IEC timer | |
| • Number | Any (only limited by the main memory) |
| Retentivity | |
| — adjustable | Yes |
| Data areas and their retentivity | |
| Retentive data area (incl. timers, counters, flags), max. | 768 kbyte; In total; available retentive memory for bit memories, timers, counters, DBs, and technology data (axes): 700 KB |
| Flag | |
| • Size, max. | 16 kbyte |
| • Number of clock memories | 8; 8 clock memory bit, grouped into one clock memory byte |
| Data blocks | |
| • Retentivity adjustable | Yes |
| • Retentivity preset | No |
| Local data | |

| | |
|---|---|
| <ul style="list-style-type: none"> per priority class, max. | 64 kbyte; max. 16 KB per block |
| Address area | |
| Number of IO modules | 8 192; max. number of modules / submodules |
| I/O address area | |
| <ul style="list-style-type: none"> Inputs Outputs | 32 kbyte; All inputs are in the process image 32 kbyte; All outputs are in the process image |
| per integrated IO subsystem | |
| — Inputs (volume) | 16 kbyte |
| — Outputs (volume) | 16 kbyte |
| Subprocess images | |
| <ul style="list-style-type: none"> Number of subprocess images, max. | 31 |
| Hardware configuration | |
| Number of distributed IO systems | 64; A distributed I/O system is characterized not only by the integration of distributed I/O via PROFINET, but also by the connection of I/O via IE/PB-Links. |
| Number of IO Controllers | |
| <ul style="list-style-type: none"> integrated | 1 |
| Rack | |
| <ul style="list-style-type: none"> Modules per rack, max. | 9; CPU + 2 PS + 6 CP |
| Time of day | |
| Clock | |
| <ul style="list-style-type: none"> Type Backup time Deviation per day, max. | Hardware clock 6 wk; At 40 °C ambient temperature, typically 10 s; Typ.: 2 s |
| Operating hours counter | |
| <ul style="list-style-type: none"> Number | 16 |
| Clock synchronization | |
| <ul style="list-style-type: none"> supported on Ethernet via NTP | Yes Yes |
| Interfaces | |
| Number of PROFINET interfaces | 2 |
| 1. Interface | |
| Interface types | |
| <ul style="list-style-type: none"> RJ 45 (Ethernet) Number of ports integrated switch | Yes; X1 2 Yes |
| Protocols | |
| <ul style="list-style-type: none"> IP protocol PROFINET IO Controller PROFINET IO Device SIMATIC communication Open IE communication Web server Media redundancy | Yes; IPv4 Yes No Yes; Only Server Yes; Optionally also encrypted Yes Yes |
| PROFINET IO Controller | |
| Services | |
| <ul style="list-style-type: none"> — Isochronous mode — IRT — PROFIenergy — Number of connectable IO Devices, max. — Updating times — PROFINET Security Class | No No Yes; per user program 256 The minimum value of the update time also depends on communication share set for PROFINET IO, on the number of IO devices, and on the quantity of configured user data 1 |
| Update time for RT | |
| — for send cycle of 1 ms | 1 ms to 512 ms |
| 2. Interface | |
| Interface types | |
| <ul style="list-style-type: none"> RJ 45 (Ethernet) Number of ports integrated switch | Yes; X2 1 No |
| Protocols | |

| | |
|--------------------------|--------------------------------|
| • IP protocol | Yes; IPv4 |
| • PROFINET IO Controller | No |
| • PROFINET IO Device | No |
| • SIMATIC communication | Yes; Only Server |
| • Open IE communication | Yes; Optionally also encrypted |
| • Web server | Yes |
| • Media redundancy | No |

3. Interface

| | |
|---------------------------|--|
| Interface type | Pluggable synchronization submodule (FO) |
| Plug-in interface modules | Synchronization module 6ES7960-1CB00-0AA5, 6ES7960-1FB00-0AA5 or 6ES7 960-1FE00-0AA5 |

4. Interface

| | |
|---------------------------|---|
| Interface type | Pluggable synchronization submodule (FO) |
| Plug-in interface modules | Synchronization module 6ES7960-1CB00-0AA5, 6ES7960-1FB00-0AA5 or 6ES7960-1FE00-0AA5 |

Interface types

| | |
|----------------------------------|-----|
| RJ 45 (Ethernet) | |
| • 100 Mbps | Yes |
| • Autonegotiation | Yes |
| • Autocrossing | Yes |
| • Industrial Ethernet status LED | Yes |

Protocols

| | |
|-----------|----|
| PROFIsafe | No |
|-----------|----|

Number of connections

| | |
|---|---|
| • Number of connections, max. | 320; via integrated interfaces of the CPU and connected CPs |
| • Number of connections reserved for ES/HMI/web | 10 |
| • Number of connections via integrated interfaces | 288 |
| • Number of S7 routing paths | 64 |

Redundancy mode

| | |
|-----------------------------------|-----|
| • PROFINET system redundancy (S2) | Yes |
| • PROFINET system redundancy (R1) | Yes |

Media redundancy

| | |
|--|--|
| — MRP | Yes; MRP Automanager according to IEC 62439-2 Edition 2.0 |
| — MRP interconnection, supported | Yes; as MRP ring node according to IEC 62439-2 Edition 3.0 |
| — MRPD | No |
| — Switchover time on line break, typ. | 200 ms; PROFINET MRP |
| — Number of stations in the ring, max. | 50 |

SIMATIC communication

| | |
|-------------------------------|--|
| • PG/OP communication | Yes; encryption with TLS V1.3 pre-selected |
| • S7 routing | Yes |
| • S7 communication, as server | Yes |
| • S7 communication, as client | No |

Open IE communication

| | |
|---|--|
| • TCP/IP | Yes |
| — Data length, max. | 64 kbyte |
| — several passive connections per port, supported | Yes |
| • ISO-on-TCP (RFC1006) | Yes |
| — Data length, max. | 64 kbyte |
| • UDP | Yes |
| — Data length, max. | 2 kbyte; 1 472 bytes for UDP broadcast |
| — UDP multicast | Yes; 128 multicast circuits (of which max. 5 via X1) |
| • DHCP | No |
| • DNS | Yes |
| • SNMP | Yes |
| • DCP | Yes |
| • LLDP | Yes |
| • Encryption | Yes; Optional |

Web server

| | |
|-----------|-----------------------|
| • HTTP | No |
| • HTTPS | Yes; only via Web API |
| • web API | Yes |

| | |
|--|--|
| — Number of sessions, max. | 200 |
| — number of simultaneous HTTP calls, max. | 4 |
| — HTTP request body, max. | 131 072 byte |
| OPC UA | |
| • Runtime license required | Yes; "Large" license required per CPU |
| • OPC UA Client | No |
| • OPC UA Server | Yes; Data access (read, write, subscribe), method call, custom address space |
| — Application authentication | Yes |
| — Security policies | available security policies: None, Basic128Rsa15, Basic256Rsa15, Basic256Sha256, Aes128Sha256RsaOaep, Aes256Sha256RsaPss |
| — User authentication | "anonymous" or by user name & password |
| — GDS support (certificate management) | No |
| — Number of sessions, max. | 32 |
| — Number of subscriptions per session, max. | 25 |
| — Sampling interval, min. | 25 ms |
| — Publishing interval, min. | 25 ms |
| — Number of server methods, max. | 100 |
| — Number of inputs/outputs per server method, max. | 20 |
| — Number of monitored items, recommended max. | 5 000; for 1 s sampling interval and 1 s send interval |
| — Number of server interfaces, max. | 10 of each "Server interfaces" / "Companion specification" type and 20 of the type "Reference namespace" |
| — Number of nodes for user-defined server interfaces, max. | 30 000 |
| • Alarms and Conditions | No |
| Further protocols | |
| • MODBUS | Yes; MODBUS TCP |
| S7 message functions | |
| Number of login stations for message functions, max. | 64 |
| number of subscriptions, max. | 750 |
| number of tags/attributes for subscriptions, max. | 20 000 |
| Program alarms | Yes |
| Number of configurable program messages, max. | 10 000; Program messages are generated by the "Program_Alarm" block, ProDiag or GRAPH |
| Number of loadable program messages in RUN, max. | 10 000 |
| Number of simultaneously active program alarms | |
| • Number of program alarms | 2 000 |
| • Number of alarms for system diagnostics | 1 000 |
| Test commissioning functions | |
| Joint commission (Team Engineering) | No |
| Status block | Yes; Up to 16 simultaneously |
| Single step | No |
| Number of breakpoints | 20; Breakpoints are only supported in RUN-Solo status |
| Status/control | |
| • Status/control variable | Yes |
| • Variables | Inputs/outputs, memory bits, DBs, distributed I/Os, timers, counters |
| • Number of variables, max. | |
| — of which status variables, max. | 200; per job |
| — of which control variables, max. | 200; per job |
| Forcing | |
| • Forcing | Yes |
| • Forcing, variables | Peripheral inputs/outputs |
| • Number of variables, max. | 200 |
| Diagnostic buffer | |
| • present | Yes |
| • Number of entries, max. | 3 200 |
| — of which powerfail-proof | 1 000 |
| Traces | |
| • Number of configurable Traces | 8 |
| • Memory size per trace, max. | 512 kbyte |
| Interrupts/diagnostics/status information | |
| Diagnostics indication LED | |
| • RUN/STOP LED | Yes |

| | |
|--|--|
| • ERROR LED | Yes |
| • MAINT LED | Yes |
| • Connection display LINK TX/RX | Yes |
| Supported technology objects | |
| Motion Control | No |
| Controller | |
| • PID_Compact | Yes; Universal PID controller with integrated optimization |
| • PID_3Step | Yes; PID controller with integrated optimization for valves |
| • PID-Temp | Yes; PID controller with integrated optimization for temperature |
| Counting and measuring | Yes |
| Standards, approvals, certificates | |
| Ecological footprint | |
| • environmental product declaration | Yes |
| Global warming potential | |
| — global warming potential, (total) [CO2 eq] | 570 kg |
| — global warming potential, (during production) [CO2 eq] | 96.9 kg |
| — global warming potential, (during operation) [CO2 eq] | 483 kg |
| — global warming potential, (after end of life cycle) [CO2 eq] | -9.97 kg |
| Ambient conditions | |
| Ambient temperature during operation | |
| • horizontal installation, min. | 0 °C |
| • horizontal installation, max. | 60 °C; Display: 50 °C, at an operating temperature of typically 50 °C, the display is switched off |
| • vertical installation, min. | 0 °C |
| • vertical installation, max. | 40 °C; Display: 40 °C, at an operating temperature of typically 40 °C, the display is switched off |
| Ambient temperature during storage/transportation | |
| • min. | -40 °C |
| • max. | 70 °C |
| Altitude during operation relating to sea level | |
| • Installation altitude above sea level, max. | 5 000 m; Restrictions for installation altitudes > 2 000 m, see manual |
| configuration / header | |
| configuration / programming / header | |
| Programming language | |
| — LAD | Yes |
| — FBD | Yes |
| — STL | Yes |
| — SCL | Yes |
| — CFC | Yes |
| — GRAPH | Yes |
| Know-how protection | |
| • User program protection/password protection | Yes |
| • Copy protection | No |
| • Block protection | Yes |
| Access protection | |
| • protection of confidential configuration data | Yes |
| • Password for display | Yes |
| • Protection level: Write protection | Yes |
| • Protection level: Read/write protection | Yes |
| • Protection level: Write protection for Failsafe | No |
| • Protection level: Complete protection | Yes |
| • User administration | Yes |
| programming / cycle time monitoring / header | |
| • lower limit | adjustable minimum cycle time |
| • upper limit | adjustable maximum cycle time |
| Dimensions | |
| Width | 210 mm |
| Height | 147 mm |
| Depth | 129 mm |

Weights

Weight, approx.

2 094 g; Interface modules: 2x 18 g

Classifications

| | Version | Classification |
|--------|---------|----------------|
| eClass | 14 | 27-24-22-07 |
| eClass | 12 | 27-24-22-07 |
| eClass | 9.1 | 27-24-22-07 |
| eClass | 9 | 27-24-22-07 |
| eClass | 8 | 27-24-22-07 |
| eClass | 7.1 | 27-24-22-07 |
| eClass | 6 | 27-24-22-07 |
| ETIM | 10 | EC000236 |
| ETIM | 9 | EC000236 |
| ETIM | 8 | EC000236 |
| ETIM | 7 | EC000236 |
| IDEA | 4 | 3565 |
| UNSPSC | 15 | 32-15-17-05 |

Approvals / Certificates

| General Product Approval | other | Environment |
|--------------------------|-------|-------------|
|--------------------------|-------|-------------|


[Confirmation](#)
[Environmental Con-
firmations](#)

last modified:

12/8/2024