

Siemens
EcoTech



SIMATIC S7-1500, digital input module DI 16x24 V DC AUX; 16 channels in groups of 8; for 24 V encoder; sensor supply 24 V DC; input type 2 (IEC 61131); input delay parameterizable 0.05..20 ms; isochronous mode up to 250 μ s; integrated counting function up to 20 kHz; pulse stretching; chatter monitoring; signal inversion diagnostics; hardware interrupts: front connector (screw terminals or push-in) and, if applicable, order shield set separately

General information	
Product type designation	DI 16x24 V DC HS
HW functional status	from FS01
Firmware version	V1.0.0
<ul style="list-style-type: none"> FW update possible 	Yes
Product function	
<ul style="list-style-type: none"> I&M data 	Yes; I&M0 to I&M3
<ul style="list-style-type: none"> Isochronous mode 	Yes
<ul style="list-style-type: none"> Prioritized startup 	Yes
Engineering with	
<ul style="list-style-type: none"> STEP 7 TIA Portal configurable/integrated from version 	STEP 7 V17 or higher
<ul style="list-style-type: none"> STEP 7 configurable/integrated from version 	V5.5 SP3 / -
<ul style="list-style-type: none"> PROFIBUS from GSD version/GSD revision 	V1.0 / V5.1
<ul style="list-style-type: none"> PROFINET from GSD version/GSD revision 	V2.3 / -
Operating mode	
<ul style="list-style-type: none"> DI 	Yes
<ul style="list-style-type: none"> Counter 	Yes
<ul style="list-style-type: none"> Oversampling 	Yes
<ul style="list-style-type: none"> MSI 	Yes
Supply voltage	
Rated value (DC)	24 V
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V
Reverse polarity protection	Yes
Input current	
Current consumption, max.	550 mA
Encoder supply	
Number of outputs	16; 2x 24 V DC
Short-circuit protection	Yes
24 V encoder supply	
<ul style="list-style-type: none"> 24 V 	Yes
<ul style="list-style-type: none"> Short-circuit protection 	Yes; Per group, electronic
<ul style="list-style-type: none"> Output current, max. 	150 mA; per group
<ul style="list-style-type: none"> Output current per module, max. 	300 mA
Power	
Power consumption from the backplane bus	0.6 W
Power loss	

Power loss, typ.	7 W
Digital inputs	
Number of digital inputs	16
Digital inputs, parameterizable	Yes
Source/sink input	P-reading
Input characteristic curve in accordance with IEC 61131, type 2	Yes
Pulse extension	Yes; 0.05 s, 0.1 s, 0.2 s, 0.5 s, 1 s, 2 s
Edge evaluation	Yes; Positive edge, negative edge
Signal change flutter	Yes; 2 to 32 signal changes
Flutter observation window	Yes; 0.5 s, 1 s to 100 s in 1-s steps
Digital input functions, parameterizable	
<ul style="list-style-type: none"> • Gate start/stop • Freely usable digital input • Counter <ul style="list-style-type: none"> — Number, max. — Counting frequency, max. — Counting width — Counting direction up/down • Digital input with oversampling <ul style="list-style-type: none"> — Number, max. — Values per cycle, max. — Resolution, min. 	<ul style="list-style-type: none"> Yes; software/hardware gate Yes 4; 4 totalizers max. 10 kHz or 2 totalizers max. 20 kHz + 2 totalizers max. 10 kHz 20 kHz 32 bit Yes Yes 16 16 15.625 µs
Input voltage	
<ul style="list-style-type: none"> • Rated value (DC) • for signal "0" • for signal "1" 	<ul style="list-style-type: none"> 24 V -30 to +5 V +11 to +30V
Input current	
<ul style="list-style-type: none"> • for signal "1", typ. 	9 mA
Input delay (for rated value of input voltage)	
for standard inputs	
<ul style="list-style-type: none"> — parameterizable — at "0" to "1", min. — at "0" to "1", max. — at "1" to "0", min. — at "1" to "0", max. 	<ul style="list-style-type: none"> Yes; 0.05 / 0.1 / 0.4 / 0.8 / 1.6 / 3.2 / 12.8 / 20 ms 0.05 ms 20 ms 0.05 ms 20 ms
for interrupt inputs	
<ul style="list-style-type: none"> — parameterizable 	Yes
for technological functions	
<ul style="list-style-type: none"> — parameterizable 	Yes
Cable length	
<ul style="list-style-type: none"> • shielded, max. • unshielded, max. 	<ul style="list-style-type: none"> 1 000 m; 600 m for technological functions; depending on input frequency, encoder and cable quality; max. 50 m at 20 kHz 600 m; for technological functions: No
Encoder	
Connectable encoders	
<ul style="list-style-type: none"> • 2-wire sensor — permissible quiescent current (2-wire sensor), max. 	<ul style="list-style-type: none"> Yes 2 mA
Isochronous mode	
Filtering and processing time (TCI), min.	60 µs; At 50 µs filter time
Bus cycle time (TDP), min.	250 µs
Interrupts/diagnostics/status information	
Diagnostics function	Yes
Alarms	
<ul style="list-style-type: none"> • Diagnostic alarm • Hardware interrupt 	<ul style="list-style-type: none"> Yes Yes
Diagnoses	
<ul style="list-style-type: none"> • Monitoring the supply voltage • Monitoring of encoder power supply • Wire-break • Short-circuit 	<ul style="list-style-type: none"> Yes Yes; short-circuit Yes; to I < 350 µA No

Diagnostics indication LED	
• RUN LED	Yes; green LED
• ERROR LED	Yes; red LED
• Monitoring of the supply voltage (PWR-LED)	Yes; green LED
• Channel status display	Yes; green LED
• for channel diagnostics	Yes; red LED
• for module diagnostics	Yes; red LED

Potential separation

Potential separation channels	
• between the channels	No
• between the channels, in groups of	8
• between the channels and backplane bus	Yes
• Between the channels and load voltage L+	Yes
• between the channels and the power supply of the electronics	No

Isolation

Isolation tested with	707 V DC (type test)
-----------------------	----------------------

Standards, approvals, certificates

Siemens Eco Profile (SEP)	Siemens EcoTech
Suitable for safety functions	No

Ecological footprint

• environmental product declaration	Yes
-------------------------------------	-----

Global warming potential

— global warming potential, (total) [CO2 eq]	18.9 kg
— global warming potential, (during production) [CO2 eq]	12.1 kg
— global warming potential, (during operation) [CO2 eq]	7.66 kg
— global warming potential, (after end of life cycle) [CO2 eq]	-1.02 kg

product functions / security / header

signed firmware update	No
data integrity	No

Ambient conditions

Ambient temperature during operation

• horizontal installation, min.	-30 °C
• horizontal installation, max.	60 °C
• vertical installation, min.	-30 °C
• vertical installation, max.	40 °C

Altitude during operation relating to sea level

• Installation altitude above sea level, max.	5 000 m; Restrictions for installation altitudes > 2 000 m, see manual
---	--

Dimensions

Width	35 mm
Height	147 mm
Depth	129 mm

Weights

Weight, approx.	240 g
-----------------	-------

Classifications

	Version	Classification
eClass	14	27-24-22-04
eClass	12	27-24-22-04
eClass	9.1	27-24-22-04
eClass	9	27-24-22-04
eClass	8	27-24-22-04
eClass	7.1	27-24-22-04
eClass	6	27-24-22-04
ETIM	10	EC001419
ETIM	9	EC001419
ETIM	8	EC001419

Approvals / Certificates

General Product Approval

[Miscellaneous](#)[Manufacturer Declaration](#)[KC](#)

General Product Approval

For use in hazardous locations

[FM](#)[CCC-Ex](#)[Type Examination Certificate](#)

For use in hazardous locations

Maritime application

[Miscellaneous](#)[NK / Nippon Kaiji Kyokai](#)

Maritime application

Environment

[CCS \(China Classification Society\)](#)Siemens
EcoTech

last modified:

10/23/2025