



Figure similar

SIMATIC ET 200SP Open Controller, CPU 1515SP PC2 + HMI 128PT, 8 GB RAM (basic device 6ES7677-2DB40-0AA0), 128 GB CFast with Windows 10 IoT Enterprise LTSC 2019 64-bit, S7-1500 Software Controller CPU 1505SP V2x and WinCC Runtime Advanced V17 preinstalled, with 128 PowerTags license; interfaces: 1x slot CFast, 1x slot SD/MMC, 1x connection for ET 200SP BusAdapter PROFINET, 1x 10/100/1000 Mbps Ethernet, 2x USB 3.0, 2x USB 2.0, 1x DisplayPort; documentation on CFast,

| General information | |
|--|--|
| Product type designation | CPU 1515SP PC2 |
| HW functional status | from FS04 |
| Firmware version | V20.8 |
| Engineering with | |
| <ul style="list-style-type: none"> STEP 7 TIA Portal configurable/integrated from version | V16 |
| Installed software | |
| <ul style="list-style-type: none"> Visualization Control | WinCC Runtime Advanced V16 S7-1500 Software Controller CPU 1505SP |
| Configuration control | |
| via dataset | Yes |
| Control elements | |
| Mode selector switch | 1 |
| Supply voltage | |
| Rated value (DC) | 24 V |
| permissible range, lower limit (DC) | 19.2 V |
| permissible range, upper limit (DC) | 28.8 V |
| Reverse polarity protection | Yes |
| Mains buffering | |
| <ul style="list-style-type: none"> Mains/voltage failure stored energy time | 5 ms |
| Input current | |
| Current consumption (rated value) | 1.8 A; Full processor load, incl. ET 200SP modules and using USB |
| Current consumption (in no-load operation), typ. | 0.5 A |
| Current consumption, max. | 2.9 A |
| I^2t | 0.426 A ² ·s; with starting current inrush |
| Power | |
| Active power input, max. | 43 W; incl. ET 200SP modules and using USB |
| Infeed power to the backplane bus | 8.75 W |
| Power loss | |
| Power loss, typ. | 16 W |
| Processor | |
| Processor type | Intel Atom E3940, 1.6 GHz, 4 cores |
| Memory | |
| Type of memory | DDR3L |
| Main memory | 8 GB RAM |
| CFast memory card | Yes; 128 GB flash memory |
| SIMATIC memory card required | No |
| Work memory | |
| <ul style="list-style-type: none"> integrated (for program) | 1 Mbyte |

| | |
|--|---|
| <ul style="list-style-type: none"> integrated (for data) | 5 Mbyte |
| <ul style="list-style-type: none"> integrated (for CPU function library of CPU Runtime) | 20 Mbyte |
| Load memory | |
| <ul style="list-style-type: none"> integrated (on PC mass storage) | 320 Mbyte |
| Backup | |
| <ul style="list-style-type: none"> with UPS | Yes; all memory areas declared retentive |
| <ul style="list-style-type: none"> with non-volatile memory | Yes |
| CPU-blocks | |
| Number of elements (total) | 6 000; In addition to blocks such as DBs, FBs and FCs, UDTs, global constants, etc. are also regarded as elements |
| DB | |
| <ul style="list-style-type: none"> Number, max. | 5 999; Number range: 1 to 65535 |
| <ul style="list-style-type: none"> Size, max. | 5 Mbyte |
| FB | |
| <ul style="list-style-type: none"> Number, max. | 5 998; Number range: 1 to 65535 |
| <ul style="list-style-type: none"> Size, max. | 1 024 kbyte |
| FC | |
| <ul style="list-style-type: none"> Number, max. | 5 999; Number range: 1 to 65535 |
| <ul style="list-style-type: none"> Size, max. | 1 024 kbyte |
| OB | |
| <ul style="list-style-type: none"> Size, max. | 1 024 kbyte |
| <ul style="list-style-type: none"> Number of free cycle OBs | 100 |
| <ul style="list-style-type: none"> Number of time alarm OBs | 20 |
| <ul style="list-style-type: none"> Number of delay alarm OBs | 20 |
| <ul style="list-style-type: none"> Number of cyclic interrupt OBs | 20 |
| <ul style="list-style-type: none"> Number of process alarm OBs | 50 |
| <ul style="list-style-type: none"> Number of DPV1 alarm OBs | 3 |
| <ul style="list-style-type: none"> Number of isochronous mode OBs | 1 |
| <ul style="list-style-type: none"> Number of technology synchronous alarm OBs | 2 |
| <ul style="list-style-type: none"> Number of startup OBs | 100 |
| <ul style="list-style-type: none"> Number of asynchronous error OBs | 4 |
| <ul style="list-style-type: none"> Number of synchronous error OBs | 2 |
| <ul style="list-style-type: none"> Number of diagnostic alarm OBs | 1 |
| Nesting depth | |
| <ul style="list-style-type: none"> per priority class | 24 |
| Counters, timers and their retentivity | |
| S7 counter | |
| <ul style="list-style-type: none"> Number | 2 048 |
| Retentivity | |
| <ul style="list-style-type: none"> adjustable | Yes |
| IEC counter | |
| <ul style="list-style-type: none"> Number | Any (only limited by the main memory) |
| Retentivity | |
| <ul style="list-style-type: none"> adjustable | Yes |
| S7 times | |
| <ul style="list-style-type: none"> Number | 2 048 |
| Retentivity | |
| <ul style="list-style-type: none"> adjustable | Yes |
| IEC timer | |
| <ul style="list-style-type: none"> Number | Any (only limited by the main memory) |
| Retentivity | |
| <ul style="list-style-type: none"> adjustable | Yes |
| Data areas and their retentivity | |
| Retentive data area (incl. timers, counters, flags), max. | 410 kbyte; For storage in NVRAM; for storage in mass storage 5 242 020 bytes |
| Flag | |
| <ul style="list-style-type: none"> Size, max. | 16 kbyte |
| <ul style="list-style-type: none"> Number of clock memories | 8; 8 clock memory bit, grouped into one clock memory byte |
| Data blocks | |
| <ul style="list-style-type: none"> Retentivity adjustable | Yes |
| <ul style="list-style-type: none"> Retentivity preset | No |
| Local data | |

| | |
|--|---|
| <ul style="list-style-type: none"> per priority class, max. | 64 kbyte; max. 16 KB per block |
| Address area | |
| Number of IO modules | 8 192 |
| I/O address area | |
| <ul style="list-style-type: none"> Inputs Outputs | 32 kbyte; All inputs are in the process image 32 kbyte; All outputs are in the process image |
| Subprocess images | |
| <ul style="list-style-type: none"> Number of subprocess images, max. | 32 |
| Hardware configuration | |
| Integrated power supply | Yes |
| Number of distributed IO systems | 20 |
| Number of DP masters | |
| <ul style="list-style-type: none"> Via CM | 1 |
| Number of IO Controllers | |
| <ul style="list-style-type: none"> via PC interfaces | 1 |
| Rack | |
| <ul style="list-style-type: none"> Modules per rack, max. Quantity of operable ET 200SP modules, max. Quantity of operable ET 200AL modules, max. Number of lines, max. | 64; CPU 1515SP PC + 64 modules + server module 64 16 1 |
| PtP CM | |
| <ul style="list-style-type: none"> Number of PtP CMs | the number of connectable PtP CMs is only limited by the number of available slots |
| Time of day | |
| Clock | |
| <ul style="list-style-type: none"> Type Hardware clock (real-time) Backup time Deviation per day, max. | Hardware clock Yes; Resolution: 1 s 6 wk; At 40 °C ambient temperature, typically 10 s; Typ.: 2 s |
| Clock synchronization | |
| <ul style="list-style-type: none"> supported to DP, master on Ethernet via NTP on Windows clock, device | Yes Yes Yes Yes |
| Interfaces | |
| Number of industrial Ethernet interfaces | 2 |
| Number of PROFINET interfaces | 1 |
| Number of PROFIBUS interfaces | 1 |
| Number of RS 485 interfaces | 1; Via CM DP module |
| Number of USB interfaces | 4; 2x USB 2.0, 2x USB 3.0 on front side |
| Number of SD card slots | 1 |
| Video interfaces | |
| <ul style="list-style-type: none"> Graphics interface | 1x DisplayPort |
| 1. Interface | |
| Interface type | PROFINET |
| automatic detection of transmission rate | Yes |
| Autonegotiation | Yes |
| Autocrossing | Yes |
| Number of connections | 88 |
| Interface types | |
| <ul style="list-style-type: none"> RJ 45 (Ethernet) <ul style="list-style-type: none"> Transmission rate, max. Industrial Ethernet status LED Number of ports integrated switch BusAdapter (PROFINET) | Yes; Via BusAdapter BA 2x RJ45 100 Mbit/s Yes 2 Yes Yes; Compatible BusAdapter: BA 2x RJ45, BA 2x FC, BA 2x SCRJ (from FS03, V2.2), BA SCRJ / RJ45 (from FS03, V3.1), BA SCRJ / FC (from FS03, V3.1), BA 2x LC (from FS03, V3.3), BA LC / RJ45 (from FS03, V3.3), BA LC / FC (from FS03, V3.3) |
| Protocols | |
| <ul style="list-style-type: none"> PROFINET IO Controller PROFINET IO Device | Yes Yes |

| | |
|---|---|
| • SIMATIC communication | Yes |
| • Open IE communication | Yes |
| • Web server | Yes |
| PROFINET IO Controller | |
| Services | |
| — Isochronous mode | Yes |
| — shortest clock pulse | 500 µs |
| — IRT | Yes |
| — PROFINergy | Yes |
| — Prioritized startup | Yes; max. 32 PROFINET devices; if you want to use the "Prioritized startup" functionality in STEP 7 for the PROFINET interface of the CPU, the CPU and the device must be separated by means of a switch (e.g. SCALANCE X205) |
| — Number of connectable IO Devices, max. | 128 |
| — Of which IO devices with IRT, max. | 64 |
| — of which in line, max. | 64 |
| — Number of connectable IO Devices for RT, max. | 128 |
| — of which in line, max. | 128 |
| — Number of IO Devices that can be simultaneously activated/deactivated, max. | 8 |
| — IO Devices changing during operation (partner ports), supported | Yes |
| — Number of IO Devices per tool, max. | 8 |
| — Updating times | The minimum value of the update time also depends on communication share set for PROFINET IO, on the number of IO devices, and on the quantity of configured user data |
| Update time for IRT | |
| — for send cycle of 500 µs | 500 µs to 8 ms |
| — for send cycle of 1 ms | 1 ms to 16 ms |
| — for send cycle of 2 ms | 2 ms to 32 ms |
| — for send cycle of 4 ms | 4 ms to 64 ms |
| — With IRT and parameterization of "odd" send cycles | Update time = set "odd" send clock (any multiple of 125 µs: 625 µs ... 3 875 µs) minimum cycle time start from 500 µs |
| Update time for RT | |
| — for send cycle of 500 µs | 500 µs to 256 ms |
| — for send cycle of 1 ms | 1 ms to 512 ms |
| — for send cycle of 2 ms | 2 ms to 512 ms |
| — for send cycle of 4 ms | 4 ms to 512 ms |
| Address area | |
| — Inputs, max. | 8 kbyte |
| — Outputs, max. | 8 kbyte |
| PROFINET IO Device | |
| Services | |
| — Isochronous mode | No |
| — shortest clock pulse | 500 µs |
| — IRT | Yes |
| — PROFINergy | Yes |
| — Prioritized startup | Yes |
| — Shared device | Yes |
| — Number of IO Controllers with shared device, max. | 4 |
| — Asset management record | Yes |
| 2. Interface | |
| Interface type | Integrated Ethernet interface |
| automatic detection of transmission rate | Yes |
| Autonegotiation | Yes |
| Autocrossing | Yes |
| Interface types | |
| • RJ 45 (Ethernet) | Yes; Integrated |
| — Transmission rate, max. | 1 000 Mbit/s |
| — Industrial Ethernet status LED | No |
| • Number of ports | 1 |
| 3. Interface | |
| Interface type | PROFIBUS with CM DP |
| Number of connections | 44 |

| | |
|--|--|
| Interface types | |
| • RS 485 | Yes |
| Protocols | |
| • PROFIBUS DP master | Yes |
| • PROFIBUS DP device | Yes |
| • SIMATIC communication | Yes |
| PROFIBUS DP master | |
| • max. number of DP devices | 125 |
| Services | |
| — Equidistance | No |
| — Isochronous mode | No |
| Address area | |
| — Inputs, max. | 8 kbyte |
| — Outputs, max. | 8 kbyte |
| Interface types | |
| RS 485 | |
| • Transmission rate, max. | 12 Mbit/s |
| Protocols | |
| PROFIsafe | No |
| Number of connections | |
| • Number of connections, max. | 88 |
| • Number of connections reserved for ES/HMI/web | 10 |
| • Number of S7 routing paths | 16 |
| Redundancy mode | |
| Media redundancy | |
| — MRP | Yes |
| — MRPD | Yes |
| — Switchover time on line break, typ. | 200 ms |
| — Number of stations in the ring, max. | 50 |
| SIMATIC communication | |
| • PG/OP communication | Yes |
| • S7 routing | Yes |
| • S7 communication, as server | Yes |
| • S7 communication, as client | Yes |
| • User data per job, max. | 64 kbyte; BSEND/BRCV: 64 KB; PUT/GET: 960 bytes |
| Open IE communication | |
| • TCP/IP | Yes |
| — Data length, max. | 64 kbyte |
| • ISO-on-TCP (RFC1006) | Yes |
| — Data length, max. | 64 kbyte |
| • UDP | Yes |
| — Data length, max. | 2 048 byte |
| • SNMP | Yes |
| • DCP | Yes |
| • LLDP | Yes |
| Web server | |
| • HTTP | Yes; Via Windows and PROFINET interface |
| • HTTPS | Yes; Via Windows and PROFINET interface |
| OPC UA | |
| • Runtime license required | Yes; "Small" license required |
| • OPC UA Client | Yes; From SW CPU 1505SP V2.6 |
| • OPC UA Server | Yes; Data access (read, write, subscribe), runtime license required |
| — Application authentication | Yes; Available security policies: None, Basic128Rsa15, Basic256Rsa15, Basic256Sha256 |
| — Security policies | Yes; Available security policies: None, Basic128Rsa15, Basic256Rsa15, Basic256Sha256 |
| — User authentication | Yes; "anonymous" or by user name & password |
| Further protocols | |
| • MODBUS | Yes; MODBUS TCP |
| S7 message functions | |
| Number of login stations for message functions, max. | 32 |

| | |
|--|--|
| Program alarms | Yes |
| Number of configurable program messages, max. | 10 000 |
| Number of simultaneously active program alarms | 1 000 |
| • Number of program alarms | 1 000 |
| • Number of alarms for system diagnostics | 200 |
| • Number of alarms for motion technology objects | 160 |
| Test commissioning functions | |
| Joint commission (Team Engineering) | Yes; Parallel online access possible for up to 8 engineering systems |
| Status block | Yes; up to 8 simultaneously |
| Single step | No |
| Number of breakpoints | 8 |
| Status/control | |
| • Status/control variable | Yes |
| • Variables | Inputs, outputs, memory bits, DB, times, counters |
| • Number of variables, max. | |
| — of which status variables, max. | 200 |
| — of which control variables, max. | 200 |
| Forcing | |
| • Forcing | Yes |
| • Forcing, variables | Inputs, outputs |
| • Number of variables, max. | 200 |
| Diagnostic buffer | |
| • present | Yes |
| • Number of entries, max. | 1 000 |
| — of which powerfail-proof | 300 |
| Traces | |
| • Number of configurable Traces | 4 |
| • Memory size per trace, max. | 512 kbyte |
| Interrupts/diagnostics/status information | |
| Diagnostics indication LED | |
| • RUN/STOP LED | Yes |
| • ERROR LED | Yes |
| • MAINT LED | Yes |
| Supported technology objects | |
| Motion Control | |
| • Number of available Motion Control resources for technology objects | 2 400 |
| • Required Motion Control resources | |
| — per speed-controlled axis | 40; per axis |
| — per positioning axis | 80; per axis |
| — per synchronous axis | 160; per axis |
| — per external encoder | 80; per external encoder |
| — per output cam | 20; per cam |
| — per cam track | 160; per cam track |
| — per probe | 40; per probe |
| • Positioning axis | |
| — Number of positioning axes at motion control cycle of 4 ms (typical value) | 15 |
| — Number of positioning axes at motion control cycle of 8 ms (typical value) | 30 |
| Controller | |
| • PID_Compact | Yes; Universal PID controller with integrated optimization |
| • PID_3Step | Yes; PID controller with integrated optimization for valves |
| • PID-Temp | Yes; PID controller with integrated optimization for temperature |
| Counting and measuring | |
| • High-speed counter | Yes |
| Standards, approvals, certificates | |
| CE mark | Yes |
| CSA approval | Yes |
| cULus | Yes |
| FM approval | Yes |

| | | | |
|---|---|----------------|-----------------------|
| RCM (formerly C-TICK) | Yes | | |
| Ambient conditions | | | |
| Ambient temperature during operation | | | |
| <ul style="list-style-type: none"> • min. • max. • horizontal installation, min. • horizontal installation, max. • vertical installation, min. • vertical installation, max. | <ul style="list-style-type: none"> -20 °C Up to 60 °C with max. 32 ET 200SP modules; up to 55 °C with max. 64 ET 200SP modules -20 °C 60 °C -20 °C 50 °C; With max. 32 ET 200SP modules | | |
| Ambient temperature during storage/transportation | | | |
| <ul style="list-style-type: none"> • min. • max. | <ul style="list-style-type: none"> -40 °C 70 °C | | |
| Vibrations | | | |
| <ul style="list-style-type: none"> • Operation, tested according to IEC 60068-2-6 • Transport, tested acc. to IEC 60068-2-6 | <ul style="list-style-type: none"> Yes Yes | | |
| Shock testing | | | |
| <ul style="list-style-type: none"> • tested according to IEC 60068-2-6 • tested according to IEC 60068-2-27 • tested according to IEC 60068-2-29 • Storage/transport, tested acc. to IEC 60068-2-27 | <ul style="list-style-type: none"> Yes Yes Yes Yes | | |
| Operating systems | | | |
| pre-installed operating system | Windows 10 IoT Enterprise 2016 LTSP, 64bit, MUI | | |
| configuration / header | | | |
| configuration / programming / header | | | |
| Programming language | | | |
| <ul style="list-style-type: none"> — LAD — FBD — STL — SCL — CFC — GRAPH | <ul style="list-style-type: none"> Yes Yes Yes Yes No Yes | | |
| Know-how protection | | | |
| <ul style="list-style-type: none"> • User program protection/password protection • Copy protection • Block protection | <ul style="list-style-type: none"> Yes Yes Yes | | |
| Access protection | | | |
| <ul style="list-style-type: none"> • Protection level: Write protection • Protection level: Read/write protection • Protection level: Complete protection | <ul style="list-style-type: none"> Yes Yes Yes | | |
| programming / cycle time monitoring / header | | | |
| <ul style="list-style-type: none"> • lower limit • upper limit | <ul style="list-style-type: none"> adjustable minimum cycle time adjustable maximum cycle time | | |
| Open Development interfaces | | | |
| <ul style="list-style-type: none"> • Size of ODK SO file, max. | 5.8 Mbyte | | |
| Peripherals/Options | | | |
| SD card | Optionally for additional mass storage | | |
| Dimensions | | | |
| Width | 160 mm | | |
| Height | 117 mm | | |
| Depth | 75 mm | | |
| Weights | | | |
| Weight, approx. | 0.83 kg | | |
| Classifications | | | |
| | | Version | Classification |
| | eClass | 14 | 27-24-26-07 |
| | eClass | 12 | 27-24-26-07 |
| | eClass | 9.1 | 27-24-26-07 |
| | eClass | 9 | 27-24-26-07 |

| | | |
|--------|-----|-------------|
| eClass | 8 | 27-24-26-07 |
| eClass | 7.1 | 27-24-26-07 |
| eClass | 6 | 27-24-26-07 |
| ETIM | 10 | EC001603 |
| ETIM | 9 | EC001603 |
| ETIM | 8 | EC001603 |
| ETIM | 7 | EC001603 |
| IDEA | 4 | 3565 |
| UNSPSC | 15 | 32-15-17-05 |

Approvals / Certificates

General Product Approval



[Miscellaneous](#)

[Manufacturer Declaration](#)

[Miscellaneous](#)



Maritime application

Environment



last modified:

12/8/2024