



SIMATIC S7-400, interface module IF963-TTY with TTY interface for PTP coupling with CP441 AB CP 441- AA05

Input current	
Current consumption, max.	15 mA from 3.3 V; 23 mA from 24 V
Power loss	
Power loss, typ.	0.6 W
Interfaces	
Point-to-point connection	
<ul style="list-style-type: none"> Transmission rate, max. 	19.2 kbit/s
<ul style="list-style-type: none"> Cable length, max. 	1 000 m; at 9 600 bps
Dimensions	
Width	19 mm
Height	67 mm
Depth	87 mm
Weights	
Weight, approx.	80 g

Classifications			
		Version	Classification
	eClass	14	27-24-22-08
	eClass	12	27-24-22-08
	eClass	9.1	27-24-22-08
	eClass	9	27-24-22-08
	eClass	8	27-24-22-08
	eClass	7.1	27-24-22-08
	eClass	6	27-24-22-08
	ETIM	10	EC001423
	ETIM	9	EC001423
	ETIM	8	EC001423
	ETIM	7	EC001423
	IDEA	4	3564
	UNSPSC	15	32-15-17-05

Approvals / Certificates	
General Product Approval	



[Miscellaneous](#)



[China RoHS](#)



[KC](#)

General Product Approval

For use in hazardous locations



[FM](#)



For use in hazardous locations

Maritime application

[Type Examination Certificate](#)



[CCS \(China Classification Society\)](#)

last modified:

6/7/2025 