

Data sheet for SINUMERIK Machine control panel

Article No. : 6FC5303-0AF32-0AA1



Figure similar

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Rated data

| | |
|-------------------------|--------|
| Input voltage | DC 5 V |
| Power consumption, max. | 2.5 W |

Mechanical data

Net weight 1.220 kg (2.69 lb)

Dimensions

| | |
|--------|---------------------|
| Width | 483.0 mm (19.02 in) |
| Height | 155.0 mm (6.10 in) |
| Depth | 54.0 mm (2.13 in) |

Degree of protection

| | |
|------------|------|
| Rear side | IP00 |
| Front side | IP65 |

Ambient conditions

Climate class according to EN60721-3-3 Condensation and icing excluded. Low air temperature 0 °C (32 °F).

Ambient temperature

| | |
|------------------------|--------------------------------|
| Operation on the front | 0 ... 45 °C (32 ... 113 °F) |
| Operation at the rear | 0 ... 55 °C (32 ... 131 °F) |
| Transport | -40 ... 70 °C (-40 ... 158 °F) |
| Storage | -40 ... 70 °C (-40 ... 158 °F) |

Relative humidity

| | |
|-----------|------------|
| Operation | 5 ... 90 % |
| Storage | 5 ... 95 % |
| Transport | 5 ... 95 % |

Approvals

Certificate of suitability CE, cULus, EAC, KCC, RCM