



Figure similar

Article No. : 6FC5303-0AF35-0AA0

Client order no. :  
Order no. :  
Offer no. :  
Remarks :

Item no. :  
Consignment no. :  
Project :

### Rated data

Input voltage	DC 5 V
Power consumption, max.	5.0 W

### Mechanical data

Net weight 0.860 kg (1.90 lb)

### Dimensions

Width	420.0 mm (16.54 in)
Height	120.0 mm (4.72 in)
Depth	58.0 mm (2.28 in)

### Mounting surface

Cutout width	406.0 mm (15.98 in)
Cutout height	106.0 mm (4.17 in)

### Degree of protection

Rear side	IP00
Front side	IP65

### Ambient conditions

Climate class according to EN60721-3-3 Condensation and icing excluded. Low air temperature 0 °C (32 °F).

### Ambient temperature

Operation on the front	0 ... 45 °C (32 ... 113 °F)
Operation at the rear	0 ... 50 °C (32 ... 122 °F)
Transport	-20 ... 60 °C (-4 ... 140 °F)
Storage	-20 ... 60 °C (-4 ... 140 °F)

### Relative humidity

Operation	5 ... 90 %
Storage	5 ... 95 %
Transport	5 ... 95 %

### Approvals

Certificate of suitability CE / EAC