



Figure similar

Article No. : 6FC5303-0AP02-0BA0

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Rated data

| | |
|-------------------------|---------|
| Input voltage | DC 24 V |
| Power consumption, max. | 115.0 W |

Mechanical data

| | |
|------------|--------------------|
| Net weight | 2.200 kg (4.85 lb) |
|------------|--------------------|

Dimensions

| | |
|--------------------|---------------------|
| Width | 464.0 mm (18.27 in) |
| Height | 165.0 mm (6.50 in) |
| Depth | 70.0 mm (2.76 in) |
| Installation depth | 70.0 mm (2.76 in) |

Mounting surface

| | |
|---------------|---------------------|
| Cutout width | 430.0 mm (16.93 in) |
| Cutout height | 131.0 mm (5.16 in) |

Degree of protection

| | |
|------------|------|
| Rear side | IP00 |
| Front side | IP65 |

Ambient conditions

Climate class according to EN60721-3-3 Condensation and icing excluded. Low air temperature 0 °C (32 °F).

Ambient temperature

| | |
|------------------------|--------------------------------|
| Operation on the front | 0 ... 45 °C (32 ... 113 °F) |
| Operation at the rear | 0 ... 55 °C (32 ... 131 °F) |
| Transport | -40 ... 70 °C (-40 ... 158 °F) |
| Storage | -40 ... 70 °C (-40 ... 158 °F) |

Relative humidity

| | |
|-----------|------------|
| Operation | 5 ... 90 % |
| Storage | 5 ... 90 % |
| Transport | 5 ... 90 % |

Approvals

Certificate of suitability CE / EAC / UL / UKCA