



Figure similar

Article No. : 6FC5303-0AP04-0AA0

Client order no. :  
Order no. :  
Offer no. :  
Remarks :

Item no. :  
Consignment no. :  
Project :

### Rated data

Input voltage	DC 24 V
Power consumption, max.	115.0 W

### Mechanical data

Net weight	3.400 kg (7.50 lb)
------------	--------------------

### Dimensions

Width	585.0 mm (23.03 in)
Height	265.0 mm (10.43 in)
Depth	55.0 mm (2.17 in)
Installation depth	55.0 mm (2.17 in)

### Mounting surface

Cutout width	551.0 mm (21.69 in)
Cutout height	231.0 mm (9.09 in)

### Degree of protection

Rear side	IP00
Front side	IP65

### Ambient conditions

Climate class according to EN60721-3-3 Condensation and icing excluded. Low air temperature 0 °C (32 °F).

### Ambient temperature

Operation on the front	0 ... 45 °C (32 ... 113 °F)
Operation at the rear	0 ... 55 °C (32 ... 131 °F)
Transport	-40 ... 70 °C (-40 ... 158 °F)
Storage	-40 ... 70 °C (-40 ... 158 °F)

### Relative humidity

Operation	5 ... 90 %
Storage	5 ... 90 %
Transport	5 ... 90 %

### Approvals

Certificate of suitability CE / EAC / UL / UKCA