



Figure similar

Article No. : 6FC5303-0AP51-0BA0

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Rated data

Input voltage	DC 24 V
Power consumption, max.	115.0 W

Mechanical data

Net weight	3.000 kg (6.61 lb)
------------	--------------------

Dimensions

Width	578.0 mm (22.76 in)
Height	218.0 mm (8.58 in)
Depth	75.0 mm (2.95 in)
Installation depth	75.0 mm (2.95 in)

Mounting surface

Cutout width	554.0 mm (21.81 in)
Cutout height	194.0 mm (7.64 in)

Degree of protection

Rear side	IP00
Front side	IP65

Ambient conditions

Climate class according to EN60721-3-3 Condensation and icing excluded. Low air temperature 0 °C (32 °F).

Ambient temperature

Operation on the front	0 ... 45 °C (32 ... 113 °F)
Operation at the rear	0 ... 55 °C (32 ... 131 °F)
Transport	-40 ... 70 °C (-40 ... 158 °F)
Storage	-40 ... 70 °C (-40 ... 158 °F)

Relative humidity

Operation	5 ... 90 %
Storage	5 ... 90 %
Transport	5 ... 90 %

Approvals

Certificate of suitability CE / EAC / UL / UKCA