



Figure similar

Article No. : 6FC5303-0AP51-0DA0

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Rated data

Input voltage	DC 24 V
Power consumption, max.	115.0 W

Mechanical data

Net weight	2.400 kg (5.29 lb)
------------	--------------------

Dimensions

Width	529.0 mm (20.83 in)
Height	165.0 mm (6.50 in)
Depth	70.0 mm (2.76 in)
Installation depth	70.0 mm (2.76 in)

Mounting surface

Cutout width	495.0 mm (19.49 in)
Cutout height	131.0 mm (5.16 in)

Degree of protection

Rear side	IP00
Front side	IP65

Ambient conditions

Climate class according to EN60721-3-3 Condensation and icing excluded. Low air temperature 0 °C (32 °F).

Ambient temperature

Operation on the front	0 ... 45 °C (32 ... 113 °F)
Operation at the rear	0 ... 55 °C (32 ... 131 °F)
Transport	-40 ... 70 °C (-40 ... 158 °F)
Storage	-40 ... 70 °C (-40 ... 158 °F)

Relative humidity

Operation	5 ... 90 %
Storage	5 ... 90 %
Transport	5 ... 90 %

Approvals

Certificate of suitability CE / EAC / UL / UKCA